

www.phoronix-test-suite.com

acer-aspire-5552-flac

Running pts/encode-flac-1.2.0.

Test Systems:

2011-10-09 16:26

Processor: AMD Phenom II N660 @ 3.00GHz (2 Cores), Motherboard: Acer JE51_DN, Chipset: AMD RS880, Memory: 2 x 2048 MB 1334MHz, Disk: 320GB Western Digital WDC WD3200BPVT-2, Graphics: ATI Mobility Radeon HD 4200 256MB (500/667MHz), Audio: Realtek ALC272X

OS: LinuxMint 11, Kernel: 3.0.4.10811a (x86_64), Desktop: GNOME 2.32.1, Display Server: X Server 1.10.1, Display Driver: fglrx 8.88.7 Catalyst 11.8, Compiler: GCC 4.5.2, File-System: ext4, Screen Resolution: 1366x768

System Notes: AMD CnQ was enabled. This was running on battery power.

amd 1090t linuxease.com

Processor: AMD Phenom II X6 1090T @ 3.20GHz (6 Cores), Motherboard: MSI 870S-G54 (MS-7599) v3.0, Chipset:


acer-aspire-5552-flac

ATI RX780/RX790, Memory: 8192MB, Disk: 1000GB Seagate ST31000528AS, Graphics: ATI Radeon HD 3450 512MB, Audio: Realtek ALC892

OS: LinuxMint 10, Kernel: 2.6.35-22-generic (x86_64), Desktop: GNOME 2.32.0, Display Server: X Server 1.9.0, Display Driver: fglrx 8.78.30, OpenGL: 3.3.10237, Compiler: GCC 4.4.5, File-System: ext4, Screen Resolution: 1024x768

System Notes: Compiz was running on this system. AMD CnQ was enabled.

	2011-10-09 16:26	amd 1090t linuxease.com
FLAC Audio Encoding - WAV To FLAC (sec)	**8.72**	**7.61**
Normalized	87.27%	100%
Standard Deviation	0.8%	0.9%



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 07:33.