

www.phoronix-test-suite.com

Calxeda ARM Server Sensor Monitoring

Testing out the node power and SoC temperatures of a Calxeda node as exposed over IPMI and automatically monitored via the Phoronix Test Suite. Tests on both 1.1GHz and 1.4GHz nodes. Benchmarking by Michael Larabel of Phoronix.com.

Test Systems:

1.1GHz Calxeda Node

1.4GHz Calxeda Node

Processor: ARMv7 rev 0 (4 Cores), Motherboard: Highbank, Memory: 4096MB, Disk: 256GB SAMSUNG MZ7PC256

OS: Ubuntu 12.10, Kernel: 3.5.0-1000-highbank (armv7l), Compiler: GCC 4.7, File-System: ext4

Compiler Notes: --build=arm-linux-gnueabihf --disable-libitm --disable-sjlj-exceptions --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-languages=c,c++,go,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch=armv7-a --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v

Calxeda ARM Server Sensor Monitoring

1.1GHz Calxeda Linaro 13.01


Processor: ARMv7 rev 0 (4 Cores), Motherboard: Highbank, Memory: 4096MB, Disk: 256GB SAMSUNG MZ7PC256

OS: Ubuntu 13.04, Kernel: 3.5.0-1000-highbank (armv7l), Compiler: GCC 4.7, File-System: ext4


Compiler Notes: --build=arm-linux-gnueabihf --disable-cloog-version-check --disable-libitm --disable-ppl-version-check --disable-sjlj-exceptions --disable-werror --enable-checking=release --enable-clocale=gnu --enable-cloog-backend=ppl --enable-gnu-unique-object --enable-languages=c,c++,go,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch=armv7-a --with-cloog --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v

	1.1GHz Calxeda Node	1.4GHz Calxeda Node	1.1GHz Calxeda Linaro 13.01
OpenSSL - R.4.b.P (Signs/sec)	**4.18**	**5.38**	4.20
Normalized	77.7%	100%	78.07%
Standard Deviation	1.2%	0.9%	0%
FFTE - N.6.1.C.F.R (MFLOPS)	**507.06**	**644.79**	507.17
Normalized	78.64%	100%	78.66%
Standard Deviation	0%	0%	0.1%
POV-Ray - Total Time (sec)	5450	**4315**	**5595**
Normalized	79.17%	100%	77.12%
Smallpt - G.I.R.1.S (sec)	**1337**	**1036**	1312
Normalized	77.49%	100%	78.96%
Standard Deviation	0.1%	0.1%	0.1%
Apache Benchmark - S.W.P.S (Reqs/sec)	**4184**	**5211**	4340
Normalized	80.29%	100%	83.28%
Standard Deviation	1.5%	0.4%	0.3%
C-Ray - Total Time (sec)	**392.28**	**305.15**	386.45
Normalized	77.79%	100%	78.96%
Standard Deviation	0.1%	0.2%	0.1%


Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring



Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring




Calxeda ARM Server Sensor Monitoring


These geometric means are based upon test groupings / test suites for this result file.



Geometric mean based upon tests: pts/c-ray, pts/apache and pts/openssl




Geometric mean based upon tests: pts/apache, pts/c-ray, pts/openssl and pts/povray




Geometric mean based upon tests: pts/c-ray, pts/povray and pts/smallpt


Calxeda ARM Server Sensor Monitoring



Geometric mean based upon tests: pts/apache and pts/openssl




Geometric mean based upon tests: pts/c-ray, pts/povray and pts/smallpt



Geometric mean based upon tests: pts/c-ray and pts/povray


Calxeda ARM Server Sensor Monitoring



Geometric mean based upon tests: pts/c-ray, pts/povray and pts/smallpt



Geometric mean based upon tests: pts/apache and pts/openssl



Geometric mean based upon tests: pts/c-ray, pts/povray and pts/openssl

This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 04:37.