

www.phoronix-test-suite.com

openssl-test-oct21

Intel Celeron 2955U testing with a Acer EA50_HW and Intel Haswell-ULT IGP on LinuxMint 17.2 via the Phoronix Test Suite.

Test Systems:

openssl

Processor: Intel Celeron 2955U @ 1.40GHz (2 Cores), Motherboard: Acer EA50_HW, Chipset: Intel Haswell-ULT DRAM, Memory: 1 x 4096 MB DDR3-1600MHz Kingston, Disk: 500GB Seagate ST500LT012-9WS14, Graphics: Intel Haswell-ULT IGP (1000MHz), Audio: Intel Haswell-ULT HD Audio, Network: Broadcom NetXtreme BCM57786 Gigabit PCIe + Qualcomm Atheros QCA9565 / AR9565

OS: LinuxMint 17.2, Kernel: 3.16.0-38-generic (x86_64), Desktop: Cinnamon 2.6.11, Display Server: X Server 1.15.1, Display Driver: intel 2.99.910, OpenGL: 3.3 Mesa 10.1.3, Compiler: GCC 4.8.4, File-System: SquashFS, Screen Resolution: 1366x768


Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-libmudflap --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug

openssl-test-oct21

--enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Processor Notes: Scaling Governor: intel_pstate powersave
System Notes: This was running on battery power.

	openssl
OpenSSL - R.4.b.P (Signs/sec)	97.70
Standard Deviation	2%

openssl-test-oct21



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 20:40.