

www.phoronix-test-suite.com

fiotest

2 x Intel Xeon X5660 testing with a Supermicro X8DTU and Matrox s MGA G200eW WPCM450 on openSUSE 13.2 via the Phoronix Test Suite.

Test Systems:

3000fio

Processor: 2 x Intel Xeon X5660 @ 2.80GHz (24 Cores), Motherboard: Supermicro X8DTU, Chipset: Intel 5520 I/O + ICH10R, Memory: 6 x 8192 MB 1333MHz, Disk: 160GB INTEL SSDSC2BB16 + 4 x 1000GB Western Digital WD1003FBYX-0, Graphics: LLVMpipe, Network: Intel 82576 Gigabit Connection + Endace Measurement s DAG 7.5G4 Gig

OS: openSUSE 13.2, Kernel: 3.16.7-29-default (x86_64), Desktop: KDE 4.14.9, Display Driver: modesetting 0.9.0, OpenGL: 3.0 Mesa 10.3.7 Gallium 0.4, Compiler: GCC 4.8.3, File-System: ext4, Screen Resolution: 1024x768


Compiler Notes: --build=x86_64-suse-linux --disable-libgcj --disable-libmudflap --disable-libssp --disable-libstdcxx-pch --disable-plugin --enable-__cxa_atexit --enable-checking=release --enable-languages=c,c++,objc,fortran,obj-c++,java,ada --enable-libstdcxx-allocator=new --enable-linux-futex --enable-ssp --enable-version-specific-runtime-libs --host=x86_64-suse-linux --mandir=/usr/share/man --with-arch-32=i586 --with-slibdir=/lib64 --with-tune=generic

fiotest

--without-system-libunwind
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,noatime,nobarrier,nodiratime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

	3000fio
Flexible IO Tester - Rand Read - POSIX AIO - No - No - 16KB - /data - MB/s (MB/s)	3.07
Standard Deviation	1.3%

fiotest



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 10:18.