

www.phoronix-test-suite.com

40-Way Linux PC Benchmark Comparison

40-way Linux system comparison from the benchmark lab.

Automated Executive Summary

Xeon E3-1270 v5 had the most wins, coming in first place for 30% of the tests.

Based on the geometric mean of all complete results, the fastest (Xeon E3-1245 v5) was 4.237x the speed of the slowest (Phenom II X3 710).

Test Systems:

2 x Xeon E5540

Processor: 2 x Intel Xeon E5540 @ 2.53GHz (16 Cores), Motherboard: SUN ASSY X4170, Chipset: Intel 5520 I/O + ICH10R, Memory: 18 x 2048 MB DDR3-800MHz Hyundai, Disk: 2 x 147GB Seagate ST914603SSUN146G + 6 x 300GB H106030SDSUN300G, Graphics: ASPEED ASPEED Family, Network: Intel 82575EB Gigabit Connection

OS: Ubuntu 15.04, Kernel: 4.6.0-999-generic (x86_64) 20160506, Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

A10-5800K

Processor: AMD A10-5800K APU @ 3.80GHz (4 Cores), Motherboard: Gigabyte F2A68HM-H, Chipset: AMD Family 15h, Memory: 1 x 8192 MB DDR3-1866MHz, Disk: 240GB OCZ ARC100, Graphics: ASUS AMD Radeon HD 7850 / R7 265 / R9 270 1024SP (300/150MHz), Audio: Realtek ALC887-VD, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 16.04, Kernel: 4.6.0-999-generic (x86_64) 20160505, Desktop: Unity 7.4.0, Display Server: X Server 1.18.3, Display Driver: radeon 7.7.0, OpenGL: 4.1 Mesa 11.3.0-devel (git-a1f6988 2016-05-06 xenial-oibaf-ppa) Gallium 0.4, Compiler: GCC 5.3.1 20160413, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

A10-7800

Processor: AMD A10-7800 Radeon R7 12 Compute Cores 4C+8G @ 3.50GHz (4 Cores), Motherboard: MSI A78M-E35 (MS-7721) v6.0, Chipset: AMD Family 15h, Memory: 2 x 4096 MB DDR3-1333MHz Corsair CMZ16GX3M4A1600C9, Disk: 500GB Western Digital WD5000AZRX-0, Graphics: MSI AMD Radeon R7 1024MB (351MHz), Audio: AMD Kaveri HDMI/DP, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 16.04, Kernel: 4.6.0-999-generic (x86_64) 20160505, Desktop: Unity 7.4.0, Display Server: X Server 1.18.3, Display Driver: radeon 7.7.0, OpenGL: 4.1 Mesa 11.3.0-devel (git-a1f6988 2016-05-06 xenial-oibaf-ppa) Gallium 0.4, Compiler: GCC 5.3.1 20160413, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

A10-7850K #1

Processor: AMD A10-7850K APU with Radeon R7 @ 3.70GHz (4 Cores), Motherboard: ASUS A88X-PRO, Chipset: AMD Family 15h, Memory: 2 x 2048 MB DDR3-1600MHz, Disk: 120GB INTEL SSDSC2BW12, Graphics: ASUS AMD Radeon R7 512MB (351MHz), Audio: AMD Kaveri HDMI/DP, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 16.04, Kernel: 4.4.0-6-generic (x86_64), Desktop: Unity 7.4.0, Display Server: X Server 1.17.3, Display Driver: radeon 7.6.1, OpenGL: 4.1 Mesa 11.1.2 Gallium 0.4, Compiler: GCC 7.0.0 20160507, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --disable-multilib --enable-checking=release --enable-languages=c,c++,fortran

Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

A10-7850K #2

Processor: AMD A10-7850K APU with Radeon R7 @ 3.70GHz (4 Cores), Motherboard: Gigabyte F2A88XM-D3H, Chipset: AMD Family 15h, Memory: 2 x 4096 MB DDR3-1333MHz, Disk: 120GB KINGSTON SV300S3, Graphics: AMD Radeon R7 1024MB (351MHz), Audio: AMD Kaveri HDMI/DP, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 16.04, Kernel: 4.6.0-999-generic (x86_64) 20160506, Desktop: Unity 7.4.0, Display Server: X Server 1.17.3, Display Driver: radeon 7.6.1, OpenGL: 4.1 Mesa 11.2.0-devel (git-3c9ed20 2016-02-21 xenial-oibaf-ppa) Gallium 0.4, Compiler: GCC 5.3.1 20160211, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

A10-7870K

Processor: AMD A10-7870K Radeon R7 12 Compute Cores 4C+8G @ 3.90GHz (4 Cores), Motherboard: ASUS A88XM-E, Chipset: AMD Family 15h, Memory: 2 x 8192 MB DDR3-1333MHz, Disk: 250GB Samsung SSD 850, Graphics: ASUS AMD Radeon R7 1024MB (355MHz), Audio: AMD Kaveri HDMI/DP, Network: Realtek RTL8111/8168/8411

OS: Fedora 22, Kernel: 4.6.0-0.rc6.git2.1.fc25.x86_64 (x86_64) 20160504, Desktop: GNOME Shell 3.16.4, Display Server: X Server 1.17.4, Display Driver: radeon 7.5.0, OpenGL: 3.3 Mesa 10.6.9 (git-8957b69) Gallium 0.4, Compiler: GCC 5.3.1 20160406, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-redhat-linux --disable-libgcj --disable-libunwind-exceptions --enable-__cxa_atexit --enable-bootstrap --enable-checking=release --enable-gnu-indirect-function --enable-gnu-unique-object --enable-initfini-array --enable-languages=c,c++,objc,obj-c++,fortran,ada,go,lto --enable-libmpx --enable-multilib --enable-plugin --enable-shared --enable-threads=posix --mandir=/usr/share/man --with-arch_32=i686 --with-default-libstdcxx-abi=gcc4-compatible --with-isl --with-linker-hash-style=gnu --with-tune=generic
Disk Notes: CFQ / data=ordered,relatime,rw,seclabel
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
System Notes: SELinux: Enabled.

A6-7400K

Processor: AMD A6-7400K Radeon R5 6 Compute Cores 2C+4G @ 3.50GHz (2 Cores), Motherboard: ASRock FM2A58M-VG3+ R2.0, Chipset: AMD Family 15h, Memory: 2 x 4096 MB DDR3-2132MHz Kingston, Disk: 120GB OCZ VECTOR150, Graphics: AMD Radeon R5 1024MB (351MHz), Audio: AMD FCH Azalia, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.04, Kernel: 3.19.0-15-generic (x86_64), Compiler: GCC 7.0.0 20160507, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --disable-multilib --enable-checking=release --enable-languages=c,c++,fortran
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

A8-3870

Processor: AMD A8-3870 APU @ 3.00GHz (4 Cores), Motherboard: Gigabyte GA-A75M-UD2H, Chipset: AMD Family 12h Root Complex, Memory: 2 x 2048 MB 1333MHz, Disk: 120GB INTEL SSDSC2BW12, Graphics: Gigabyte AMD

Radeon HD 6550D 512MB (282MHz), Audio: AMD BeaverCreek HDMI Audio, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.04, Kernel: 4.6.0-999-generic (x86_64) 20160506, Desktop: Unity 7.3.2, Display Server: X Server 1.17.1, Display Driver: radeon 7.5.0, Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

Core i3 2100

Processor: Intel Core i3-2100 @ 3.10GHz (4 Cores), Motherboard: MSI H61M-P31/W8 (MS-7788) v1.0, Chipset: Intel 2nd Generation Core Family DRAM, Memory: 2 x 2048 MB DDR3-1067MHz OCZ3BE1600C8LV2G, Disk: 500GB Seagate ST500DM002-1BD14, Graphics: Intel HD 2000 (1100MHz), Audio: Realtek ALC887-VD, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 16.04, Kernel: 4.6.0-999-generic (x86_64) 20160506, Display Server: X Server 1.17.3, Display Driver: intel 2.99.917, Compiler: GCC 5.3.1 20151219, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i3 2120

Processor: Intel Core i3-2120 @ 3.30GHz (4 Cores), Motherboard: BIOSTAR B75MU3B v5.0, Chipset: Intel 2nd Generation Core Family DRAM, Memory: 1 x 4096 MB DDR3-1333MHz, Disk: 2000GB Seagate ST2000DM001-1E61, Graphics: Intel HD 2000 (1100MHz), Audio: Realtek ALC662 rev1, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.10, Kernel: 4.6.0-999-generic (x86_64) 20160506, Desktop: Unity, Display Server: X Server 1.17.2, Display Driver: intel 2.99.917, OpenGL: 3.3 Mesa 11.0.2, Compiler: GCC 5.2.1 20151010, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i3 4130

Processor: Intel Core i3-4130 @ 3.40GHz (4 Cores), Motherboard: Intel DH87RL, Chipset: Intel 4th Gen Core DRAM, Memory: 2 x 1024 MB DDR3-1333MHz, Disk: 128GB TOSHIBA THNSNH12, Graphics: Intel Device 041e (1150MHz), Audio: Intel Xeon E3-1200 v3/4th, Network: Intel Connection I217-V

OS: Ubuntu 14.04, Kernel: 4.0.0-999-generic (x86_64) 20150310, Compiler: GCC 4.2.1 + Clang 3.9.0-svn267343-1~exp1, File-System: btrfs, Screen Resolution: 1024x768

Disk Notes: DEADLINE / relatime,rw,space_cache,ssd

Processor Notes: Scaling Governor: intel_pstate performance

Core i3 5010U

Processor: Intel Core i3-5010U @ 2.10GHz (4 Cores), Motherboard: Intel NUC5i3RYB, Chipset: Intel Broadwell-U-OPI, Memory: 8192MB, Disk: 256GB TS256GSSD370, Graphics: Intel Broadwell-U (900MHz), Audio: Intel Broadwell-U Audio, Network: Intel Connection + Intel Wireless 7265

OS: Ubuntu 15.04, Kernel: 4.1.0-999-generic (x86_64) 20150529, Desktop: Unity 7.3.2, Display Server: X Server 1.17.1, Display Driver: intel 2.99.917, Compiler: GCC 7.0.0 20160506, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --disable-multilib --enable-checking=release --enable-languages=c,c++,fortran
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave
System Notes: Disk Scheduler: DEADLINE.

Core i5 2400S

Processor: Intel Core i5-2400S @ 3.30GHz (4 Cores), Motherboard: ASRock Z68 Pro3, Chipset: Intel 2nd Generation Core Family DRAM, Memory: 2 x 2048 MB DDR3-1600MHz, Disk: 250GB SAMSUNG HD253GJ, Graphics: Intel Gen6 (1100MHz), Audio: Intel 6 /C200, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.04, Kernel: 3.19.0-15-generic (x86_64), Compiler: GCC 7.0.0 20160507, File-System: xfs, Screen Resolution: 1024x768

Compiler Notes: --disable-multilib --enable-checking=release --enable-languages=c,c++,fortran
Disk Notes: DEADLINE / attr2,inode64,noquota,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i5 2500K

Processor: Intel Core i5-2500K @ 3.70GHz (4 Cores), Motherboard: ASRock H61M-VG3, Chipset: Intel 2nd Generation Core Family DRAM, Memory: 2048MB, Disk: 1000GB Western Digital WD10EZRX-00A, Graphics: Intel Gen6 (1100MHz), Audio: Realtek ALC662 rev1, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 14.04, Kernel: 4.1.0-999-generic (x86_64) 20150607, Compiler: GCC 4.2.1 + Clang 3.9.0-svn267343-1~exp1, File-System: ext4, Screen Resolution: 1024x768

Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i5 3470

Processor: Intel Core i5-3470 @ 3.20GHz (4 Cores), Motherboard: ECS H61H2-I3 v1.0, Chipset: Intel Xeon E3-1200 v2/3rd, Memory: 1 x 4096 MB DDR3-1600MHz, Disk: 1000GB Western Digital WD10EZEX-00K, Graphics: Intel Gen7 (1100MHz), Audio: VIA VT1705, Monitor: VA2431, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 14.04, Kernel: 3.13.0-32-generic (x86_64), Compiler: GCC 4.2.1 + Clang 3.9.0-svn267343-1~exp1, File-System: ext4, Screen Resolution: 1920x1080

Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

Core i5 4670

Processor: Intel Core i5-4670 @ 3.80GHz (4 Cores), Motherboard: MSI B85M-P33 (MS-7817) v1.0, Chipset: Intel 4th Gen Core DRAM, Memory: 2 x 4096 MB DDR3-1600MHz CMY8GX3M2B2133C9, Disk: 63GB SanDisk SDSSDP06, Graphics: Intel HD 4600 (1200MHz), Audio: Intel Xeon E3-1200 v3/4th, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.10, Kernel: 4.6.0-999-generic (x86_64) 20160506, Display Server: X Server 1.17.2, Display Driver: intel 2.99.917, Compiler: GCC 5.2.1 20151010, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i7 3770K

Processor: Intel Core i7-3770K @ 3.90GHz (8 Cores), Motherboard: ECS Z77H2-A2X v1.0, Chipset: Intel Xeon E3-1200 v2/3rd, Memory: 8192MB, Disk: 160GB INTEL SSDSA2M160, Graphics: Intel HD 4000 (1150MHz), Audio: Realtek ALC892, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.04, Kernel: 4.1.0-999-generic (x86_64) 20150525, Desktop: Unity 7.3.2, Display Server: X Server 1.17.1, Display Driver: intel 2.99.917, Compiler: GCC 7.0.0 20160507, File-System: btrfs, Screen Resolution: 1024x768

Compiler Notes: --disable-multilib --enable-checking=release --enable-languages=c,c++,fortran
Disk Notes: DEADLINE / relatime,rw,space_cache,ssd
Processor Notes: Scaling Governor: intel_pstate powersave

Core i7 3960X

Processor: Intel Core i7-3960X @ 3.30GHz (12 Cores), Motherboard: Intel DX79SI, Chipset: Intel Xeon E5/Core, Memory: 8192MB, Disk: 120GB KINGSTON SV300S3, Graphics: Sapphire AMD Radeon HD 6770, Audio: Realtek ALC892, Network: Intel 82579LM Gigabit Connection

OS: Clear Linux 7820, Kernel: 4.5.2-202.native (x86_64), Display Server: X Server 1.18.3, Compiler: GCC 5.3.0 + Clang 3.8.0 + LLVM 3.8.0, File-System: ext4, Screen Resolution: 800x600

Compiler Notes: --build=x86_64-generic-linux --disable-multiarch --disable-multilib --disable-vtable-verify --enable-__cxa_atexit --enable-bootstrap --enable-clocale=gnu --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libmpx --enable-libstdcxx-pch --enable-lto --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-system-libunwind --with-tune=haswell
Disk Notes: CFQ / data=ordered,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq performance

Core i7 4600U

Processor: Intel Core i7-4600U @ 3.30GHz (4 Cores), Motherboard: CompuLab Intense-PC2 (IPC2), Chipset: Intel Haswell-ULT DRAM, Memory: 2 x 4096 MB DDR3-1600MHz, Disk: 120GB Micron_M500_MTFD, Graphics: Intel Haswell-ULT IGP (1100MHz), Audio: Intel Haswell-ULT HD Audio, Network: Intel Connection I218-LM + Intel Wireless 7260

OS: Ubuntu 16.04, Kernel: 4.6.0-999-generic (x86_64) 20160505, Desktop: Unity 7.4.0, Display Server: X Server 1.18.3, Display Driver: intel 2.99.917, OpenGL: 3.3 Mesa 11.3.0-devel (git-a1f6988 2016-05-06 xenial-oibaf-ppa), Compiler: GCC 5.3.1 20160413, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx

--enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i7 4770K

Processor: Intel Core i7-4770K @ 3.90GHz (8 Cores), Motherboard: Gigabyte Z97-HD3, Chipset: Intel 4th Gen Core DRAM, Memory: 2 x 4096 MB DDR3-1600MHz Kingston, Disk: 128GB Crucial_CT128MX1, Graphics: Intel HD 4600 (1250MHz), Audio: Intel Xeon E3-1200 v3/4th, Network: Realtek RTL8111/8168/8411

OS: Fedora 22, Kernel: 4.6.0-0.rc6.git2.1.fc25.x86_64 (x86_64) 20160504, Display Server: X Server 1.17.4, Display Driver: intel 2.99.917, OpenGL: 3.3 Mesa 10.6.9 (git-8957b69), Compiler: GCC 5.3.1 20160406, File-System: btrfs, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-redhat-linux --disable-libgcj --disable-libunwind-exceptions --enable-__cxa_atexit --enable-bootstrap --enable-checking=release --enable-gnu-indirect-function --enable-gnu-unique-object --enable-initfini-array --enable-languages=c,c++,objc,obj-c++,fortran,ada,go,lto --enable-libmpx --enable-multilib --enable-plugin --enable-shared --enable-threads=posix --mandir=/usr/share/man --with-arch_32=i686 --with-default-libstdcxx-abi=gcc4-compatible --with-isl --with-linker-hash-style=gnu --with-tune=generic
Disk Notes: CFQ / relatime,rw,seclabel,space_cache,ssd,subvol=/root,subvolid=257
Processor Notes: Scaling Governor: intel_pstate powersave
System Notes: SELinux: Enabled.

Core i7 4790K

Processor: Intel Core i7-4790K @ 4.40GHz (8 Cores), Motherboard: Gigabyte Z97-HD3P, Chipset: Intel 4th Gen Core DRAM, Memory: 2 x 8192 MB DDR3-1600MHz, Disk: 120GB OCZ TRION100, Graphics: Intel HD 4600 (1250MHz), Audio: Intel Xeon E3-1200 v3/4th, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 16.04, Kernel: 4.6.0-999-generic (x86_64) 20160506, Desktop: Unity 7.4.0, Display Server: X Server 1.17.3, Display Driver: intel 2.99.917, OpenGL: 3.3 Mesa 11.0.7, Compiler: GCC 5.3.1 20151219, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i7 4960X

Processor: Intel Core i7-4960X @ 4.00GHz (12 Cores), Motherboard: MSI X79MA-GD45 (MS-7738) v1.0, Chipset: Intel Xeon E7 v2/Xeon, Memory: 2 x 4096 MB DDR3-1600MHz, Disk: 1000GB Seagate ST1000DX001-1CM1, Graphics: AMD FirePro V4800 1024MB (157/300MHz), Audio: Intel C600/X79, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 14.04, Kernel: 3.18.0-999-generic (x86_64) 20141203, Compiler: GCC 4.2.1 + Clang 3.9.0-svn267343-1~exp1, File-System: btrfs, Screen Resolution: 1024x768

Disk Notes: DEADLINE / relatime,rw,space_cache
Processor Notes: Scaling Governor: intel_pstate powersave
System Notes: Disk Scheduler: DEADLINE.

Core i7 5775C

Processor: Intel Core i7-5775C @ 3.70GHz (8 Cores), Motherboard: MSI Z97-G45 GAMING (MS-7821) v1.0, Chipset: Intel Broadwell-U- DMI, Memory: 2 x 8192 MB DDR3-1800MHz, Disk: 120GB CT120BX100SSD1, Graphics: Intel

Broadwell-U (1150MHz), Audio: Intel Broadwell-U Audio, Network: Qualcomm Atheros Killer E220x Gigabit

OS: Ubuntu 16.04, Kernel: 4.6.0-999-generic (x86_64) 20160507, Desktop: Unity 7.4.0, Display Server: X Server 1.17.3, Display Driver: intel 2.99.917, OpenGL: 3.3 Mesa 11.3.0-devel (git-4b7e219 2016-02-24 xenial-oibaf-ppa), Compiler: GCC 5.3.1 20160222, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave
System Notes: Disk Scheduler: DEADLINE.

Core i7 5960X

Processor: Intel Core i7-5960X @ 3.50GHz (16 Cores), Motherboard: Gigabyte X99-UD4-CF, Chipset: Intel Xeon E7 v3/Xeon, Memory: 4 x 4096 MB 2133MHz CMK16GX4M4A2666C16, Disk: 120GB INTEL SSDSC2BW12, Graphics: AMD FirePro V7800 2048MB, Audio: Realtek ALC1150, Network: Intel Connection

OS: Debian testing, Kernel: 4.4.0-1-amd64 (x86_64), Display Server: X Server 1.18.2, Display Driver: modesetting 1.18.2, Compiler: GCC 5.3.1 20160323, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i586 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: CFQ / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i7 5960X Haswell-E

Processor: Intel Core i7-5960X @ 3.50GHz (16 Cores), Motherboard: ASRock X99 Extreme3, Chipset: Intel Xeon E5 v3/Core, Memory: 4 x 4096 MB 2400MHz, Disk: 256GB CORSAIR FORCE LX, Graphics: NVIDIA GeForce GTX 770 2048MB, Audio: Realtek ALC1150, Network: Intel Connection

OS: Ubuntu 14.10, Kernel: 4.6.0-999-generic (x86_64) 20160506, Desktop: Xfce 4.10, Display Server: X Server 1.16.0, Display Driver: nouveau 1.0.11, OpenGL: 3.3 Mesa 10.3.0 Gallium 0.4, Compiler: GCC 4.9.1, File-System: btrfs, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / relatime,rw,space_cache,ssd,subvol=/@,subvolid=257
Processor Notes: Scaling Governor: intel_pstate powersave

FX-8150

Processor: AMD FX-8150 Eight-Core @ 3.60GHz (8 Cores), Motherboard: ASUS M5A78L-M LX PLUS, Chipset: AMD RS780 + SB7x0/SB8x0/SB9x0, Memory: 1 x 8192 MB 1600MHz, Disk: 120GB Samsung SSD 840, Graphics: AMD FirePro V5800 1024MB (157/300MHz), Audio: Realtek ALC887-VD, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.10, Kernel: 4.6.0-999-generic (x86_64) 20160506, Desktop: Unity, Display Server: X Server 1.17.2, Display Driver: radeon 7.5.99, OpenGL: 3.3 Mesa 11.0.2 Gallium 0.4, Compiler: GCC 5.2.1 20151010, File-System: btrfs, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / relatime,rw,space_cache,ssd,subvol=/@,subvolid=257
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

FX-8350

Processor: AMD FX-8350 Eight-Core @ 4.00GHz (8 Cores), Motherboard: ASUS Crosshair V Formula, Chipset: AMD RD890 bridge, Memory: 2 x 4096 MB DDR3-2133MHz, Disk: 1000GB Western Digital WD10EARS-00M, Graphics: AMD FirePro V3800 512MB (157/200MHz), Audio: Realtek ALC889, Network: Intel 82583V Gigabit Connection

OS: Ubuntu 14.04, Kernel: 3.13.0-40-generic (x86_64), Compiler: GCC 4.2.1 + Clang 3.9.0-svn267343-1~exp1, File-System: ext4, Screen Resolution: 1024x768

Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
System Notes: Disk Scheduler: DEADLINE.

FX-8370

Processor: AMD FX-8370 Eight-Core @ 4.00GHz (8 Cores), Motherboard: ASRock 990FX Killer, Chipset: AMD RD890 bridge, Memory: 2 x 4096 MB DDR3-2400MHz, Disk: 120GB SPCC Solid State, Graphics: AMD FirePro V8700 1024MB (750/850MHz), Audio: Realtek ALC1150, Network: Qualcomm Atheros Killer E220x Gigabit

OS: Ubuntu 15.10, Kernel: 4.6.0-999-generic (x86_64) 20160506, Desktop: Unity, Display Server: X Server 1.17.2, Display Driver: radeon 7.5.99, OpenGL: 3.3 Mesa 11.0.2 Gallium 0.4, Compiler: GCC 5.2.1 20151010, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

FX-8370E

Processor: AMD FX-8370E Eight-Core @ 3.30GHz (8 Cores), Motherboard: ASUS M5A99FX PRO R2.0, Chipset: AMD RD890 bridge, Memory: 2 x 4096 MB DDR3-1866MHz, Disk: 120GB Samsung SSD 850, Graphics: AMD FirePro V5900 2048MB (250/500MHz), Audio: AMD SBx00 Azalia, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.04, Kernel: 3.19.0-15-generic (x86_64), Compiler: GCC 7.0.0 20160507, File-System: btrfs, Screen Resolution: 1024x768

Compiler Notes: --disable-multilib --enable-checking=release --enable-languages=c,c++,fortran
Disk Notes: DEADLINE / relatime,rw,space_cache,ssd
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

Pentium G3258

Processor: Intel Pentium G3258 @ 3.20GHz (2 Cores), Motherboard: Gigabyte H97M-D3H, Chipset: Intel 4th Gen Core DRAM, Memory: 2 x 4096 MB DDR3-1400MHz CMY8GX3M2A2400C11, Disk: 250GB SAMSUNG HD253GJ, Graphics: Intel HD (1100MHz), Audio: Intel Xeon E3-1200 v3/4th, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.10, Kernel: 4.6.0-999-generic (x86_64) 20160505, Desktop: Unity, Display Server: X Server 1.17.2, Display Driver: intel 2.99.917, OpenGL: 3.3 Mesa 11.3.0-devel (git-a1f6988 2016-05-06 wily-oibaf-ppa), Compiler: GCC 5.2.1 20151010, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Pentium G4400

Processor: Intel Pentium G4400 @ 3.30GHz (2 Cores), Motherboard: MSI B150M MORTAR (MS-7972) v2.0, Chipset: Intel Skylake, Memory: 8192MB, Disk: 120GB Samsung SSD 850, Graphics: Intel Device 1902 (1000MHz), Audio: Realtek ALC892, Network: Realtek RTL8111/8168/8411

OS: Clear Linux 7820, Kernel: 4.5.2-202.native (x86_64), Compiler: GCC 5.3.0 + Clang 3.8.0 + LLVM 3.8.0, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-generic-linux --disable-multiarch --disable-multilib --disable-vtable-verify --enable-__cxa_atexit --enable-bootstrap --enable-clocale=gnu --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libmpx --enable-libstdcxx-pch --enable-lto --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-system-libunwind --with-tune=haswell
Disk Notes: CFQ / data=ordered,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq performance

Phenom II X3 710

Processor: AMD Phenom II X3 710 @ 2.60GHz (3 Cores), Motherboard: MSI 890GXM-G65 (MS-7642) v1.0, Chipset: AMD RS880, Memory: 2 x 8192 MB 667MHz, Disk: 250GB Seagate ST3250310AS, Graphics: MSI AMD Radeon HD 4290 320MB (500/667MHz), Audio: AMD SBx00 Azalia, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 15.04, Kernel: 3.19.0-15-generic (x86_64), Compiler: GCC 7.0.0 20160507, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --disable-multilib --enable-checking=release --enable-languages=c,c++,fortran
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

Xeon E3-1231 v3

Processor: Intel Xeon E3-1231 v3 @ 3.80GHz (8 Cores), Motherboard: Gigabyte H81M-S1, Chipset: Intel Xeon E3-1200 v3 DRAM, Memory: 2 x 8192 MB DDR3-1600MHz, Disk: 120GB Samsung SSD 850, Graphics: Sapphire AMD Radeon HD 4550, Audio: Realtek ALC887-VD, Network: Realtek RTL8111/8168/8411

OS: Debian testing, Kernel: 4.3.0-1-amd64 (x86_64), Display Server: X Server 1.18.1, Display Driver: modesetting 1.18.1, Compiler: GCC 5.3.1 20160307, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i586 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: CFQ / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Xeon E3-1235L v5

Processor: Intel Xeon E3-1235L v5 @ 2.00GHz (4 Cores), Motherboard: ASRockRack C236M WS, Chipset: Intel Skylake, Memory: 8192MB, Disk: 120GB OCZ TRION150, Graphics: Intel Skylake (1000MHz), Audio: Realtek ALC1150, Network: Intel Connection

OS: Clear Linux 7820, Kernel: 4.5.2-202.native (x86_64), Display Server: X Server 1.18.3, Compiler: GCC 5.3.0 + Clang 3.8.0 + LLVM 3.8.0, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-generic-linux --disable-multiarch --disable-multilib --disable-vtable-verify --enable-__cxa_atexit --enable-bootstrap --enable-clocale=gnu --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libmpx --enable-libstdcxx-pch --enable-lto --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-system-libunwind --with-tune=haswell
Disk Notes: CFQ / data=ordered,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq performance

Xeon E3-1245 v5

Processor: Intel Xeon E3-1245 v5 @ 3.50GHz (8 Cores), Motherboard: Supermicro X11SAE-M v1.01, Chipset: Intel Skylake, Memory: 32768MB, Disk: 120GB Samsung SSD 850, Graphics: Intel Device 191d (1150MHz), Audio: Realtek ALC888-VD, Network: Intel Connection

OS: Clear Linux 7820, Kernel: 4.5.2-202.native (x86_64), Display Server: X Server 1.18.3, Compiler: GCC 5.3.0 + Clang 3.8.0 + LLVM 3.8.0, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-generic-linux --disable-multiarch --disable-multilib --disable-vtable-verify --enable-__cxa_atexit --enable-bootstrap --enable-clocale=gnu --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libmpx --enable-libstdcxx-pch --enable-lto --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-system-libunwind --with-tune=haswell
Disk Notes: CFQ / data=ordered,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq performance

Xeon E3-1260L v5

Processor: Intel Xeon E3-1260L v5 @ 2.90GHz (8 Cores), Motherboard: ASRock E3V5 WS, Chipset: Intel Skylake, Memory: 8192MB, Disk: 120GB INTEL SSDSC2BW12, Graphics: XFX NVIDIA GeForce GT 220, Audio: Realtek ALC892, Network: Intel Connection

OS: Clear Linux 7820, Kernel: 4.5.2-202.native (x86_64), Display Server: X Server 1.18.3, Compiler: GCC 5.3.0 + Clang 3.8.0 + LLVM 3.8.0, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-generic-linux --disable-multiarch --disable-multilib --disable-vtable-verify --enable-__cxa_atexit --enable-bootstrap --enable-clocale=gnu --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libmpx --enable-libstdcxx-pch --enable-lto --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-system-libunwind --with-tune=haswell
Disk Notes: CFQ / data=ordered,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq performance

Xeon E3-1270 v5

Processor: Intel Xeon E3-1270 v5 @ 4.00GHz (8 Cores), Motherboard: ASUS E3 PRO GAMING V5, Chipset: Intel Sky Lake, Memory: 2 x 4096 MB DDR4-2133MHz, Disk: 120GB Toshiba MKNSSDEC120GB, Graphics: AMD Radeon HD 5750, Audio: Realtek ALC1150, Network: Intel Connection

OS: Debian testing, Kernel: 4.4.0-1-amd64 (x86_64), Display Server: X Server 1.18.3, Display Driver: modesetting 1.18.3, Compiler: GCC 5.3.1 20160409 + Clang 3.6.2-3, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i586 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new

--with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: CFQ / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Xeon E3-1280 v5

Processor: Intel Xeon E3-1280 v5 @ 4.00GHz (8 Cores), Motherboard: MSI C236A WORKSTATION (MS-7998) v1.0, Chipset: Intel Sky Lake, Memory: 16384MB, Disk: 120GB Samsung SSD 850, Graphics: NVIDIA GeForce GTX 680 2048MB (324/324MHz), Audio: Realtek ALC1150, Network: Intel Connection

OS: Ubuntu 16.04, Kernel: 4.4.0-22-generic (x86_64), Desktop: Unity 7.4.0, Display Server: X Server 1.18.3, Display Driver: NVIDIA 364.19, OpenGL: 4.5.0, OpenCL: OpenCL 1.2 CUDA 8.0.0, Vulkan: 1.0.8, Compiler: GCC 5.3.1 20160413, File-System: ext4, Screen Resolution: 3840x2160

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Xeon E5-1680 v3

Processor: Intel Xeon E5-1680 v3 @ 3.80GHz (16 Cores), Motherboard: ASUS X99-A, Chipset: Intel Xeon E5 v3/Core, Memory: 4 x 4096 MB 2400MHz, Disk: 120GB OCZ ARC100, Graphics: eVGA NVIDIA GeForce GT 740 1024MB, Audio: Intel C610/X99, Network: Intel Connection

OS: Ubuntu 15.04, Kernel: 3.19.0-49-generic (x86_64), Compiler: GCC 7.0.0 20160507, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --disable-multilib --enable-checking=release --enable-languages=c,c++,fortran
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Xeon E5-2687W v3

Processor: Intel Xeon E5-2687W v3 @ 3.50GHz (20 Cores), Motherboard: MSI X99S SLI PLUS (MS-7885) v1.0, Chipset: Intel Xeon E7 v3/Xeon, Memory: 16384MB, Disk: PNY CS1211 120GB + 80GB INTEL SSDSCKGW08, Graphics: AMD FirePro V7900 2048MB, Audio: Realtek ALC892, Monitor: ASUS PB278, Network: Intel Connection

OS: Debian testing, Kernel: 4.5.0-1-amd64 (x86_64), Display Server: X Server 1.18.3, Display Driver: modesetting 1.18.3, OpenGL: 3.3 Mesa 11.1.3 Gallium 0.4, Compiler: GCC 5.3.1 20160409, File-System: ext4, Screen Resolution: 2560x1440

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i586 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: CFQ / data=ordered,errors=remount-ro,relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

Core i5 3210M

Processor: Intel Core i5-3210M @ 3.10GHz (4 Cores), Motherboard: Sony VAIO, Chipset: Intel 3rd Gen Core DRAM, Memory: 2 x 4096 MB DDR3, Disk: 256GB Crucial_CT256MX1, Graphics: Intel Ivybridge Mobile 1536MB, Audio: Realtek ALC275, Network: Realtek RTL8111/8168/8411 + Intel Centrino Advanced-N 6235

OS: Ubuntu 16.04, Kernel: 4.4.0-51-generic (x86_64), Display Server: X Server 1.18.4, Display Driver: intel 2.99.917, OpenGL: 3.3 Mesa 11.2.0, Vulkan: 1.0.8, Compiler: GCC 5.4.0 20160609, File-System: ext4, Screen Resolution: 1366x768

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-default-libstdcxx-abi=new --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Disk Notes: DEADLINE / data=ordered,errors=remount-ro,noatime,nodiratime,rw
Processor Notes: Scaling Governor: intel_pstate powersave

FX-8350 on Gigabyte 990FXA UD3

Processor: AMD FX-8350 Eight-Core @ 4.00GHz (8 Cores), Motherboard: Gigabyte GA-990FXA-UD3, Chipset: AMD RD9x0/RX980, Memory: 16384MB, Disk: 4001GB Western Digital WD40EZRX-00S + 240GB ADATA SX930 + 512GB ADATA SP610 + 2000GB Western Digital WD20EARX-00P + 1500GB Western Digital WD15EARS-00M, Graphics: Gigabyte AMD Radeon R9 380X / R9 M295X 4096MB, Audio: Realtek ALC889, Monitor: ASUS PB278, Network: Realtek RTL8111/8168/8411 + Intel Wireless 7260

OS: Arch Linux, Kernel: 4.8.10-1-ARCH (x86_64), Desktop: Xfce 4.12, OpenGL: 4.3 Mesa 13.0.1 Gallium 0.4, Compiler: GCC 6.2.1 20160830, File-System: ext4, Screen Resolution: 2560x1440

Kernel Notes: amdgpu.powerplay=1
Disk Notes: CFQ / data=ordered,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

40-Way Linux PC Benchmark Comparison

	SQLite - D.T.D (sec)	Normalized
2xXeon E5540	244.92	9.09%
A10-5800K	138.51	16.07%
A10-7800	618.32	3.6%
A10-7850K #1	320.20	6.95%
A10-7850K #2	94.66	23.52%
A10-7870K	97.26	22.89%
A6-7400K	87.44	25.46%
A8-3870	315.38	7.06%
Core i3 2100	566.34	3.93%
Core i3 2120	662.37	3.36%
Core i3 4130	77.84	28.6%
Core i3 5010U	58.21	38.24%
Core i5 2400S	864.00	2.58%
Core i5 2500K	331.38	6.72%
Core i5 3470	400.70	5.56%
Core i5 4670	44.91	49.57%
Core i7 3770K	32.33	68.85%
Core i7 3960X		
Core i7 4600U	141.84	15.69%
Core i7 4770K	338.81	6.57%
Core i7 4790K	33.65	66.15%
Core i7 4960X	623.06	3.57%
Core i7 5775C	49.17	45.27%
Core i7 5960X	164.39	13.54%
Core i7 5960X Haswell-E	155.50	14.32%
FX-8150	306.74	7.26%
FX-8350	859.13	2.59%
FX-8370	55.97	39.77%
FX-8370E	57.49	38.72%
Pentium G3258	566.72	3.93%
Pentium G4400	22.26	100%
Phenom II X3 710	466.61	4.77%
Xeon E3-1231 v3	25.52	87.23%
Xeon E3-1235L v5	34.24	65.01%
Xeon E3-1245 v5	23.76	93.69%
Xeon E3-1260L v5	324.23	6.87%
Xeon E3-1270 v5	558.28	3.99%
Xeon E3-1280 v5	25.41	87.6%
Xeon E5-1680 v3	124.25	17.92%
Xeon E5-2687W v3	57.45	38.75%
Core i5 3210M	144.26	15.43%
FX-8350 on Gigabyte 990FXA UD3	65.83	33.81%

40-Way Linux PC Benchmark Comparison

Standard Deviation	3.1%	0.1%	14.9%	1.2%	0%	4.1%	0.3%	0.3%	25.2%	11.8%	3.1%	0.3%	2.1%	0.5%	6.9%	3.3%	9.7%		0.3%	9.5%	9.1%	2%	1.7%	0.2%	1%	0.2%	2%	0.4%	2%	19.4%	1.4%	11.6%	1%	3.7%	0.7%	0.4%	0.2%	2.2%	0.5%	0.3%	0.7%	0.5%
LAMMPS Molecular Dynamics Simulator - Rhodopsin Protein (Loop Tim	61.32							**85.23**		46.90	41.05			37.11	**32.12**	32.57						32.30			36.94	55.03	44.83	52.08		40.82								52.06		37.33		
Normalized	52.38%							37.69%		68.49%	78.25%			86.55%	100%	98.62%						99.44%			86.95%	58.37%	71.65%	61.67%		78.69%								61.7%		86.04%		
Standard Deviation	0.4%							1%		0.7%	0.8%			0.6%	0.2%	0.2%						0.2%			0.5%	0.6%	0.2%	1.1%		0.7%								0.9%		0.2%		

FFT E-N.6.1.C.F.R (MFLOPS)	Normalized	Standard Deviation	Himeno Benchmark - P.P.S (MFLOPS)	Normalized	Standard Deviation
3846	47.57%	1.3%	1135	43.03%	0.7%
3944	48.79%	1%	712.53	27%	0.5%
3764	46.56%	1.5%	796.83	30.2%	4.4%
4162	51.48%	0.5%	907.17	34.38%	3%
3980	49.23%	1%	830.57	31.48%	7.7%
4233	52.36%	1.8%	753.02	28.54%	11.6%
3910	48.36%	0.7%	849.66	32.2%	2.7%
3656	45.23%	2.8%	542.85	20.57%	3.5%
4364	53.98%	0.8%	1275	48.33%	3.4%
4680	57.89%	0%	1318	49.96%	0.2%
5273	65.23%	0%	1084	41.1%	0.6%
3308	40.92%	0.1%	1207	45.73%	0.5%
4685	57.95%	0.7%	1372	52.01%	0.3%
4867	60.2%	0.1%	1264	47.91%	0.2%
5444	67.35%	0.3%	1336	50.63%	0.2%
5764	71.3%	0.1%	1869	70.84%	0.4%
5822	72.02%	0%	1563	59.23%	3.3%
5009	61.96%	2.3%	1416	53.65%	0%
4943	61.14%	1.1%	1613	61.13%	0.1%
5910	73.1%	0.1%	1747	66.21%	4.8%
6660	82.38%	0.3%	2161	81.91%	1.5%
5429	67.16%	0.2%	1371	51.97%	0.2%
5776	71.45%	0.2%	2116	80.18%	0.3%
5299	65.54%	0%	1794	67.98%	0.1%
5319	65.8%	0.1%	1781	67.52%	0.3%
3985	49.3%	2.9%	681.56	25.83%	0.3%
3756	46.46%	3.3%	607.26	23.02%	0.1%
3919	48.48%	5.5%	694.23	26.31%	1.4%
3692	45.67%	22.7%	719.04	27.25%	0.8%
4853	60.03%	0.1%	1592	60.35%	0.1%
			2153	81.62%	0.9%
3165	39.15%	0.6%	505.20	19.15%	0.4%
5754	71.17%	0%	1919	72.73%	0%
6271	77.57%	0.1%	2093	79.32%	0.4%
7943	98.25%	0.5%	2568	97.31%	0.7%
8084	100%	0.2%	2605	98.75%	5.6%
7834	96.9%	0.1%	2639	100%	0.4%
3794	46.93%	3%	2231	84.55%	2%
5800	71.75%	0.2%	2023	76.66%	1.9%
5226	64.65%	1.6%	1776	67.3%	0.3%
4548	56.26%	0.1%	1316	49.87%	0.4%
4022	49.75%	1.7%	671.87	25.46%	0.4%

Timed Linux Kernel Compilation - Time To Compile (sec)	106.90	248.06	238.12	277.29	221.22	212.04	**645.54**	259.99	291.86	323.39		426.43	268.91			141.83	161.35	111.08	242.05	107.36	86.23		97.32	61.76	68.70	173.17		127.70	175.45	321.40	273.83	415.57	101.50	162.89	101.11	107.76	86.44	93.32	71.13	**53.14**	317.25	141.06
Normalized	49.71%	21.41%	22.33%	19.18%	24.02%	25.06%	8.23%	20.44%	18.21%	16.43%		12.46%	19.76%			37.47%	32.93%	47.84%	21.95%	49.5%	61.63%		54.6%	86.04%	77.35%	30.69%		41.61%	30.29%	16.53%	19.41%	12.79%	52.35%	32.62%	52.56%	49.31%	61.48%	56.94%	74.71%	100%	16.75%	37.67%
Standard Deviation	2.1%	0.3%	1%	0.6%	1%	0.7%	0.4%	0.8%	0.7%	0.5%		0.4%	0.7%			3.3%	1%	2%	1.4%	1.3%	1.5%		1.7%	1.9%	2.5%	4.7%		1.6%	1.2%	1.3%	0.5%	1%	1%	0.7%	1.2%	0.8%	1.5%	1.6%	2.8%	2%	1.8%	1.7%
C-Ray - Total Time (sec)	18.39	54.12	57.06	53.35	53.36	50.76	**112.84**	43.22	70.08	66.13	61.46	79.64	45.71	54.58	48.54	24.54	28.67	22.40	56.17	22.80	19.15	23.05	22.61	12.99	12.96	32.21	33.43	25.19	30.35	55.13	46.48	67.91	23.48	37.80	24.39	24.74	19.14	26.05	11.19	**10.72**	74.50	25.50
Normalized	58.29%	19.81%	18.79%	20.09%	20.09%	21.12%	9.5%	24.8%	15.3%	16.21%	17.44%	13.46%	23.45%	19.64%	22.08%	43.68%	37.39%	47.86%	19.08%	47.02%	55.98%	46.51%	47.41%	82.53%	82.72%	33.28%	32.07%	42.56%	35.32%	19.44%	23.06%	15.79%	45.66%	28.36%	43.95%	43.33%	56.01%	41.15%	95.8%	100%	14.81%	42.04%

40-Way Linux PC Benchmark Comparison


Standard Deviation	0.1%	1.5%	0.1%	0.2%	0.8%	0.1%	0.1%	2.8%	1.7%	0.9%	0.1%	0%	0.1%	0.2%	0.1%	0.1%	0.2%	0.5%	0%	0.1%	0.1%	0.1%	0.1%	0.5%	0.3%	5.2%	0.1%	0.1%	0.1%	0.1%	0.1%	0.1%	0.1%	0.3%	0.2%	0.3%	0%	0.1%	1%	0.2%	1%	0.1%
FLAC Audio Encoding - WAV To FLAC (sec)	11.76	9.77	11.48	10.55	11.08	10.32	11.18	13.11	9.79	9.21	8.80	10.50	8.64	10.56	8.72	5.89	6.69	9.49	6.87	5.77	5.14	8.94	6.04	6.70	6.89	9.57	11.75	10.04	9.44	7.94	6.64	**15.36**	5.91	6.62	5.17	5.11	**5.01**	5.48	6.02	6.92	8.73	10.15
Normalized	42.6%	51.28%	43.64%	47.49%	45.22%	48.55%	44.81%	38.22%	51.17%	54.4%	56.93%	47.71%	57.99%	47.44%	57.45%	85.06%	74.89%	52.79%	72.93%	86.83%	97.47%	56.04%	82.95%	74.78%	72.71%	52.35%	42.64%	49.9%	53.07%	63.1%	75.45%	32.62%	84.77%	75.68%	96.91%	98.04%	100%	91.42%	83.22%	72.4%	57.39%	49.36%
Standard Deviation	0%	0.1%	0.7%	0.6%	0.7%	0.5%	0.3%	0.1%	1.6%	0.4%	0.1%	0.3%	0.3%	1.1%	0%	0.1%	0.7%	5.3%	2.3%	0.1%	1.5%	0.3%	0.1%	0.8%	2.7%	0.3%	0.1%	0.2%	0.2%	0.1%	0%	0.1%	0.4%	0.1%	0.1%	0.4%	0.3%	4.4%	1.5%	1.5%	0.3%	0.4%


	PostgreSQL pgbench - Buffer Test - Normal Load - Read Write (TPS)	Normalized	Standard Deviation	Redis - GET (Reqs/sec)
1	481.17	4.65%	6.9%	1513351
2	1138	10.99%	0.9%	1385795
3	369.44	3.57%	2.3%	1122118
4	339.63	3.28%	1.2%	1204371
5	1347	13.01%	2%	1210310
6	1336	12.91%	3.5%	1147789
7	981.26	9.48%	1.4%	1177861
8	328.18	3.17%	2.6%	1112461
9	171.65	1.66%	54.8%	1816069
10	251.01	2.43%	6.2%	1574477
11	681.44	6.58%	1.9%	1880970
12	2293	22.16%	1%	1467023
13	258.51	2.5%	40.3%	1765958
14	212.63	2.05%	1.7%	1902403
15	416.63	4.03%	3.3%	552084
16	758.41	7.33%	8%	2375702
17	3066	29.63%	3.1%	2079665
18	10349	100%	3.1%	1485164
19	732.58	7.08%	19.1%	2147712
20	639.84	6.18%	4.3%	2491926
21	1871	18.08%	15%	2399230
22	344.99	3.33%	57.1%	599355
23	3418	33.03%	2.6%	2154295
24	2490	24.06%	1.1%	633169
25	2565	24.78%	1.7%	622999
26	697.58	6.74%	7.1%	1209220
27	415.15	4.01%	1.9%	1258308
28	2364	22.84%	1.3%	500027
29	1010	9.76%	24%	1310867
30	349.05	3.37%	2.3%	1991426
31	3017	29.15%	0.7%	2732525
32	232.19	2.24%	4.2%	1021057
33	6840	66.09%	0.6%	2515137
34	3502	33.84%	4.5%	2340965
35	3491	33.73%	8.5%	3209832
36	764.50	7.39%	3.1%	3092810
37	398.48	3.85%	1.7%	3051843
38	4352	42.05%	21.3%	2989593
39	2974	28.74%	0.9%	2002672
40	4571	44.17%	3.3%	657796
41	1081	10.45%	2.4%	1487655
42	3294	31.82%	2.5%	1345169


40-Way Linux PC Benchmark Comparison


Apache Benchmark - S.W.P.S (Reqs/sec)	16393	20727	22261	19324	19715	14040	**10842**	18932	20260	20983	17346	20034	25053	30653	17592	**52502**	28817	20330	27335	22565	48265	19033	40177	18658	20324	20393	16817	19034	20831	20833	49229	41091	42014	47405	45027	19521
Normalized	31.22%	39.48%	42.4%	36.81%	37.55%	26.74%	20.65%	36.06%	38.59%	39.97%	33.04%	38.16%	47.72%	58.38%	33.51%	100%	54.89%	38.72%	52.06%	42.98%	91.93%	36.25%	76.52%	35.54%	38.71%	38.84%	32.03%	36.25%	39.68%	39.68%	81.77%	78.27%	80.02%	90.29%	85.76%	37.18%
Standard Deviation	0.7%	0.2%	0.4%	1.9%	3.2%	0.2%	0.3%	0.3%	0.7%	0.8%	0.6%	0.2%	0.3%	0.6%	0.2%	1.1%	0.8%	17.2%	0.5%	1%	4.4%	0.8%	0.1%	4.7%	0.3%	0.1%	0.1%	0.9%	1.2%	0.4%	0.1%	1%	3.4%	0.9%	0.2%	0.6%


40-Way Linux PC Benchmark Comparison



SQLite 3.8.10.2
Test Target: Default Test Directory
Seconds, Fewer Is Better
2 x Xeon E5540
SE +/- 3.84, N = 4
244.92
A10-5800K
SE +/- 0.07, N = 3
138.51
A10-7800
SE +/- 37.65, N = 6
618.32
A10-7850K #1
SE +/- 2.20, N = 3
320.20
A10-7850K #2
SE +/- 0.03, N = 3
94.66
A10-7870K
SE +/- 1.62, N = 6
97.26
A6-7400K
SE +/- 0.15, N = 3
87.44
A8-3870
SE +/- 0.57, N = 3
315.38
Core i3 2100
SE +/- 58.34, N = 6
566.34
Core i3 2120
SE +/- 31.92, N = 6
662.37
Core i3 4130
SE +/- 1.40, N = 3
77.84
Core i3 5010U
SE +/- 0.09, N = 3
58.21
Core i5 2400S
SE +/- 10.65, N = 3
864.00
Core i5 2500K
SE +/- 0.98, N = 3
331.38
Core i5 3210M
SE +/- 0.62, N = 3
144.26
Core i5 3470
SE +/- 11.29, N = 6
400.70
Core i5 4670
SE +/- 0.73, N = 4
44.91
Core i7 3770K
SE +/- 1.29, N = 6
32.33
Core i7 4600U
SE +/- 0.21, N = 3
141.84
Core i7 4770K
SE +/- 13.16, N = 6
338.81
Core i7 4790K
SE +/- 1.25, N = 6
33.65
Core i7 4960X
SE +/- 7.14, N = 3
623.06
Core i7 5775C
SE +/- 0.47, N = 3
49.17
Core i7 5960X
SE +/- 0.20, N = 3
164.39
Core i7 5960X Haswell-E
SE +/- 0.94, N = 3
155.50
FX-8150
SE +/- 0.42, N = 3
306.74
FX-8350
SE +/- 9.75, N = 3
859.13
FX-8350 on Gigabyte 990FXA UD3
SE +/- 0.17, N = 3
65.83
FX-8370
SE +/- 0.14, N = 3
55.97
FX-8370E
SE +/- 0.66, N = 3
57.49
Pentium G3258
SE +/- 44.94, N = 6
566.72
Pentium G4400
SE +/- 0.18, N = 3
22.26
Phenom II X3 710
SE +/- 22.17, N = 6
466.61
Xeon E3-1231 v3
25.52



LAMMPS Molecular Dynamics Simulator 1.0
Test: Rhodopsin Protein
Loop Time, Fewer Is Better
2 x Xeon E5540
SE +/- 0.16, N = 3
61.32
A8-3870
SE +/- 0.48, N = 3
85.23
Core i3 2120
SE +/- 0.19, N = 3
46.90
Core i3 4130
SE +/- 0.18, N = 3
41.05
Core i5 2500K
SE +/- 0.14, N = 3
37.11
Core i5 3470
SE +/- 0.05, N = 3
32.12
Core i5 4670
SE +/- 0.04, N = 3
32.57
Core i7 4960X
SE +/- 0.04, N = 3
32.30
Core i7 5960X Haswell-E
SE +/- 0.11, N = 3
36.94
FX-8150
SE +/- 0.20, N = 3
55.03
FX-8350
SE +/- 0.05, N = 3
44.83
FX-8370
SE +/- 0.32, N = 3
52.08
Pentium G3258
SE +/- 0.15, N = 3
40.82
Xeon E3-1280 v5
SE +/- 0.27, N = 3
52.06
Xeon E5-2687W v3
SE +/- 0.05, N = 3
37.33
20
40
60
80
100
1. (CXX) g++ options: -lfftw -lmpich



FFTE 5.0
Test: N=64, 1D Complex FFT Routine
MFLOPS, More Is Better
2 x Xeon E5540
SE +/- 29.69, N = 3
3845.52
A10-5800K
SE +/- 22.18, N = 3
3944.21
A10-7800
SE +/- 32.85, N = 3
3763.90
A10-7850K #1
SE +/- 12.79, N = 3
4161.70
A10-7850K #2
SE +/- 22.23, N = 3
3980.15
A10-7870K
SE +/- 45.00, N = 3
4232.96
A6-7400K
SE +/- 15.84, N = 3
3909.65
A8-3870
SE +/- 58.56, N = 3
3656.02
Core i3 2100
SE +/- 21.13, N = 3
4363.59
Core i3 2120
SE +/- 0.61, N = 3
4680.06
Core i3 4130
SE +/- 0.09, N = 3
5273.42
Core i3 5010U
SE +/- 0.96, N = 3
3307.84
Core i5 2400S
SE +/- 18.34, N = 3
4684.93
Core i5 2500K
SE +/- 2.92, N = 3
4866.90
Core i5 3210M
SE +/- 2.60, N = 3
4548.45
Core i5 3470
SE +/- 10.45, N = 3
5444.39
Core i5 4670
SE +/- 4.54, N = 3
5763.99
Core i7 3770K
SE +/- 0.33, N = 3
5822.44
Core i7 3960X
SE +/- 67.76, N = 3
5008.50
Core i7 4600U
SE +/- 31.61, N = 3
4942.57
Core i7 4770K
SE +/- 2.19, N = 3
5909.50
Core i7 4790K
SE +/- 11.18, N = 3
6659.56
Core i7 4960X
SE +/- 7.76, N = 3
5429.16
Core i7 5775C
SE +/- 6.60, N = 3
5776.35
Core i7 5960X
SE +/- 1.20, N = 3
5298.59
Core i7 5960X Haswell-E
SE +/- 2.11, N = 3
5319.04
FX-8150
SE +/- 67.62, N = 3
3985.36
FX-8350
SE +/- 71.89, N = 3
3756.13
FX-8350 on Gigabyte 990FXA UD3
SE +/- 38.45, N = 3
4021.85
FX-8370
SE +/- 87.44, N = 6
3919.16
FX-8370E
SE +/- 341.70, N = 6
3692.37
Pentium G3258
SE +/- 2.26, N = 3
4852.93
Phenom II X3 710
SE +/- 11.44, N = 3
3164.68
Xeon E3-1231 v3
5753.81



Himeno Benchmark 3.0
Poisson Pressure Solver
MFLOPS, More Is Better
2 x Xeon E5540
SE +/- 4.77, N = 3
1135.36
A10-5800K
SE +/- 2.00, N = 3
712.53
A10-7800
SE +/- 14.31, N = 6
796.83
A10-7850K #1
SE +/- 15.81, N = 3
907.17
A10-7850K #2
SE +/- 26.21, N = 6
830.57
A10-7870K
SE +/- 35.81, N = 6
753.02
A6-7400K
SE +/- 13.41, N = 3
849.66
A8-3870
SE +/- 7.73, N = 6
542.85
Core i3 2100
SE +/- 24.74, N = 3
1275.13
Core i3 2120
SE +/- 1.22, N = 3
1318.29
Core i3 4130
SE +/- 3.69, N = 3
1084.45
Core i3 5010U
SE +/- 3.47, N = 3
1206.71
Core i5 2400S
SE +/- 2.28, N = 3
1372.30
Core i5 2500K
SE +/- 1.80, N = 3
1264.06
Core i5 3210M
SE +/- 2.85, N = 3
1315.88
Core i5 3470
SE +/- 1.65, N = 3
1335.86
Core i5 4670
SE +/- 4.38, N = 3
1869.23
Core i7 3770K
SE +/- 25.68, N = 4
1562.77
Core i7 3960X
SE +/- 0.44, N = 2
1415.61
Core i7 4600U
SE +/- 1.35, N = 3
1612.81
Core i7 4770K
SE +/- 34.45, N = 6
1747.01
Core i7 4790K
SE +/- 18.32, N = 3
2161.10
Core i7 4960X
SE +/- 1.76, N = 3
1371.14
Core i7 5775C
SE +/- 4.03, N = 3
2115.61
Core i7 5960X
SE +/- 1.06, N = 3
1793.70
Core i7 5960X Haswell-E
SE +/- 2.82, N = 3
1781.44
FX-8150
SE +/- 1.24, N = 3
681.56
FX-8350
SE +/- 0.36, N = 3
607.26
FX-8350 on Gigabyte 990FXA UD3
SE +/- 1.51, N = 3
671.87
FX-8370
SE +/- 5.43, N = 3
694.23
FX-8370E
SE +/- 3.24, N = 3
719.04
Pentium G3258
SE +/- 1.27, N = 3
1592.33
Pentium G4400
SE +/- 10.78, N = 3
2153.49
Phenom II X3 710
505.20



Timed Linux Kernel Compilation 4.3
Time To Compile
Seconds, Fewer Is Better
2 x Xeon E5540
SE +/- 1.27, N = 3
106.90
A10-5800K
SE +/- 0.47, N = 3
248.16
A10-7800
SE +/- 1.37, N = 3
238.02
A10-7850K #1
SE +/- 0.95, N = 3
277.09
A10-7850K #2
SE +/- 1.23, N = 3
221.22
A10-7870K
SE +/- 0.84, N = 3
212.04
A6-7400K
SE +/- 1.38, N = 3
645.54
A8-3870
SE +/- 1.25, N = 3
259.99
Core i3 2100
SE +/- 1.11, N = 3
291.86
Core i3 2120
SE +/- 0.94, N = 3
323.39
Core i3 5010U
SE +/- 1.07, N = 3
426.43
Core i5 2400S
SE +/- 1.12, N = 3
268.91
Core i5 3210M
SE +/- 3.27, N = 3
317.25
Core i5 4670
SE +/- 2.72, N = 3
141.83
Core i7 3770K
SE +/- 0.89, N = 3
161.35
Core i7 3960X
SE +/- 1.26, N = 3
111.08
Core i7 4600U
SE +/- 1.94, N = 3
242.05
Core i7 4770K
SE +/- 0.80, N = 3
107.36
Core i7 4790K
SE +/- 0.77, N = 3
86.23
Core i7 5775C
SE +/- 0.93, N = 3
97.32
Core i7 5960X
SE +/- 0.67, N = 3
61.76
Core i7 5960X Haswell-E
SE +/- 0.99, N = 3
68.70
FX-8150
SE +/- 3.30, N = 6
173.17
FX-8350 on Gigabyte 990FXA UD3
SE +/- 1.37, N = 3
141.06
FX-8370
SE +/- 1.16, N = 3
127.70
FX-8370E
SE +/- 1.25, N = 3
175.45
Pentium G3258
SE +/- 2.39, N = 3
321.40
Pentium G4400
SE +/- 0.81, N = 3
273.83
Phenom II X3 710
SE +/- 2.38, N = 3
415.57
Xeon E3-1231 v3
SE +/- 0.58, N = 3
101.50
Xeon E3-1235L v5
SE +/- 0.67, N = 3
162.89
Xeon E3-1245 v5
SE +/- 0.73, N = 3
101.11
Xeon E3-1260L v5
SE +/- 0.50, N = 3
107.76
Xeon E3-1270 v5
86.44



C-Ray 1.1
Total Time
Seconds, Fewer Is Better
2 x Xeon E5540
SE +/- 0.01, N = 3
18.39
A10-5800K
SE +/- 0.46, N = 3
54.12
A10-7800
SE +/- 0.05, N = 3
57.06
A10-7850K #1
SE +/- 0.06, N = 3
53.35
A10-7850K #2
SE +/- 0.24, N = 3
53.36
A10-7870K
SE +/- 0.04, N = 3
50.76
A6-7400K
SE +/- 0.03, N = 3
112.84
A8-3870
SE +/- 0.71, N = 3
43.22
Core i3 2100
SE +/- 0.70, N = 3
70.08
Core i3 2120
SE +/- 0.35, N = 3
66.13
Core i3 4130
SE +/- 0.02, N = 3
61.46
Core i3 5010U
SE +/- 0.01, N = 3
79.64
Core i5 2400S
SE +/- 0.02, N = 3
45.71
Core i5 2500K
SE +/- 0.06, N = 3
54.58
Core i5 3210M
SE +/- 0.40, N = 3
72.40
Core i5 3470
SE +/- 0.04, N = 3
48.54
Core i5 4670
SE +/- 0.01, N = 3
24.54
Core i7 3770K
SE +/- 0.03, N = 3
28.67
Core i7 3960X
SE +/- 0.07, N = 3
22.40
Core i7 4600U
SE +/- 0.00, N = 3
56.17
Core i7 4770K
SE +/- 0.02, N = 3
22.80
Core i7 4790K
SE +/- 0.01, N = 3
19.15
Core i7 4960X
SE +/- 0.01, N = 3
23.05
Core i7 5775C
SE +/- 0.01, N = 3
22.61
Core i7 5960X
SE +/- 0.04, N = 3
12.99
Core i7 5960X Haswell-E
SE +/- 0.02, N = 3
12.96
FX-8150
SE +/- 0.69, N = 6
32.21
FX-8350
SE +/- 0.01, N = 3
33.43
FX-8350 on Gigabyte 990FXA UD3
SE +/- 0.02, N = 3
25.50
FX-8370
SE +/- 0.01, N = 3
25.19
FX-8370E
SE +/- 0.01, N = 3
30.35
Pentium G3258
SE +/- 0.04, N = 3
55.13
Pentium G4400
SE +/- 0.01, N = 3
46.48
Phenom II X3 710
67.91


FLAC Audio Encoding 1.3.1
WAV To FLAC
Seconds, Fewer Is Better
2 x Xeon E5540
SE +/- 0.00, N = 5
11.76
A10-5800K
SE +/- 0.01, N = 5
9.77
A10-7800
SE +/- 0.04, N = 5
11.48
A10-7850K #1
SE +/- 0.03, N = 5
10.55
A10-7850K #2
SE +/- 0.04, N = 5
11.08
A10-7870K
SE +/- 0.02, N = 5
10.32
A6-7400K
SE +/- 0.02, N = 5
11.18
A8-3870
SE +/- 0.01, N = 5
13.11
Core i3 2100
SE +/- 0.07, N = 5
9.79
Core i3 2120
SE +/- 0.02, N = 5
9.21
Core i3 4130
SE +/- 0.00, N = 5
8.80
Core i3 5010U
SE +/- 0.02, N = 5
10.50
Core i5 2400S
SE +/- 0.01, N = 5
8.64
Core i5 2500K
SE +/- 0.05, N = 5
10.56
Core i5 3210M
SE +/- 0.01, N = 5
8.73
Core i5 3470
SE +/- 0.00, N = 5
8.72
Core i5 4670
SE +/- 0.00, N = 5
5.89
Core i7 3770K
SE +/- 0.02, N = 5
6.69
Core i7 3960X
SE +/- 0.16, N = 10
9.49
Core i7 4600U
SE +/- 0.07, N = 5
6.87
Core i7 4770K
SE +/- 0.00, N = 5
5.77
Core i7 4790K
SE +/- 0.04, N = 5
5.14
Core i7 4960X
SE +/- 0.01, N = 5
8.94
Core i7 5775C
SE +/- 0.00, N = 5
6.04
Core i7 5960X
SE +/- 0.02, N = 5
6.70
Core i7 5960X Haswell-E
SE +/- 0.08, N = 5
6.89
FX-8150
SE +/- 0.01, N = 5
9.57
FX-8350
SE +/- 0.01, N = 5
11.75
FX-8350 on Gigabyte 990FXA UD3
SE +/- 0.02, N = 5
10.15
FX-8370
SE +/- 0.01, N = 5
10.04
FX-8370E
SE +/- 0.01, N = 5
9.44
Pentium G3258
SE +/- 0.01, N = 5
7.94
Pentium G4400
SE +/- 0.00, N = 5
6.64
Phenom II X3 710
15.36


PostgreSQL pgbench 9.4.3
Scaling: Buffer Test - Test: Normal Load - Mode: Read Write
TPS, More Is Better
2 x Xeon E5540
SE +/- 13.57, N = 6
481.17
A10-5800K
SE +/- 5.62, N = 3
1137.77
A10-7800
SE +/- 4.95, N = 3
369.44
A10-7850K #3
SE +/- 2.34, N = 3
339.63
A10-7850K #2
SE +/- 15.86, N = 3
1346.65
A10-7870K
SE +/- 26.65, N = 3
1335.84
A6-7400K
SE +/- 7.76, N = 3
981.26
A8-3870
SE +/- 4.85, N = 3
328.18
Core i3 2100
SE +/- 38.39, N = 6
171.65
Core i3 2120
SE +/- 6.39, N = 6
251.01
Core i3 4130
SE +/- 7.39, N = 3
681.44
Core i3 5010U
SE +/- 13.24, N = 3
2293.04
Core i5 2400S
SE +/- 42.57, N = 6
258.51
Core i5 2500K
SE +/- 2.08, N = 3
212.63
Core i5 3210M
SE +/- 15.22, N = 3
1081.24
Core i5 3470
SE +/- 7.90, N = 3
416.63
Core i5 4670
SE +/- 24.87, N = 6
758.41
Core i7 3770K
SE +/- 54.53, N = 3
3066.14
Core i7 3960X
SE +/- 142.12, N = 5
10349.30
Core i7 4600U
SE +/- 57.05, N = 6
732.58
Core i7 4770K
SE +/- 11.13, N = 6
639.84
Core i7 4790K
SE +/- 114.27, N = 6
1871.07
Core i7 4960X
SE +/- 80.38, N = 6
344.99
Core i7 5775C
SE +/- 50.82, N = 3
3417.91
Core i7 5960X
SE +/- 16.47, N = 3
2489.80
Core i7 5960X Haswell-E
SE +/- 25.27, N = 3
2564.94
FX-8150
SE +/- 20.21, N = 6
697.58
FX-8350
SE +/- 4.45, N = 3
415.15
FX-8350 on Gigabyte 990FXA UD3
SE +/- 46.63, N = 3
3293.59
FX-8370
SE +/- 17.89, N = 3
2364.03
FX-8370E
SE +/- 98.99, N = 6
1010.00
Pentium G3258
SE +/- 4.72, N = 3
349.05
Pentium G4400
SE +/- 11.43, N = 3
3016.92
Phenom II X3 710
232.19



Redis 3.0.1
Test: GET
Requests Per Second, More Is Better
2 x Xeon E5540
SE +/- 22344.06, N = 6
1513350.83
A10-5800K
SE +/- 8880.73, N = 3
1385795.25
A10-7800
SE +/- 10632.76, N = 3
1122117.83
A10-7850K #1
SE +/- 4609.53, N = 3
1204370.92
A10-7850K #2
SE +/- 9331.57, N = 3
1210309.63
A10-7870K
SE +/- 8387.61, N = 3
1147788.79
A6-7400K
SE +/- 1601.97, N = 3
1177860.67
A8-3870
SE +/- 7981.88, N = 3
1112461.17
Core i3 2100
SE +/- 8962.79, N = 3
1816069.41
Core i3 2120
SE +/- 107561.53, N = 6
1574476.98
Core i3 4130
SE +/- 99805.46, N = 6
1880970.17
Core i3 5010U
SE +/- 60985.24, N = 6
1467022.86
Core i5 2400S
SE +/- 26630.34, N = 5
1765958.07
Core i5 2500K
SE +/- 7344.94, N = 3
1902402.87
Core i5 3210M
SE +/- 14843.70, N = 3
1487655.08
Core i5 3470
SE +/- 1169.27, N = 3
552084.48
Core i5 4670
SE +/- 60637.29, N = 6
2375701.71
Core i7 3770K
SE +/- 26224.53, N = 3
2079665.29
Core i7 3960X
SE +/- 130188.51, N = 6
1485164.25
Core i7 4600U
SE +/- 62617.73, N = 6
2147711.79
Core i7 4770K
SE +/- 17034.62, N = 3
2491925.92
Core i7 4790K
SE +/- 37259.97, N = 3
2399230.33
Core i7 4960X
SE +/- 7654.65, N = 3
599355.31
Core i7 5775C
SE +/- 119004.23, N = 6
2154295.35
Core i7 5960X
SE +/- 9709.20, N = 6
633168.53
Core i7 5960X Haswell-E
SE +/- 7839.76, N = 3
622992.02
FX-8150
SE +/- 2532.55, N = 3
1209200.42
FX-8350
SE +/- 2302.29, N = 3
1258397.66
FX-8350 on Gigabyte 990FXA UD3
SE +/- 18087.82, N = 3
1345168.71
FX-8370
SE +/- 2612.46, N = 3
500027.45
FX-8370E
SE +/- 12770.15, N = 3
1310867.25
Pentium G3258
SE +/- 26874.42, N = 3
1991426.00
Pentium G4400
SE +/- 19677.28, N = 3
2732524.92
Phenom II X3 710
1021057.42


Redis 3.0.1
Test: SET
Requests Per Second, More Is Better
2 x Xeon E5540
SE +/- 21525.41, N = 3
1104171.50
A10-5800K
SE +/- 7430.27, N = 3
1012596.62
A10-7800
SE +/- 1171.32, N = 3
815220.77
A10-7850K #1
SE +/- 8393.15, N = 3
893814.08
A10-7850K #2
SE +/- 15518.21, N = 3
864614.35
A10-7870K
SE +/- 1573.24, N = 3
868815.41
A6-7400K
SE +/- 8438.11, N = 3
896217.60
A8-3870
SE +/- 4240.42, N = 3
835465.00
Core i3 2100
SE +/- 19213.74, N = 5
1245950.80
Core i3 2120
SE +/- 70996.39, N = 6
1182071.41
Core i3 4130
SE +/- 41563.03, N = 6
1500535.08
Core i3 5010U
SE +/- 3789.13, N = 3
1132100.84
Core i5 2400S
SE +/- 5643.74, N = 3
1326308.08
Core i5 2500K
SE +/- 8859.00, N = 3
1338805.13
Core i5 3210M
SE +/- 7742.47, N = 3
1049798.60
Core i5 3470
SE +/- 2957.72, N = 3
493618.75
Core i5 4670
SE +/- 31921.52, N = 6
1694051.79
Core i7 3770K
SE +/- 9814.45, N = 3
1554527.91
Core i7 3960X
SE +/- 56339.64, N = 6
1293401.57
Core i7 4600U
SE +/- 42210.70, N = 6
1373932.27
Core i7 4770K
SE +/- 18413.37, N = 3
1758881.33
Core i7 4790K
SE +/- 91573.12, N = 6
1836375.90
Core i7 4960X
SE +/- 3391.32, N = 3
537677.40
Core i7 5775C
SE +/- 55386.85, N = 6
1686550.58
Core i7 5960X
SE +/- 12289.52, N = 6
560359.88
Core i7 5960X Haswell-E
SE +/- 10437.78, N = 3
552471.21
FX-8150
SE +/- 3106.15, N = 3
921963.23
FX-8350
SE +/- 14612.66, N = 3
939720.50
FX-8350 on Gigabyte 990FXA UD3
SE +/- 16126.73, N = 3
960548.19
FX-8370
SE +/- 1984.21, N = 3
444462.09
FX-8370E
SE +/- 15754.53, N = 3
976751.44
Pentium G3258
SE +/- 2460.55, N = 3
1429941.75
Pentium G4400
SE +/- 6611.25, N = 3
1884468.33
Phenom II X3 710
742626.54


Apache Benchmark 2.4.7
Static Web Page Serving
Requests Per Second, More Is Better
2 x Xeon E5540
SE +/- 67.45, N = 3
16393.03
A10-5800K
SE +/- 27.29, N = 3
20726.51
A10-7800
SE +/- 50.82, N = 3
22261.26
A10-7850K #1
SE +/- 210.74, N = 3
19324.07
A10-7850K #2
SE +/- 363.64, N = 3
19714.67
A10-7870K
SE +/- 15.10, N = 3
14040.28
A6-7400K
SE +/- 21.44, N = 3
10841.66
A8-3870
SE +/- 29.36, N = 3
18932.24
Core i3 2100
SE +/- 78.91, N = 3
20260.21
Core i3 2120
SE +/- 92.35, N = 3
20983.08
Core i3 4130
SE +/- 57.17, N = 3
17346.11
Core i3 5010U
SE +/- 23.48, N = 3
20034.47
Core i5 2400S
SE +/- 45.53, N = 3
25052.50
Core i5 2500K
SE +/- 114.89, N = 3
30653.36
Core i5 3210M
SE +/- 62.28, N = 3
19521.07
Core i5 3470
SE +/- 21.24, N = 3
17592.47
Core i5 4670
SE +/- 325.96, N = 3
52502.40
Core i7 3770K
SE +/- 127.64, N = 3
28817.42
Core i7 3960X
SE +/- 1426.32, N = 6
20330.34
Core i7 4600U
SE +/- 78.53, N = 3
27334.98
Core i7 4770K
SE +/- 129.45, N = 3
22564.76
Core i7 4790K
SE +/- 860.84, N = 6
48264.54
Core i7 4960X
SE +/- 84.54, N = 3
19032.97
Core i7 5775C
SE +/- 18.26, N = 3
40176.86
Core i7 5960X Haswell-E
SE +/- 360.69, N = 6
18657.51
FX-8150
SE +/- 38.99, N = 3
20323.52
FX-8350
SE +/- 9.93, N = 3
20392.93
FX-8370
SE +/- 8.47, N = 3
16816.61
FX-8370E
SE +/- 99.82, N = 3
19034.21
Pentium G3258
SE +/- 138.45, N = 3
20831.46
Phenom II X3 710
SE +/- 47.69, N = 3
20833.26
Xeon E3-1235L v5
SE +/- 27.87, N = 3
42928.92
Xeon E3-1245 v5
SE +/- 233.31, N = 3
41091.31
Xeon E3-1260L v5
42014.15


40-Way Linux PC Benchmark Comparison

These geometric means are based upon test groupings / test suites for this result file.


Geometric Mean Of C/C++ Compiler Tests
Result Composite - 40-Way Linux PC Benchmark Comparison
Relative Performance, More Is Better
2 x Xeon E5540
2.177
A10-5800K
1.922
A10-7800
1.414
A10-7850K #1
1.485
A10-7850K #2
2.025
A10-7870K
2.033
A6-7400K
1.557
A8-3870
1.293
Core i3 2100
1.298
Core i3 2120
1.483
Core i3 4130
1.867
Core i3 5010U
2.329
Core i5 2400S
1.681
Core i5 2500K
1.427
Core i5 3210M
2.115
Core i5 3470
1.849
Core i5 4670
3.056
Core i7 3770K
3.861
Core i7 3960X
4.975
Core i7 4600U
2.284
Core i7 4770K
2.948
Core i7 4790K
4.372
Core i7 4960X
2.126
Core i7 5775C
4.658
Core i7 5960X
4.622
Core i7 5960X Haswell-E
4.619
FX-8150
1.924
FX-8350
1.546
FX-8350 on Gigabyte 990FXA UD3
2.953
FX-8370
2.756
FX-8370E
2.179
Pentium G3258
1.833
Pentium G4400
3.699
Phenom II X3 710
1.000


40-Way Linux PC Benchmark Comparison

Geometric mean based upon tests: pts/himeno, pts/c-ray, pts/encode-flac, pts/pgbench, pts/apache and pts/lammps


Geometric Mean Of CPU Massive Tests
Result Composite - 40-Way Linux PC Benchmark Comparison
Relative Performance, More Is Better
2 x Xeon E5540
1.916
A10-5800K
1.713
A10-7800
1.300
A10-7850K #1
1.380
A10-7850K #2
1.689
A10-7870K
1.680
A6-7400K
1.420
A8-3870
1.228
Core i3 2100
1.428
Core i3 2120
1.510
Core i3 4130
1.888
Core i3 5010U
2.002
Core i5 2400S
1.706
Core i5 2500K
1.551
Core i5 3210M
1.859
Core i5 3470
1.270
Core i5 4670
2.781
Core i7 3770K
3.134
Core i7 3960X
3.403
Core i7 4600U
2.175
Core i7 4770K
2.754
Core i7 4790K
3.585
Core i7 4960X
1.433
Core i7 5775C
3.622
Core i7 5960X
2.445
Core i7 5960X Haswell-E
2.431
FX-8150
1.650
FX-8350
1.440
FX-8350 on Gigabyte 990FXA UD3
2.249
FX-8370
1.602
FX-8370E
1.834
Pentium G3258
1.867
Pentium G4400
3.291
Phenom II X3 710
1.000


40-Way Linux PC Benchmark Comparison

Geometric mean based upon tests: pts/apache, pts/build-linux-kernel, pts/c-ray, pts/encode-flac, pts/himeno, pts/lammps, pts/pgbench and pts/redis


Geometric Mean Of Creator Workloads Tests
Result Composite - 40-Way Linux PC Benchmark Comparison
Relative Performance, More Is Better
2 x Xeon E5540
2.416
A10-5800K
1.545
A10-7800
1.388
A10-7850K #1
1.497
A10-7850K #2
1.461
A10-7870K
1.552
A6-7400K
1.000
A8-3870
1.492
Core i3 2100
1.356
Core i3 2120
1.439
Core i3 4130
1.528
Core i3 5010U
1.228
Core i5 2400S
1.788
Core i5 2500K
1.480
Core i5 3210M
1.413
Core i5 3470
1.727
Core i5 4670
2.955
Core i7 3770K
2.565
Core i7 3960X
2.437
Core i7 4600U
1.809
Core i7 4770K
3.097
Core i7 4790K
3.580
Core i7 4960X
2.475
Core i7 5775C
3.040
Core i7 5960X
3.808
Core i7 5960X Haswell-E
3.759
FX-8150
2.023
FX-8350
1.793
FX-8350 on Gigabyte 990FXA UD3
2.208
FX-8370
2.234
FX-8370E
2.099
Pentium G3258
1.698
Pentium G4400
2.022
Phenom II X3 710
1.100


40-Way Linux PC Benchmark Comparison

Geometric mean based upon tests: pts/c-ray and pts/encode-flac


Geometric Mean Of Database Test Suite
Result Composite - 40-Way Linux PC Benchmark Comparison
Relative Performance, More Is Better
2 x Xeon E5540 1.934
A10-5800K 2.431
A10-7800 1.449
A10-7850K #1 1.487
A10-7850K #2 2.332
A10-7870K 2.288
A6-7400K 2.104
A8-3870 1.400
Core i3 2100 1.517
Core i3 2120 1.614
Core i3 4130 2.586
Core i3 5010U 3.248
Core i5 2400S 1.759
Core i5 2500K 1.695
Core i5 3210M 2.477
Core i5 3470 1.007
Core i5 4670 3.017
Core i7 3770K 4.467
Core i7 3960X 5.634
Core i7 4600U 2.689
Core i7 4770K 2.933
Core i7 4790K 4.201
Core i7 4960X 1.000
Core i7 5775C 4.816
Core i7 5960X 1.995
Core i7 5960X Haswell-E 1.995
FX-8150 1.912
FX-8350 1.641
FX-8350 on Gigabyte 990FXA UD3 3.370
FX-8370 1.678
FX-8370E 2.266
Pentium G3258 2.075
Pentium G4400 5.189
Phenom II X3 710 1.166


40-Way Linux PC Benchmark Comparison

Geometric mean based upon tests: pts/sqlite, pts/redis and pts/pgbench


Geometric Mean Of Multi-Core Tests
Result Composite - 40-Way Linux PC Benchmark Comparison
Relative Performance, More Is Better
2 x Xeon E5540
3.268
A10-5800K
2.930
A10-7800
1.626
A10-7850K #1
1.612
A10-7850K #2
3.210
A10-7870K
3.278
A6-7400K
1.884
A8-3870
1.761
Core i3 2100
1.000
Core i3 2120
1.245
Core i3 4130
2.128
Core i3 5010U
3.429
Core i5 2400S
1.520
Core i5 2500K
1.261
Core i5 3210M
2.469
Core i5 3470
1.872
Core i5 4670
3.552
Core i7 3770K
6.608
Core i7 3960X
13.735
Core i7 4600U
2.308
Core i7 4770K
3.385
Core i7 4790K
6.316
Core i7 4960X
2.472
Core i7 5775C
7.856
Core i7 5960X
8.846
Core i7 5960X Haswell-E
8.989
FX-8150
2.974
FX-8350
2.252
FX-8350 on Gigabyte 990FXA UD3
7.262
FX-8370
6.190
FX-8370E
3.686
Pentium G3258
1.608
Pentium G4400
5.148
Phenom II X3 710
1.182


40-Way Linux PC Benchmark Comparison

Geometric mean based upon tests: pts/c-ray, pts/lammps, pts/build-linux-kernel and pts/pgbench


Geometric Mean Of Server Tests
Result Composite - 40-Way Linux PC Benchmark Comparison
Relative Performance, More Is Better
2 x Xeon E5540
1.934
A10-5800K
2.431
A10-7800
1.449
A10-7850K #1
1.487
A10-7850K #2
2.332
A10-7870K
2.288
A6-7400K
2.104
A8-3870
1.400
Core i3 2100
1.517
Core i3 2120
1.614
Core i3 4130
2.586
Core i3 5010U
3.248
Core i5 2400S
1.759
Core i5 2500K
1.695
Core i5 3210M
2.477
Core i5 3470
1.007
Core i5 4670
3.017
Core i7 3770K
4.467
Core i7 3960X
5.634
Core i7 4600U
2.689
Core i7 4770K
2.933
Core i7 4790K
4.201
Core i7 4960X
1.000
Core i7 5775C
4.816
Core i7 5960X
1.995
Core i7 5960X Haswell-E
1.995
FX-8150
1.912
FX-8350
1.641
FX-8350 on Gigabyte 990FXA UD3
3.370
FX-8370
1.678
FX-8370E
2.266
Pentium G3258
2.075
Pentium G4400
5.189
Phenom II X3 710
1.166


40-Way Linux PC Benchmark Comparison

Geometric mean based upon tests: pts/apache, pts/pgbench, pts/redis and pts/sqlite


Geometric Mean Of Server CPU Tests
Result Composite - 40-Way Linux PC Benchmark Comparison
Relative Performance, More Is Better
2 x Xeon E5540
2.068
A10-5800K
1.345
A10-7800
1.227
A10-7850K #1
1.342
A10-7850K #2
1.304
A10-7870K
1.273
A6-7400K
1.090
A8-3870
1.199
Core i3 2100
1.644
Core i3 2120
1.601
Core i3 4130
1.724
Core i3 5010U
1.453
Core i5 2400S
1.879
Core i5 2500K
1.798
Core i5 3210M
1.498
Core i5 3470
1.074
Core i5 4670
2.715
Core i7 3770K
2.364
Core i7 3960X
2.154
Core i7 4600U
1.969
Core i7 4770K
2.778
Core i7 4790K
3.064
Core i7 4960X
1.358
Core i7 5775C
2.786
Core i7 5960X
1.717
Core i7 5960X Haswell-E
1.702
FX-8150
1.430
FX-8350
1.397
FX-8350 on Gigabyte 990FXA UD3
1.567
FX-8370
1.021
FX-8370E
1.523
Pentium G3258
1.954
Pentium G4400
2.550
Phenom II X3 710
1.000

40-Way Linux PC Benchmark Comparison

Geometric mean based upon tests: pts/himeno, pts/build-linux-kernel, pts/c-ray and pts/redis


Geometric Mean Of Single-Threaded Tests
Result Composite - 40-Way Linux PC Benchmark Comparison
Relative Performance, More Is Better
2 x Xeon E5540
1.858
A10-5800K
1.865
A10-7800
1.533
A10-7850K #1
1.664
A10-7850K #2
1.622
A10-7870K
1.634
A6-7400K
1.622
A8-3870
1.474
Core i3 2100
2.186
Core i3 2120
2.090
Core i3 4130
2.438
Core i3 5010U
1.926
Core i5 2400S
2.305
Core i5 2500K
2.217
Core i5 3210M
2.007
Core i5 3470
1.122
Core i5 4670
3.137
Core i7 3770K
2.795
Core i7 3960X
2.091
Core i7 4600U
2.687
Core i7 4770K
3.250
Core i7 4790K
3.383
Core i7 4960X
1.176
Core i7 5775C
3.006
Core i7 5960X
1.337
Core i7 5960X Haswell-E
1.312
FX-8150
1.739
FX-8350
1.657
FX-8350 on Gigabyte 990FXA UD3
1.792
FX-8370
1.000
FX-8370E
1.830
Pentium G3258
2.530
Pentium G4400
3.272
Phenom II X3 710
1.307

40-Way Linux PC Benchmark Comparison

Geometric mean based upon tests: pts/encode-flac and pts/redis

This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 15:57.