

www.phoronix-test-suite.com

OpenCL Intel Beignet

Intel Core i7-7700K testing with a ASUS PRIME Z270-P and Intel Kabylake GT2 3072MB on Clear Linux 12960 via the Phoronix Test Suite.

Automated Executive Summary

Core i7 7700K had the most wins, coming in first place for 66% of the tests.

Based on the geometric mean of all complete results, the fastest (Core i7 7700K) was 1.11x the speed of the slowest (Core i3 7100). Core i5 7600K was 0.966x the speed of Core i7 7700K and Core i3 7100 was 0.932x the speed of Core i5 7600K.

Test Systems:

Core i3 7100

Processor: Intel Core i3-7100 @ 3.90GHz (4 Cores), Motherboard: ASUS PRIME Z270-P, Chipset: Intel Device 590f, Memory: 16384MB, Disk: Samsung SSD 950 PRO 256GB, Graphics: Intel Kabylake GT2 3072MB (1100MHz), Audio:

Realtek ALC887-VD, Monitor: DELL P2415Q, Network: Realtek RTL8111/8168/8411

OS: Clear Linux 12950, Kernel: 4.9.5-302.native (x86_64), Desktop: Xfce 4.12, Display Server: X Server 1.19.1, Display Driver: modesetting 1.19.1, OpenGL: 4.5 Mesa 17.0.0-devel, OpenCL: OpenCL 2.0 beignet 1.3, Vulkan: 1.0.37, Compiler: GCC 6.3.0 + Clang 3.9.1 + LLVM 3.9.1, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-generic-linux --disable-libunwind-exceptions --disable-multiarch --disable-vtable-verify --enable-__cxa_atexit --enable-bootstrap --enable-clocale=gnu --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libmpx --enable-libstdcxx-pch --enable-lto --enable-multilib --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-tune=haswell
Processor Notes: Scaling Governor: acpi-cpufreq performance

Core i5 7600K

Processor: Intel Core i5-7600K @ 3.80GHz (4 Cores), Motherboard: ASUS PRIME Z270-P, Chipset: Intel Device 591f, Memory: 16384MB, Disk: Samsung SSD 950 PRO 256GB, Graphics: Intel Kabylake GT2 3072MB (1150MHz), Audio: Realtek ALC887-VD, Monitor: DELL P2415Q, Network: Realtek RTL8111/8168/8411

OS: Clear Linux 12950, Kernel: 4.9.5-302.native (x86_64), Desktop: Xfce 4.12, Display Server: X Server 1.19.1, Display Driver: modesetting 1.19.1, OpenGL: 4.5 Mesa 17.0.0-devel, OpenCL: OpenCL 2.0 beignet 1.3, Vulkan: 1.0.37, Compiler: GCC 6.3.0 + Clang 3.9.1 + LLVM 3.9.1, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-generic-linux --disable-libunwind-exceptions --disable-multiarch --disable-vtable-verify --enable-__cxa_atexit --enable-bootstrap --enable-clocale=gnu --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libmpx --enable-libstdcxx-pch --enable-lto --enable-multilib --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-tune=haswell
Processor Notes: Scaling Governor: acpi-cpufreq performance

Core i7 7700K

Processor: Intel Core i7-7700K @ 4.20GHz (8 Cores), Motherboard: ASUS PRIME Z270-P, Chipset: Intel Device 591f, Memory: 16384MB, Disk: Samsung SSD 950 PRO 256GB, Graphics: Intel Kabylake GT2 3072MB (1150MHz), Audio: Realtek ALC887-VD, Monitor: DELL P2415Q, Network: Realtek RTL8111/8168/8411

OS: Clear Linux 12960, Kernel: 4.9.5-302.native (x86_64), Desktop: Xfce 4.12, Display Server: X Server 1.19.1, Display Driver: modesetting 1.19.1, OpenGL: 4.5 Mesa 17.0.0-devel, OpenCL: OpenCL 2.0 beignet 1.3, Vulkan: 1.0.37, Compiler: GCC 6.3.0 + Clang 3.9.1 + LLVM 3.9.1, File-System: ext4, Screen Resolution: 1920x1080


Compiler Notes: --build=x86_64-generic-linux --disable-libunwind-exceptions --disable-multiarch --disable-vtable-verify --enable-__cxa_atexit --enable-bootstrap --enable-clocale=gnu --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libmpx --enable-libstdcxx-pch --enable-lto --enable-multilib --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-tune=haswell
Processor Notes: Scaling Governor: acpi-cpufreq performance

	Core i3 7100	Core i5 7600K	Core i7 7700K
cl-mem - Read (GB/s)	**44.12**	**39.72**	41.07
Normalized	100%	90.03%	93.09%
Standard Deviation	8%	8.5%	14.3%
cl-mem - Write (GB/s)	**47.97**	42.92	**39.13**
Normalized	100%	89.47%	81.57%
Standard Deviation	17.1%	11.6%	3.4%
JuliaGPU - GPU (Samples/sec)	**31987657**	36333557	**37085080**


OpenCL Intel Beignet

Normalized	86.25%	97.97%	100%
Standard Deviation	0.2%	1.8%	2.2%
MandelbulbGPU - GPU (Samples/sec)	**6991142**	7893609	**7953468**
Normalized	87.9%	99.25%	100%
Standard Deviation	0%	0.4%	0.4%
MandelGPU - GPU (Samples/sec)	**8031119**	9180692	**9186739**
Normalized	87.42%	99.93%	100%
Standard Deviation	0%	0%	0.1%
SHOC Scalable HeterOgeneous Computing - OpenCL - Triad (GB/s)	**6.61**	8.37	**12.23**
Normalized	54.05%	68.44%	100%
Standard Deviation	0.2%	0.4%	2.7%
SHOC Scalable HeterOgeneous Computing - OpenCL - FFT SP (GFLOPS)	**9.67**	**10.90**	10.88
Normalized	88.72%	100%	99.82%
Standard Deviation	0.1%	0%	0%
SHOC Scalable HeterOgeneous Computing - OpenCL - MD5 Hash (GHash/s)	**0.28**	**0.32**	**0.32**
Normalized	87.5%	100%	100%
Standard Deviation	0%	0%	0%
SHOC Scalable HeterOgeneous Computing - OpenCL - Max SP Flops (GFLOPS)	**297.39**	340.69	**340.71**
Normalized	87.29%	99.99%	100%
Standard Deviation	0%	0%	0%
SHOC Scalable HeterOgeneous Computing - OpenCL - Bus Speed Download (GB/s)	**24.86**	26.18	**28.39**
Normalized	87.57%	92.22%	100%
Standard Deviation	0.2%	1.3%	0.3%
SHOC Scalable HeterOgeneous Computing - OpenCL - Bus Speed Readback (GB/s)	**32.08**	35.12	**38.52**
Normalized	83.28%	91.17%	100%
Standard Deviation	1.6%	1.8%	1.4%
SHOC Scalable HeterOgeneous Computing - OpenCL - T.R.B (GB/s)	**51.52**	**58.11**	57.89
Normalized	88.66%	100%	99.62%
Standard Deviation	0%	0%	0.7%
SmallPT GPU - GPU - Complex	1485491582	**1485461759**	**1485532534**
Normalized	100%	100%	100%
Standard Deviation	0%	0%	0%
SmallPT GPU - GPU - Cornell (Samples/sec)	1485492354	**1485462437**	**1485533211**
Normalized	100%	100%	100%
Standard Deviation	0%	0%	0%
SmallPT GPU - GPU - Caustic3	1485492483	**1485462559**	**1485533333**
Normalized	100%	100%	100%
Standard Deviation	0%	0%	0%


OpenCL Intel Beignet




OpenCL Intel Beignet




OpenCL Intel Beignet




OpenCL Intel Beignet




OpenCL Intel Beignet



These geometric means are based upon test groupings / test suites for this result file.



Geometric mean based upon tests: pts/cl-mem, pts/mandelgpu and pts/shoc



Geometric mean based upon tests: pts/juliagpu, pts/mandelgpu, pts/smallpt-gpu, pts/mandelbulbgpu, pts/shoc and pts/cl-mem

This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 07:15.