

www.phoronix-test-suite.com

DL-360-Gen10-Performance-Test-System

DL-360-Gen10-Performance-Test-System-Test-Hint

Test Systems:

DL-360-Gen10-Performance-Test-System


Processor: 2 x Intel Xeon Gold 6148 @ 3.70GHz (40 Cores / 80 Threads), Motherboard: HPE ProLiant DL360 Gen10 (U32 BIOS), Memory: 24 x 64 GB DDR4-2666MHz HPE 840759-091, Disk: 8 x 960GB LOGICAL VOLUME + 240GB LOGICAL VOLUME, Graphics: mgadrmfb

OS: Red Hat Enterprise Linux Server 7.4, Kernel: 3.10.0-693.17.1.el7.x86_64 (x86_64), Compiler: GCC 4.8.5 20150623, File-System: xfs, Screen Resolution: 1024x768

Compiler Notes: --build=x86_64-redhat-linux --disable-libgcj --disable-libunwind-exceptions --enable-__cxa_atexit --enable-bootstrap --enable-checking=release --enable-gnu-indirect-function --enable-gnu-unique-object --enable-initfini-array --enable-languages=c,c++,objc,obj-c++,java,fortran,ada,go,lto --enable-plugin --enable-shared --enable-threads=posix --mandir=/usr/share/man --with-arch_32=x86-64 --with-linker-hash-style=gnu --with-tune=generic
Processor Notes: Scaling Governor: intel_pstate performance
Security Notes: SELinux

DL-360-Gen10-Performance-Test-System

	DL-360-Gen10-Performance-Test-System
Hierarchical INTegration - FLOAT (QUIPs)	380737377
Standard Deviation	0.3%
Hierarchical INTegration - DOUBLE (QUIPs)	833946357
Standard Deviation	0.4%



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 06:30.