

www.phoronix-test-suite.com

Intel Xeon vs. AMD EPYC Linux Performance Benchmarks

2 x AMD EPYC 7501 32-Core testing with a Supermicro H11DSi-NT v1.01 (1.1c BIOS) and AMD Radeon PRO SSG 16GB on Ubuntu 18.10 via the Phoronix Test Suite.

Automated Executive Summary

2 x EPYC 7601 had the most wins, coming in first place for 77% of the tests.

Based on the geometric mean of all complete results, the fastest (2 x EPYC 7601) was 7.242x the speed of the slowest (Xeon Silver 4108).

The results with the greatest spread from best to worst included:

m-queens (Time To Solve) at 12.99x
John The Ripper (Test: Traditional DES) at 9.302x
m-queens (Time To Solve) at 9.265x
Sysbench (Test: CPU) at 9.242x
John The Ripper (Test: Blowfish) at 8.771x
POV-Ray (Trace Time) at 8.591x
NAMD (ATPase Simulation - 327,506 Atoms) at 8.515x
ebizzy at 8.157x
Stockfish (Total Time) at 8.048x

asmFish (1024 Hash Memory, 26 Depth) at 7.936x.

Test Systems:

EPYC 7251

Processor: AMD EPYC 7251 8-Core @ 2.10GHz (8 Cores / 16 Threads), Motherboard: TYAN B8026T70AE24HR (V1.02.B10 BIOS), Chipset: AMD Family 17h, Memory: 129024MB, Disk: 280GB INTEL SSDPE21D280GA, Graphics: ASPEED ASPEED Family, Monitor: VE228, Network: Broadcom and subsidiaries NetXtreme BCM5720 Gigabit PCIe

OS: Ubuntu 18.10, Kernel: 4.18.0-8-generic (x86_64), Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1920x1080

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: __user pointer sanitization + Full AMD retpoline IBPB + SSB disabled via prctl and seccomp

EPYC 7351P

Processor: AMD EPYC 7351P 16-Core @ 2.40GHz (16 Cores / 32 Threads), Motherboard: TYAN B8026T70AE24HR (V1.02.B10 BIOS), Chipset: AMD Family 17h, Memory: 129024MB, Disk: 280GB INTEL SSDPE21D280GA, Graphics: ASPEED ASPEED Family, Monitor: VE228, Network: Broadcom and subsidiaries NetXtreme BCM5720 Gigabit PCIe

OS: Ubuntu 18.10, Kernel: 4.18.0-8-generic (x86_64), Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1920x1080

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: __user pointer sanitization + Full AMD retpoline IBPB + SSB disabled via prctl and seccomp

EPYC 7401P

Processor: AMD EPYC 7401P 24-Core @ 2.00GHz (24 Cores / 48 Threads), Motherboard: TYAN B8026T70AE24HR (V1.02.B10 BIOS), Chipset: AMD Family 17h, Memory: 129024MB, Disk: 280GB INTEL SSDPE21D280GA, Graphics: ASPEED ASPEED Family, Monitor: VE228, Network: Broadcom and subsidiaries NetXtreme BCM5720 Gigabit PCIe

OS: Ubuntu 18.10, Kernel: 4.18.0-8-generic (x86_64), Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1920x1080

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes

--enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: __user pointer sanitization + Full AMD retpoline IBPB + SSB disabled via prctl and seccomp

EPYC 7551

Processor: AMD EPYC 7551 32-Core @ 2.00GHz (32 Cores / 64 Threads), Motherboard: GIGABYTE MZ31-AR0-00 v01010101 (F07 BIOS), Chipset: AMD Family 17h, Memory: 28672MB, Disk: 525GB 2115 + 2 x Samsung SSD 960 EVO 500GB, Graphics: ASPEED ASPEED Family, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 18.10, Kernel: 4.18.0-9-generic (x86_64), Desktop: GNOME Shell 3.30.1, Display Server: X Server 1.20.1, Display Driver: modesetting 1.20.1, Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1024x768

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: __user pointer sanitization + Full AMD retpoline IBPB + SSB disabled via prctl and seccomp

EPYC 7601

Processor: AMD EPYC 7601 32-Core @ 2.20GHz (32 Cores / 64 Threads), Motherboard: TYAN B8026T70AE24HR (V1.02.B10 BIOS), Chipset: AMD Family 17h, Memory: 129024MB, Disk: 280GB INTEL SSDPE21D280GA, Graphics: ASPEED ASPEED Family, Monitor: VE228, Network: Broadcom and subsidiaries NetXtreme BCM5720 Gigabit PCIe

OS: Ubuntu 18.10, Kernel: 4.18.0-8-generic (x86_64), Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1920x1080

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: __user pointer sanitization + Full AMD retpoline IBPB + SSB disabled via prctl and seccomp

2 x EPYC 7601

Processor: 2 x AMD EPYC 7601 32-Core @ 2.62GHz (64 Cores / 128 Threads), Motherboard: Dell 02MJ3T (1.2.5 BIOS), Chipset: AMD Family 17h, Memory: 516096MB, Disk: 120GB SSDSCKJB120G7R, Graphics: Matrox Matrox G200eW3, Monitor: VE228, Network: Broadcom and subsidiaries BCM57416 NetXtreme-E Dual-Media 10G RDMA

OS: Ubuntu 18.10, Kernel: 4.18.0-8-generic (x86_64), Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1600x1200

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: __user pointer sanitization + Full AMD retpoline IBPB + SSB disabled via prctl and seccomp

Xeon E5-2687W v3

Processor: Intel Xeon E5-2687W v3 @ 3.50GHz (10 Cores / 20 Threads), Motherboard: MSI X99S SLI PLUS (MS-7885) v1.0 (1.E0 BIOS), Chipset: Intel Xeon E7 v3/Xeon, Memory: 32768MB, Disk: 525GB 2115 + 80GB INTEL SSDSCKGW08, Graphics: NVIDIA GeForce GTX 770, Audio: Realtek ALC892, Network: Intel Connection

OS: Ubuntu 18.10, Kernel: 4.18.0-9-generic (x86_64), Desktop: GNOME Shell 3.30.1, Display Server: X Server 1.20.1, Display Driver: modesetting 1.20.1, Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1024x768

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: intel_pstate powersave
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: KPTI + __user pointer sanitization + Full generic retpoline IBPB IBRS_FW + SSB disabled via prctl and seccomp + PTE Inversion; VMX: conditional cache flushes SMT vulnerable

Xeon Silver 4108

Processor: Intel Xeon Silver 4108 @ 3.00GHz (8 Cores / 16 Threads), Motherboard: TYAN S7100AG2NR (V3.02 BIOS), Chipset: Intel Sky Lake-E DMI3 Registers, Memory: 23552MB, Disk: 525GB 2115 + 240GB Force MP500, Graphics: ASPEED ASPEED Family, Audio: Realtek ALC892, Monitor: VE228, Network: Intel I350 Gigabit Connection

OS: Ubuntu 18.10, Kernel: 4.18.0-9-generic (x86_64), Desktop: GNOME Shell 3.30.1, Display Server: X Server 1.20.1, Display Driver: modesetting 1.20.1, Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1920x1080

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: intel_pstate powersave
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: KPTI + __user pointer sanitization + Full generic retpoline IBPB IBRS_FW + SSB disabled via prctl and seccomp + PTE Inversion; VMX: conditional cache flushes SMT vulnerable

2 x Xeon Gold 6138

Processor: 2 x Intel Xeon Gold 6138 @ 3.70GHz (40 Cores / 80 Threads), Motherboard: TYAN S7106 (V1.01 BIOS), Chipset: Intel Sky Lake-E DMI3 Registers, Memory: 96256MB, Disk: 256GB Samsung SSD 850 + Samsung SSD 970 EVO 250GB, Graphics: ASPEED ASPEED Family, Monitor: VE228, Network: Intel I210 Gigabit Connection

OS: Ubuntu 18.10, Kernel: 4.18.0-8-generic (x86_64), Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 1920x1080

Environment Notes: CXXFLAGS=-O3-march=native CFLAGS=-O3-march=native
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: intel_pstate powersave
Python Notes: Python 2.7.15+ + Python 3.6.7rc1
Security Notes: KPTI + __user pointer sanitization + Full generic retpoline IBPB IBRS_FW + SSB disabled via prctl and seccomp + PTE Inversion; VMX: conditional cache flushes SMT vulnerable

2 x EPYC 7501

Processor: 2 x AMD EPYC 7501 32-Core @ 2.00GHz (64 Cores / 128 Threads), Motherboard: Supermicro H11DSi-NT

v1.01 (1.1c BIOS), Chipset: AMD Family 17h, Memory: 64512MB, Disk: 1000GB Western Digital WD10EZEX-22M + FORESEE 64GB SSD + 4 x 512GB SAMSUNG MZVKW512HMJP-00007, Graphics: AMD Radeon PRO SSG 16GB (1500/945MHz), Audio: AMD Device aaf8, Monitor: C49HG9x, Network: Intel 10G X550T

OS: Ubuntu 18.10, Kernel: 4.18.0-13-generic (x86_64), Desktop: GNOME Shell 3.30.1, Display Server: X Server 1.20.1, Display Driver: amdgpu 18.1.0, Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 3840x1080

Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
Python Notes: Python 2.7.15+ + Python 3.6.7
Security Notes: __user pointer sanitization + Full AMD retpoline IBPB + SSB disabled via prctl and seccomp

2 X EPYC 7501

DUAL EPYC 7501

2p epyc 7501

Processor: 2 x AMD EPYC 7501 32-Core @ 2.00GHz (64 Cores / 128 Threads), Motherboard: Supermicro H11DSi-NT v1.01 (1.1c BIOS), Chipset: AMD Family 17h, Memory: 64512MB, Disk: 1000GB Western Digital WD10EZEX-22M + FORESEE 64GB SSD + 4 x 512GB SAMSUNG MZVKW512HMJP-00007, Graphics: AMD Radeon PRO SSG 16GB (1500/945MHz), Audio: AMD Device aaf8, Monitor: C49HG9x, Network: Intel 10G X550T

OS: Ubuntu 18.10, Kernel: 4.18.0-13-generic (x86_64), Desktop: GNOME Shell 3.30.1, Display Server: X Server 1.20.1, Display Driver: amdgpu 18.1.0, OpenGL: 4.5 Mesa 18.2.2 (LLVM 7.0.0), Compiler: GCC 8.2.0, File-System: ext4, Screen Resolution: 3840x1080

Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq ondemand
Python Notes: Python 2.7.15+ + Python 3.6.7
Security Notes: __user pointer sanitization + Full AMD retpoline IBPB + SSB disabled via prctl and seccomp

	EPYC 7251	EPYC 7351P	EPYC 7401P	EPYC 7551	EPYC 7601	2 x EPYC 7601	Xeon E5-2687W v3	Xeon Silver 4108	2 x Xeon Gold 6138	2 x EPYC 7501	2 X EPYC 7501	DUAL EPYC 7501	2p epyc 7501
NAMD - ATPase Simulation - 327,506 Atoms (days/ns)	3.07634	1.50532	1.20652	0.93584	0.91431	**0.44749**	1.93496	**3.81056**	0.64964	0.46073	1.16545	1.09397	0.45982
Normalized	14.55%	29.73%	37.09%	47.82%	48.94%	100%	23.13%	11.74%	68.88%	97.13%	38.4%	40.91%	97.32%
Standard Deviation	0.3%	0.1%	0.8%	0.5%	1.2%	0.3%	0.4%	0.2%	0.7%	0.1%	9.3%	1.7%	0.1%


John The Ripper - Blowfish (Real	10132	19846	22754		27682	**70223**	13802	**8006**	49183	46875	31830	31515	46343
Normalized	14.43%	28.26%	32.4%		39.42%	100%	19.65%	11.4%	70.04%	66.75%	45.33%	44.88%	65.99%
Standard Deviation	0.9%	1.7%	9.3%		0.2%	1.8%	0.2%		1.2%	0.6%	4.4%	2%	1.7%
John The Ripper - Traditional DES	426873 33	835183 33	106688 667		138201 667	**258439 000**	522656 67	**277823 33**	149246 667	247492 000	980423 33	979890 00	250408 000
Normalized	16.52%	32.32%	41.28%		53.48%	100%	20.22%	10.75%	57.75%	95.76%	37.94%	37.92%	96.89%
Standard Deviation	0.2%	0.4%	0.2%		0.9%	1.2%	0.2%	0.1%	2.7%	0.4%	0.1%	0.2%	0.9%
7-Zip Compression - C.S.T (MIPS)	32590	63667	81664	91318	98518	**156310**	44675	**28680**	146340	137716	106551	104985	138596
Normalized	20.85%	40.73%	52.24%	58.42%	63.03%	100%	28.58%	18.35%	93.62%	88.1%	68.17%	67.16%	88.67%
Standard Deviation	0.8%	2.1%	0.5%	3.5%	1.7%	4.7%	0.7%	1.9%	1.7%	7.8%	3.1%	1.3%	6.2%
Stockfish - Total Time	163226 76	330027 54	431600 28	547065 31	572615 92	102477 345	222265 22	**127930 54**	688216 37	**102962 025**	787696 13	789138 74	101115 084
Normalized	15.85%	32.05%	41.92%	53.13%	55.61%	99.53%	21.59%	12.43%	66.84%	100%	76.5%	76.64%	98.21%
Standard Deviation	1.7%	1.4%	1.2%	1.1%	2.5%	0.8%	1.4%	0.4%	1.5%	0.7%	2.3%	3.2%	0.8%
asmFish - 1.H.M.2.D (Nodes/s)	174649 78	375542 34	484002 59	630455 42	639392 07	**120566 996**	262501 73	**151914 94**	814339 33	119486 834	118538 238	118678 708	120427 619
Normalized	14.49%	31.15%	40.14%	52.29%	53.03%	100%	21.77%	12.6%	67.54%	99.1%	98.32%	98.43%	99.88%
Standard Deviation	0.7%	1.3%	0.6%	1.8%	0.8%	0.9%	1.7%	0.7%	1.9%	1%	0.7%	1.2%	1%
ebizzy (Records/s)	459503	921003	106020 1	107247 1	118259 4	**171743 6**	265125	**210556**	996830	166556 8	151987 4	149676 8	166397 5
Normalized	26.76%	53.63%	61.73%	62.45%	68.86%	100%	15.44%	12.26%	58.04%	96.98%	88.5%	87.15%	96.89%
Standard Deviation	1.5%	1.8%	3.2%	1.4%	1.7%	3.6%	1.3%	5.9%	10%	4.3%	10.5%	8.8%	2%
Timed Linux Kernel Compilation - Time To Compile (sec)	115.16	61.84	52.95	46.54	42.57	**27.27**	91.39	**133.28**	35.33	28.50	29.25	29.21	28.44
Normalized	23.68%	44.1%	51.5%	58.59%	64.06%	100%	29.84%	20.46%	77.19%	95.68%	93.23%	93.36%	95.89%
Standard Deviation	2.2%	3.4%	2.3%	5.6%	3.4%	7.6%	2.6%	2.2%	8.1%	3.9%	9.2%	5.1%	4.3%
Timed LLVM Compilation - Time To Compile (sec)	652	318	284	250	240	**151**	514	**739**	176	158	183	188	162
Normalized	23.16%	47.48%	53.17%	60.4%	62.92%	100%	29.38%	20.43%	85.8%	95.57%	82.51%	80.32%	93.21%
POV-Ray - Trace Time	71.54	36.91	29.33	23.35	22.84	**12.75**	57.48	**109.54**	18.99	13.41	16.55	16.25	13.12
Normalized	17.82%	34.54%	43.47%	54.6%	55.82%	100%	22.18%	11.64%	67.14%	95.08%	77.04%	78.46%	97.18%
Standard Deviation	0.2%	0.3%	1.4%	0.6%	0.6%	0.9%	0.1%	0.2%	0.5%	1.1%	2%	0.5%	1.9%
Primesieve - 1.P.N.G (sec)	42.44	20.65	16.86	13.03	12.65	6.35	36.29	**48.07**	8.81	**6.09**	7.28	7.54	6.12
Normalized	14.35%	29.49%	36.12%	46.74%	48.14%	95.91%	16.78%	12.67%	69.13%	100%	83.65%	80.77%	99.51%
Standard Deviation	0.5%	0.6%	0.9%	0.1%	0.2%	0.8%	0.2%	0.5%	0.7%	0.7%	9.9%	11.9%	0.7%
m-queens - Time To Solve	106.66	54.45	42.04	33.91	32.16	**19.00**	88.51	**176.03**	29.38	19.62	24.39	24.75	19.74
Normalized	17.81%	34.89%	45.2%	56.03%	59.08%	100%	21.47%	10.79%	64.67%	96.84%	77.9%	76.77%	96.25%
Standard Deviation	0.5%	0.3%	0.3%	0.5%	0.4%	1%	0.2%	0.1%	0.4%	0.7%	4.3%	0.5%	0.5%


Tachyon - Total Time (sec)	7.81	3.97	3.03	2.57	2.38	1.46	6.05	**9.80**	2.09	**1.35**	2.11	2.17	1.41
Normalized	17.29%	34.01%	44.55%	52.53%	56.72%	92.47%	22.31%	13.78%	64.59%	100%	63.98%	62.21%	95.74%
Standard Deviation	2.6%	2%	2.5%	0.8%	2.4%	6.4%	0.3%	0.1%	2.3%	6.4%	2.8%	1.7%	5.6%
OpenSSL - R.4.b.P (Signs/sec)	**1242**	2485	3358	4328	4515	**9233**	1458	1281	7838	8878	6355	6499	8876
Normalized	13.45%	26.91%	36.37%	46.88%	48.9%	100%	15.79%	13.87%	84.89%	96.16%	68.83%	70.39%	96.13%
Standard Deviation	0.1%	0.1%	0.9%	0.9%	0.2%	0.3%	0%	0.2%	1.2%	0.1%	0.6%	2%	0.3%
Sysbench - CPU	12102	24174	34891	42199	44813	**89107**	16625	**9642**	60825	86139	64100	62727	85988
Normalized	13.58%	27.13%	39.16%	47.36%	50.29%	100%	18.66%	10.82%	68.26%	96.67%	71.94%	70.4%	96.5%
Standard Deviation	0%	0.1%	0%	0.2%	0.1%	0.5%	0.1%	0%	0.4%	0.1%	3.5%	5.2%	0.1%
Blender - BMW27 - CPU-Only (sec)	335.53	164.30	130.82	104.87	101.70	**57.80**	245.61	**407.11**	77.91	60	69.19	70.62	60.35
Normalized	17.23%	35.18%	44.18%	55.12%	56.83%	100%	23.53%	14.2%	74.19%	96.33%	83.54%	81.85%	95.77%
Blender - Barbershop - CPU-Only (sec)	1797	851	666	531	504	**312**	1183	**1894**	376		334	362	314
Normalized	17.36%	36.66%	46.85%	58.76%	61.9%	100%	26.37%	16.47%	82.98%		93.41%	86.19%	99.36%
RAR Compression - L.S.T.A.T.R (sec)	**186**	149	150	157	143	109	**97.53**	147	116		149.34	152.81	161.66
Normalized	52.44%	65.46%	65.02%	62.12%	68.2%	89.48%	100%	66.35%	84.08%		65.31%	63.82%	60.33%
Standard Deviation	2.5%	2.5%	2.4%	3.3%	2.3%	2.3%	2.1%	0.2%	1.6%		2.2%	0.6%	3.4%
Chaos Group V-RAY - CPU (sec)	116.03	59.25	48.13	40.37	39.32	**25.40**	93.93	**137.93**	31.28				
Normalized	21.89%	42.87%	52.77%	62.92%	64.6%	100%	27.04%	18.42%	81.2%				
Standard Deviation	0.1%	0.2%	1.6%	3.4%	1.6%	2.2%	0.5%	0.5%	0.7%				
Open Porous Media Git - Flow MPI Extra - 8 (sec)	**460**	371	360		353	**334**			374				
Normalized	72.61%	90.03%	92.78%		94.62%	100%			89.3%				
Standard Deviation	0.5%	2.3%	0.4%		0.4%	0.5%			0.6%				
Open Porous Media Git - Flow MPI Extra - 8 - Solver Time (sec)	**453**	364	354		347	**328**			367				
Normalized	72.41%	90.11%	92.66%		94.52%	100%			89.37%				
Standard Deviation	0.5%	2.3%	0.5%		0.4%	0.6%			0.6%				


Open Porous Media Git - Flow MPI Norne - 8 (sec)	158	119	115	114	114	123
Normalized	72.15%	95.8%	99.13%	100%	100%	92.68%
Standard Deviation	2.3%	3.4%	0.5%	0.1%	2.6%	0.3%
Open Porous Media Git - Flow MPI Norne - 8 - Solver Time (sec)	155	118	113	112	112	121
Normalized	72.26%	94.92%	99.12%	100%	100%	92.56%
Standard Deviation	2.3%	3.5%	0.5%	0.1%	2.6%	0.3%
Open Porous Media Git - Flow MPI Extra - 16 (sec)		421	413	415	294	360
Normalized		69.83%	71.19%	70.84%	100%	81.67%
Standard Deviation		1%	0.6%	1.4%	0.4%	0.3%
Open Porous Media Git - Flow MPI Extra - 16 - Solver Time (sec)		415	407	409	288	353
Normalized		69.4%	70.76%	70.42%	100%	81.59%
Standard Deviation		1%	0.6%	1.4%	0.4%	0.3%
Open Porous Media Git - Flow MPI Extra - 32 (sec)				360	219	258
Normalized				60.83%	100%	84.88%
Standard Deviation				0.7%	0.7%	1.5%
Open Porous Media Git - Flow MPI Extra - 32 - Solver Time (sec)				353	213	251
Normalized				60.34%	100%	84.86%
Standard Deviation				0.7%	0.7%	1.5%
Open Porous Media Git - Flow MPI Norne - 16 (sec)		89.66	84.23	85.46	61.93	73.18
Normalized		69.07%	73.52%	72.47%	100%	84.63%
Standard Deviation		1.8%	2.3%	1%	3.9%	0.9%


Open Porous Media Git - Flow MPI Norne - 16 - Solver Time (sec)		87.79	82.42		83.62	60.38			71.22			
Normalized		68.78%	73.26%		72.21%	100%			84.78%			
Standard Deviation		1.8%	2.4%		1%	4%			0.9%			
Open Porous Media Git - Flow MPI Norne - 32 (sec)					107.75	72.20			89.21			
Normalized					67.01%	100%			80.93%			
Standard Deviation					1.7%	1.3%			3.2%			
Open Porous Media Git - Flow MPI Norne - 32 - Solver Time (sec)					105.54	70.34			86.86			
Normalized					66.65%	100%			80.98%			
Standard Deviation					1.7%	1.3%			3.3%			
m-queens - Time To Solve	100.15	49.70	36.96	28.42	27.37	13.67	84.58	177.57	28.11	20.36	21.15	14.01
Normalized	13.65%	27.51%	36.99%	48.1%	49.95%	100%	16.16%	7.7%	48.63%	67.14%	64.63%	97.57%
Standard Deviation	1.7%	0%	1.1%	0.3%	0.3%	0.1%	0%	0%	0.3%	8%	5%	0.1%
John The Ripper - Blowfish (Real						202.81			155.38			
Normalized						100%			76.61%			
John The Ripper - Traditional DES (Real C/S/Watt)						637840			421920			
Normalized						100%			66.15%			
7-Zip Compression - C.S.T (MIPS/Watt)						406.85			453.40			
Normalized						89.73%			100%			
Stockfish - Total Time (Nodes/s/Watt)						202014			181794			
Normalized						100%			89.99%			
asmFish - 1.H.M.2.D (Nodes/s/Watt)						232035			219925			
Normalized						100%			94.78%			
ebizzy (Records/s/Wat						3896			3129			
Normalized						100%			80.31%			


OpenSSL - R.4.b.P (Signs/sec/Watt	**25.14**	**22.27**
Normalized	100%	88.58%
Sysbench - CPU (Events/sec/Wa	**300.83**	**176.90**
Normalized	100%	58.8%



NAMD 2.13b1
ATPase Simulation - 327,506 Atoms
days/ns, Fewer Is Better
EPYC 7251
SE +/- 0.00563, N = 3
3.07634
EPYC 7351P
SE +/- 0.00096, N = 3
1.50532
EPYC 7401P
SE +/- 0.00523, N = 3
1.20652
EPYC 7551
SE +/- 0.00263, N = 3
0.93584
EPYC 7601
SE +/- 0.00656, N = 3
0.91431
2 x EPYC 7601
SE +/- 0.00087, N = 3
0.44749
Xeon E5-2687W v3
SE +/- 0.00399, N = 3
1.93496
Xeon Silver 4108
SE +/- 0.00480, N = 3
3.81056
2 x Xeon Gold 6138
SE +/- 0.00262, N = 3
0.64964
2 x EPYC 7501
SE +/- 0.00040, N = 3
0.46073
2 X EPYC 7501
SE +/- 0.03120, N = 12
1.16545
DUAL EPYC 7501
SE +/- 0.01087, N = 3
1.09397
2p epyc 7501
SE +/- 0.00039, N = 3
0.45982
0.8574
1.7148
2.5722
3.4296
4.287



John The Ripper 1.8.0-jumbo-1
Test: Blowfish
Real C/S, More Is Better
EPYC 7251
SE +/- 52.09, N = 3
10132
EPYC 7351P
SE +/- 193.98, N = 3
19846
EPYC 7401P
SE +/- 608.03, N = 12
22754
EPYC 7601
SE +/- 37.60, N = 3
27682
2 x EPYC 7601
SE +/- 746.57, N = 3
70223
Xeon E5-2687W v3
SE +/- 19.67, N = 3
-lgmp
13802
Xeon Silver 4108
-lgmp
8006
2 x Xeon Gold 6138
SE +/- 346.62, N = 3
49183
2 x EPYC 7501
SE +/- 148.88, N = 3
46875
2 X EPYC 7501
SE +/- 400.03, N = 12
31830
DUAL EPYC 7501
SE +/- 370.17, N = 3
31515
2p epyc 7501
SE +/- 462.08, N = 3
46343
15K
30K
45K
60K
75K
1. (CC) gcc options: -lssl -lcrypto -fopenmp -pthread -lm -lz -ldl -lcrypt -lbz2



John The Ripper 1.8.0-jumbo-1
Test: Traditional DES
Real C/S, More Is Better
EPYC 7251
SE +/- 51385.26, N = 3
42687333
EPYC 7351P
SE +/- 187820.25, N = 3
83518333
EPYC 7401P
SE +/- 113874.69, N = 3
106688667
EPYC 7601
SE +/- 724006.06, N = 3
138201667
2 x EPYC 7601
SE +/- 1826124.04, N = 3
258439000
Xeon E5-2687W v3
SE +/- 66423.72, N = 3
-lgmp
52265667
Xeon Silver 4108
SE +/- 12414.15, N = 3
27782333
2 x Xeon Gold 6138
SE +/- 2318740.77, N = 3
149246667
2 x EPYC 7501
SE +/- 637680.17, N = 3
247492000
2 X EPYC 7501
SE +/- 61780.08, N = 3
98042333
DUAL EPYC 7501
SE +/- 118238.46, N = 3
97989000
2p epyc 7501
SE +/- 1294489.99, N = 3
250408000
60M
120M
180M
240M
300M
1. (CC) gcc options: -lssl -lcrypto -fopenmp -pthread -lm -lz -ldl -lcrypt -lbz2



7-Zip Compression 16.02
Compress Speed Test
MIPS, More Is Better
EPYC 7251
SE +/- 154.50, N = 3
32590
EPYC 7351P
SE +/- 766.71, N = 3
63667
EPYC 7401P
SE +/- 239.07, N = 3
81664
EPYC 7551
SE +/- 1299.36, N = 6
91318
EPYC 7601
SE +/- 949.05, N = 3
98518
2 x EPYC 7601
SE +/- 4241.04, N = 3
156310
Xeon E5-2687W v3
SE +/- 178.22, N = 3
44675
Xeon Silver 4108
SE +/- 313.22, N = 3
28680
2 x Xeon Gold 6138
SE +/- 1426.52, N = 3
146340
2 x EPYC 7501
SE +/- 3232.61, N = 11
137716
2 X EPYC 7501
SE +/- 1629.83, N = 4
106551
DUAL EPYC 7501
SE +/- 785.09, N = 3
104985
2p epyc 7501
SE +/- 2471.85, N = 12
138596
30K
60K
90K
120K
150K
1. (CXX) g++ options: -pipe -lpthread



Stockfish 9
Total Time
Nodes Per Second, More Is Better
EPYC 7251
SE +/- 163392.89, N = 3
-march=native
16322676
EPYC 7351P
SE +/- 266155.23, N = 3
-march=native
33002754
EPYC 7401P
SE +/- 300857.43, N = 3
-march=native
43160028
EPYC 7551
SE +/- 334319.15, N = 3
-march=native
54706531
EPYC 7601
SE +/- 839740.50, N = 3
-march=native
57261592
2 x EPYC 7601
SE +/- 495197.34, N = 3
-march=native
102477345
Xeon E5-2687W v3
SE +/- 174981.26, N = 3
-march=native
22226522
Xeon Silver 4108
SE +/- 26532.68, N = 3
-march=native
12793054
2 x Xeon Gold 6138
SE +/- 615118.06, N = 3
-march=native
68821637
2 x EPYC 7501
SE +/- 396028.35, N = 3
102962025
2 X EPYC 7501
SE +/- 1029131.56, N = 3
78769613
DUAL EPYC 7501
SE +/- 1137971.42, N = 5
78913874
2p epyc 7501
SE +/- 473639.74, N = 3
101115084
20M
40M
60M
80M
100M
1. (CXX) g++ options: -m64 -lpthread -O3 -fno-exceptions -std=c++11 -pedantic -msse -msse3 -mpopcnt -flto



asmFish 2017-09-19
1024 Hash Memory, 26 Depth
Nodes/second, More Is Better
EPYC 7251
SE +/- 67388.88, N = 3
17464978
EPYC 7351P
SE +/- 280862.99, N = 3
37554234
EPYC 7401P
SE +/- 161891.38, N = 3
48400259
EPYC 7551
SE +/- 662599.16, N = 3
63045542
EPYC 7601
SE +/- 303021.59, N = 3
63939207
2 x EPYC 7601
SE +/- 645460.31, N = 3
120566996
Xeon E5-2687W v3
SE +/- 259482.10, N = 3
26250173
Xeon Silver 4108
SE +/- 59693.74, N = 3
15191494
2 x Xeon Gold 6138
SE +/- 897247.72, N = 3
81433933
2 x EPYC 7501
SE +/- 687172.69, N = 3
119486834
2 X EPYC 7501
SE +/- 474852.10, N = 3
118538238
DUAL EPYC 7501
SE +/- 845736.38, N = 3
118678708
2p epyc 7501
SE +/- 724740.58, N = 3
120427619
30M
60M
90M
120M
150M



ebizzy 0.3
Records/s, More Is Better
EPYC 7251
SE +/- 3988.78, N = 3
459503
EPYC 7351P
SE +/- 9794.98, N = 3
921003
EPYC 7401P
SE +/- 19725.31, N = 3
1060201
EPYC 7551
SE +/- 8712.06, N = 3
1072471
EPYC 7601
SE +/- 11622.04, N = 3
1182594
2 x EPYC 7601
SE +/- 35972.43, N = 3
1717436
Xeon E5-2687W v3
SE +/- 1968.54, N = 3
265125
Xeon Silver 4108
SE +/- 3596.08, N = 12
210556
2 x Xeon Gold 6138
SE +/- 57749.43, N = 3
996830
2 x EPYC 7501
SE +/- 20593.28, N = 12
1665568
2 X EPYC 7501
SE +/- 53240.58, N = 9
1519874
DUAL EPYC 7501
SE +/- 38052.26, N = 12
1496768
2p epyc 7501
SE +/- 19387.09, N = 3
1663975
400K
800K
1200K
1600K
2000K
1. (CC) gcc options: -pthread -lpthread -O3 -march=native



Timed Linux Kernel Compilation 4.18
Time To Compile
Seconds, Fewer Is Better
EPYC 7251
SE +/- 1.47, N = 3
115.16
EPYC 7351P
SE +/- 0.87, N = 6
61.84
EPYC 7401P
SE +/- 0.70, N = 3
52.95
EPYC 7551
SE +/- 0.75, N = 12
46.54
EPYC 7601
SE +/- 0.43, N = 11
42.57
2 x EPYC 7601
SE +/- 1.20, N = 3
27.27
Xeon E5-2687W v3
SE +/- 1.35, N = 3
91.39
Xeon Silver 4108
SE +/- 1.70, N = 3
133.28
2 x Xeon Gold 6138
SE +/- 1.66, N = 3
35.33
2 x EPYC 7501
SE +/- 0.32, N = 12
28.50
2 X EPYC 7501
SE +/- 0.78, N = 12
29.25
DUAL EPYC 7501
SE +/- 0.43, N = 12
29.21
2p epyc 7501
SE +/- 0.36, N = 12
28.44
30
60
90
120
150



Timed LLVM Compilation 6.0.1
Time To Compile
Seconds, Fewer Is Better
EPYC 7251
652
EPYC 7351P
318
EPYC 7401P
284
EPYC 7551
250
EPYC 7601
240
2 x EPYC 7601
151
Xeon E5-2687W v3
514
Xeon Silver 4108
739
2 x Xeon Gold 6138
176
2 x EPYC 7501
158
2 X EPYC 7501
183
DUAL EPYC 7501
188
2p epyc 7501
162
160
320
480
640
800



POV-Ray 3.7.0.7
Trace Time
Seconds, Fewer Is Better
EPYC 7251
SE +/- 0.10, N = 3
71.54
EPYC 7351P
SE +/- 0.06, N = 3
36.91
EPYC 7401P
SE +/- 0.24, N = 3
29.33
EPYC 7551
SE +/- 0.08, N = 3
-lSDL -lIlmImf -lImath -lHalf -lIex -lIexMath -lIlmThread -lpthread
23.35
EPYC 7601
SE +/- 0.08, N = 3
22.84
2 x EPYC 7601
SE +/- 0.07, N = 3
-lSDL -lIlmImf -lImath -lHalf -lIex -lIexMath -lIlmThread -lpthread
12.75
Xeon E5-2687W v3
SE +/- 0.03, N = 3
-lSDL -lIlmImf -lImath -lHalf -lIex -lIexMath -lIlmThread -lpthread
57.48
Xeon Silver 4108
SE +/- 0.10, N = 3
-lSDL -lIlmImf -lImath -lHalf -lIex -lIexMath -lIlmThread -lpthread
109.54
2 x Xeon Gold 6138
SE +/- 0.05, N = 3
-lSDL -lIlmImf -lImath -lHalf -lIex -lIexMath -lIlmThread -lpthread
18.99
2 x EPYC 7501
SE +/- 0.09, N = 3
13.41
2 X EPYC 7501
SE +/- 0.19, N = 3
16.55
DUAL EPYC 7501
SE +/- 0.05, N = 3
16.25
2p epyc 7501
SE +/- 0.14, N = 3
13.12
20
40
60
80
100
1. (CXX) g++ options: -pipe -O3 -ffast-math -march=native -pthread -lXpm -lSM -lICE -lX11 -ltiff -ljpeg -lpng -lz -lrt -lm -lboost_thread -lboost_system



Primesieve 7.1
1e12 Prime Number Generation
Seconds, Fewer Is Better
EPYC 7251
SE +/- 0.13, N = 3
-march=native
42.44
EPYC 7351P
SE +/- 0.08, N = 3
-march=native
20.65
EPYC 7401P
SE +/- 0.09, N = 3
-march=native
16.86
EPYC 7551
SE +/- 0.01, N = 3
-march=native
13.03
EPYC 7601
SE +/- 0.02, N = 3
-march=native
12.65
2 x EPYC 7601
SE +/- 0.03, N = 3
-march=native
6.35
Xeon E5-2687W v3
SE +/- 0.04, N = 3
-march=native
36.29
Xeon Silver 4108
SE +/- 0.14, N = 3
-march=native
48.07
2 x Xeon Gold 6138
SE +/- 0.04, N = 3
-march=native
8.81
2 x EPYC 7501
SE +/- 0.03, N = 3
6.09
2 X EPYC 7501
SE +/- 0.21, N = 12
7.28
DUAL EPYC 7501
SE +/- 0.26, N = 12
7.54
2p epyc 7501
SE +/- 0.03, N = 3
6.12
11
22
33
44
55
1. (CXX) g++ options: -O3 -lpthread



m-queens 1.1
Time To Solve
Seconds, Fewer Is Better
EPYC 7251
SE +/- 0.33, N = 3
-O3
106.66
EPYC 7351P
SE +/- 0.10, N = 3
-O3
54.45
EPYC 7401P
SE +/- 0.08, N = 3
-O3
42.04
EPYC 7551
SE +/- 0.10, N = 3
-O3
33.91
EPYC 7601
SE +/- 0.08, N = 3
-O3
32.16
2 x EPYC 7601
SE +/- 0.11, N = 3
-O3
19.00
Xeon E5-2687W v3
SE +/- 0.08, N = 3
-O3
88.51
Xeon Silver 4108
SE +/- 0.08, N = 3
-O3
176.03
2 x Xeon Gold 6138
SE +/- 0.06, N = 3
-O3
29.38
2 x EPYC 7501
SE +/- 0.08, N = 3
19.62
2 X EPYC 7501
SE +/- 0.30, N = 12
24.39
DUAL EPYC 7501
SE +/- 0.07, N = 3
24.75
2p epyc 7501
SE +/- 0.05, N = 3
19.74
40
80
120
160
200
1. (CXX) g++ options: -fopenmp -march=native -O2



Tachyon 0.98.9
Total Time
Seconds, Fewer Is Better
EPYC 7251
SE +/- 0.12, N = 3
7.81
EPYC 7351P
SE +/- 0.05, N = 3
3.97
EPYC 7401P
SE +/- 0.04, N = 3
3.03
EPYC 7551
SE +/- 0.01, N = 3
2.57
EPYC 7601
SE +/- 0.03, N = 3
2.38
2 x EPYC 7601
SE +/- 0.05, N = 3
1.46
Xeon E5-2687W v3
SE +/- 0.01, N = 3
6.05
Xeon Silver 4108
SE +/- 0.01, N = 3
9.80
2 x Xeon Gold 6138
SE +/- 0.03, N = 3
2.09
2 x EPYC 7501
SE +/- 0.03, N = 12
1.35
2 X EPYC 7501
SE +/- 0.03, N = 3
2.11
DUAL EPYC 7501
SE +/- 0.02, N = 3
2.17
2p epyc 7501
SE +/- 0.02, N = 12
1.41
3
6
9
12
15
1. (CC) gcc options: -m32 -O3 -fomit-frame-pointer -ffast-math -ltachyon -lm -lpthread



OpenSSL 1.1.1
RSA 4096-bit Performance
Signs Per Second, More Is Better
EPYC 7251
SE +/- 0.41, N = 3
-march=native
1242
EPYC 7351P
SE +/- 0.87, N = 3
-march=native
2485
EPYC 7401P
SE +/- 17.88, N = 3
-march=native
3358
EPYC 7551
SE +/- 21.97, N = 3
-march=native
4328
EPYC 7601
SE +/- 4.53, N = 3
-march=native
4515
2 x EPYC 7601
SE +/- 13.53, N = 3
-march=native
9233
Xeon E5-2687W v3
SE +/- 0.17, N = 3
-march=native
1458
Xeon Silver 4108
SE +/- 1.39, N = 3
-march=native
1281
2 x Xeon Gold 6138
SE +/- 52.87, N = 3
-march=native
7838
2 x EPYC 7501
SE +/- 5.98, N = 3
8878
2 X EPYC 7501
SE +/- 23.53, N = 3
6355
DUAL EPYC 7501
SE +/- 76.91, N = 3
6499
2p epyc 7501
SE +/- 13.03, N = 3
8876
2K
4K
6K
8K
10K
1. (CC) gcc options: -pthread -m64 -O3 -lssl -lcrypto -ldl



Sysbench 2018-07-28
Test: CPU
Events Per Second, More Is Better
EPYC 7251
SE +/- 2.03, N = 3
-march=native
12102
EPYC 7351P
SE +/- 9.99, N = 3
-march=native
24174
EPYC 7401P
SE +/- 7.85, N = 3
-march=native
34891
EPYC 7551
SE +/- 46.82, N = 3
-march=native
42199
EPYC 7601
SE +/- 37.77, N = 3
-march=native
44813
2 x EPYC 7601
SE +/- 263.79, N = 3
-march=native
89107
Xeon E5-2687W v3
SE +/- 5.87, N = 3
-march=native
16625
Xeon Silver 4108
SE +/- 0.69, N = 3
-march=native
9642
2 x Xeon Gold 6138
SE +/- 127.33, N = 3
-march=native
60825
2 x EPYC 7501
SE +/- 65.25, N = 3
-march=amdfam10
86139
2 X EPYC 7501
SE +/- 841.80, N = 7
-march=amdfam10
64100
DUAL EPYC 7501
SE +/- 941.86, N = 12
-march=amdfam10
62727
2p epyc 7501
SE +/- 73.80, N = 3
-march=amdfam10
85988
20K
40K
60K
80K
100K
1. (CC) gcc options: -pthread -O3 -funroll-loops -ggdb3 -rdynamic -ldl -laio -lm



Blender 2.79a
Blend File: BMW27 - Compute: CPU-Only
Seconds, Fewer Is Better
EPYC 7251
335.53
EPYC 7351P
164.30
EPYC 7401P
130.82
EPYC 7551
104.87
EPYC 7601
101.70
2 x EPYC 7601
57.80
Xeon E5-2687W v3
245.61
Xeon Silver 4108
407.11
2 x Xeon Gold 6138
77.91
2 x EPYC 7501
60.00
2 X EPYC 7501
69.19
DUAL EPYC 7501
70.62
2p epyc 7501
60.35
90
180
270
360
450



Blender 2.79a
Blend File: Barbershop - Compute: CPU-Only
Seconds, Fewer Is Better
EPYC 7251
1797
EPYC 7351P
851
EPYC 7401P
666
EPYC 7551
531
EPYC 7601
504
2 x EPYC 7601
312
Xeon E5-2687W v3
1183
Xeon Silver 4108
1894
2 x Xeon Gold 6138
376
2 X EPYC 7501
334
DUAL EPYC 7501
362
2p epyc 7501
314
400
800
1200
1600
2000



RAR Compression 5.6.1
Linux Source Tree Archiving To RAR
Seconds, Fewer Is Better
EPYC 7251
SE +/- 2.74, N = 3
186.00
EPYC 7351P
SE +/- 2.12, N = 3
149.00
EPYC 7401P
SE +/- 2.05, N = 3
150.00
EPYC 7551
SE +/- 1.75, N = 9
157.00
EPYC 7601
SE +/- 1.91, N = 3
143.00
2 x EPYC 7601
SE +/- 1.44, N = 3
109.00
Xeon E5-2687W v3
SE +/- 1.19, N = 3
97.53
Xeon Silver 4108
SE +/- 0.18, N = 3
147.00
2 x Xeon Gold 6138
SE +/- 1.08, N = 3
116.00
2 X EPYC 7501
SE +/- 1.93, N = 3
149.34
DUAL EPYC 7501
SE +/- 0.55, N = 3
152.81
2p epyc 7501
SE +/- 3.14, N = 3
161.66
40
80
120
160
200



Chaos Group V-RAY 1.1.0
Mode: CPU
Seconds, Fewer Is Better
EPYC 7251
SE +/- 0.06, N = 3
116.03
EPYC 7351P
SE +/- 0.08, N = 3
59.25
EPYC 7401P
SE +/- 0.45, N = 3
48.13
EPYC 7551
SE +/- 0.40, N = 12
40.37
EPYC 7601
SE +/- 0.37, N = 3
39.32
2 x EPYC 7601
SE +/- 0.32, N = 3
25.40
Xeon E5-2687W v3
SE +/- 0.24, N = 3
93.93
Xeon Silver 4108
SE +/- 0.41, N = 3
137.93
2 x Xeon Gold 6138
SE +/- 0.13, N = 3
31.28
30
60
90
120
150



Open Porous Media Git
OPM Benchmark: Flow MPI Extra - Threads: 8
Seconds, Fewer Is Better
EPYC 7251
SE +/- 1.23, N = 3
460
EPYC 7351P
SE +/- 4.84, N = 3
371
EPYC 7401P
SE +/- 0.92, N = 3
360
EPYC 7601
SE +/- 0.77, N = 3
353
2 x EPYC 7601
SE +/- 1.06, N = 3
334
2 x Xeon Gold 6138
SE +/- 1.33, N = 3
374
100
200
300
400
500
1. EPYC 7251: Build Time Sat Oct 13 20:57:42 EDT 2018;
2. EPYC 7351P: Build Time Sun Oct 14 07:37:41 EDT 2018;
3. EPYC 7401P: Build Time Sat Oct 13 14:49:03 EDT 2018;
4. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
5. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
6. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;



Open Porous Media Git
OPM Benchmark: Flow MPI Extra - Threads: 8 - Solver Time
Seconds, Fewer Is Better
EPYC 7251
SE +/- 1.19, N = 3
453
EPYC 7351P
SE +/- 4.79, N = 3
364
EPYC 7401P
SE +/- 0.92, N = 3
354
EPYC 7601
SE +/- 0.78, N = 3
347
2 x EPYC 7601
SE +/- 1.06, N = 3
328
2 x Xeon Gold 6138
SE +/- 1.32, N = 3
367
100
200
300
400
500
1. EPYC 7251: Build Time Sat Oct 13 20:57:42 EDT 2018;
2. EPYC 7351P: Build Time Sun Oct 14 07:37:41 EDT 2018;
3. EPYC 7401P: Build Time Sat Oct 13 14:49:03 EDT 2018;
4. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
5. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
6. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;



Open Porous Media Git
OPM Benchmark: Flow MPI Norne - Threads: 8
Seconds, Fewer Is Better
EPYC 7251
SE +/- 2.09, N = 3
158
EPYC 7351P
SE +/- 1.68, N = 6
119
EPYC 7401P
SE +/- 0.34, N = 3
115
EPYC 7601
SE +/- 0.04, N = 3
114
2 x EPYC 7601
SE +/- 1.71, N = 3
114
2 x Xeon Gold 6138
SE +/- 0.24, N = 3
123
30
60
90
120
150
1. EPYC 7251: Build Time Sat Oct 13 20:57:42 EDT 2018;
2. EPYC 7351P: Build Time Sun Oct 14 07:37:41 EDT 2018;
3. EPYC 7401P: Build Time Sat Oct 13 14:49:03 EDT 2018;
4. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
5. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
6. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;
Open Porous Media Git
OPM Benchmark: Flow MPI Norne - Threads: 8 - Solver Time
Seconds, Fewer Is Better
EPYC 7251
SE +/- 2.08, N = 3
155
EPYC 7351P
SE +/- 1.68, N = 6
118
EPYC 7401P
SE +/- 0.34, N = 3
113
EPYC 7601
SE +/- 0.04, N = 3
112
2 x EPYC 7601
SE +/- 1.71, N = 3
112
2 x Xeon Gold 6138
SE +/- 0.24, N = 3
121
30
60
90
120
150
1. EPYC 7251: Build Time Sat Oct 13 20:57:42 EDT 2018;
2. EPYC 7351P: Build Time Sun Oct 14 07:37:41 EDT 2018;
3. EPYC 7401P: Build Time Sat Oct 13 14:49:03 EDT 2018;
4. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
5. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
6. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;



Open Porous Media Git
OPM Benchmark: Flow MPI Extra - Threads: 16
Seconds, Fewer Is Better
EPYC 7351P
SE +/- 2.44, N = 3
421
EPYC 7401P
SE +/- 1.39, N = 3
413
EPYC 7601
SE +/- 3.27, N = 3
415
2 x EPYC 7601
SE +/- 0.65, N = 3
294
2 x Xeon Gold 6138
SE +/- 0.71, N = 3
360
90
180
270
360
450
1. EPYC 7351P: Build Time Sun Oct 14 07:37:41 EDT 2018;
2. EPYC 7401P: Build Time Sat Oct 13 14:49:03 EDT 2018;
3. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
4. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
5. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;
Open Porous Media Git
OPM Benchmark: Flow MPI Extra - Threads: 16 - Solver Time
Seconds, Fewer Is Better
EPYC 7351P
SE +/- 2.46, N = 3
415
EPYC 7401P
SE +/- 1.35, N = 3
407
EPYC 7601
SE +/- 3.26, N = 3
409
2 x EPYC 7601
SE +/- 0.66, N = 3
288
2 x Xeon Gold 6138
SE +/- 0.69, N = 3
353
90
180
270
360
450
1. EPYC 7351P: Build Time Sun Oct 14 07:37:41 EDT 2018;
2. EPYC 7401P: Build Time Sat Oct 13 14:49:03 EDT 2018;
3. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
4. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
5. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;



Open Porous Media Git
OPM Benchmark: Flow MPI Extra - Threads: 32
Seconds, Fewer Is Better
EPYC 7601
SE +/- 1.43, N = 3
360
2 x EPYC 7601
SE +/- 0.91, N = 3
219
2 x Xeon Gold 6138
SE +/- 2.17, N = 3
258
80
160
240
320
400
1. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
2. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
3. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;
Open Porous Media Git
OPM Benchmark: Flow MPI Extra - Threads: 32 - Solver Time
Seconds, Fewer Is Better
EPYC 7601
SE +/- 1.42, N = 3
353
2 x EPYC 7601
SE +/- 0.91, N = 3
213
2 x Xeon Gold 6138
SE +/- 2.19, N = 3
251
80
160
240
320
400
1. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
2. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
3. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;



Open Porous Media Git
OPM Benchmark: Flow MPI Norne - Threads: 16
Seconds, Fewer Is Better
EPYC 7351P
SE +/- 0.91, N = 3
89.66
EPYC 7401P
SE +/- 1.11, N = 3
84.23
EPYC 7601
SE +/- 0.49, N = 3
85.46
2 x EPYC 7601
SE +/- 1.40, N = 3
61.93
2 x Xeon Gold 6138
SE +/- 0.40, N = 3
73.18
20
40
60
80
100
1. EPYC 7351P: Build Time Sun Oct 14 07:37:41 EDT 2018;
2. EPYC 7401P: Build Time Sat Oct 13 14:49:03 EDT 2018;
3. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
4. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
5. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;
Open Porous Media Git
OPM Benchmark: Flow MPI Norne - Threads: 16 - Solver Time
Seconds, Fewer Is Better
EPYC 7351P
SE +/- 0.91, N = 3
87.79
EPYC 7401P
SE +/- 1.12, N = 3
82.42
EPYC 7601
SE +/- 0.49, N = 3
83.62
2 x EPYC 7601
SE +/- 1.39, N = 3
60.38
2 x Xeon Gold 6138
SE +/- 0.38, N = 3
71.22
20
40
60
80
100
1. EPYC 7351P: Build Time Sun Oct 14 07:37:41 EDT 2018;
2. EPYC 7401P: Build Time Sat Oct 13 14:49:03 EDT 2018;
3. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
4. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
5. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;



Open Porous Media Git
OPM Benchmark: Flow MPI Norne - Threads: 32
Seconds, Fewer Is Better
EPYC 7601
SE +/- 1.06, N = 3
107.75
2 x EPYC 7601
SE +/- 0.55, N = 3
72.20
2 x Xeon Gold 6138
SE +/- 1.65, N = 3
89.21
20
40
60
80
100
1. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
2. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
3. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;
Open Porous Media Git
OPM Benchmark: Flow MPI Norne - Threads: 32 - Solver Time
Seconds, Fewer Is Better
EPYC 7601
SE +/- 1.03, N = 3
105.54
2 x EPYC 7601
SE +/- 0.54, N = 3
70.34
2 x Xeon Gold 6138
SE +/- 1.65, N = 3
86.86
20
40
60
80
100
1. EPYC 7601: Build Time Sat Oct 13 09:15:23 EDT 2018;
2. 2 x EPYC 7601: Build Time Fri Oct 12 08:04:54 EDT 2018;
3. 2 x Xeon Gold 6138: Build Time Fri Oct 12 18:12:17 EDT 2018;



m-queens 1.2
Time To Solve
Seconds, Fewer Is Better
EPYC 7251
SE +/- 0.96, N = 3
-O3
100.15
EPYC 7351P
SE +/- 0.01, N = 3
-O3
49.70
EPYC 7401P
SE +/- 0.23, N = 3
-O3
36.96
EPYC 7551
SE +/- 0.05, N = 3
-O3
28.42
EPYC 7601
SE +/- 0.05, N = 3
-O3
27.37
2 x EPYC 7601
SE +/- 0.01, N = 3
13.67
Xeon E5-2687W v3
SE +/- 0.01, N = 3
-O3
84.58
Xeon Silver 4108
SE +/- 0.01, N = 3
-O3
177.57
2 x Xeon Gold 6138
SE +/- 0.05, N = 3
-O3
28.11
2 X EPYC 7501
SE +/- 0.47, N = 12
20.36
DUAL EPYC 7501
SE +/- 0.31, N = 12
21.15
2p epyc 7501
SE +/- 0.01, N = 3
14.01
40
80
120
160
200
1. (CXX) g++ options: -fopenmp -march=native -O2
NAMD 2.13b1
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 245 / Avg: 506.16 / Max: 569.4
2 x Xeon Gold 6138
Min: 101.2 / Avg: 374.34 / Max: 423.1
100
200
300
400
500


John The Ripper 1.8.0-jumbo-1
Test: Blowfish
Real C/S Per Watt, More Is Better
2 x EPYC 7601
202.81
2 x Xeon Gold 6138
155.38
40
80
120
160
200
John The Ripper 1.8.0-jumbo-1
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 153.5 / Avg: 346.26 / Max: 426
2 x Xeon Gold 6138
Min: 98 / Avg: 316.53 / Max: 370.6
80
160
240
320
400
John The Ripper 1.8.0-jumbo-1
Test: Traditional DES
Real C/S Per Watt, More Is Better
2 x EPYC 7601
637839.75
2 x Xeon Gold 6138
421920.39
140K
280K
420K
560K
700K
John The Ripper 1.8.0-jumbo-1
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 147.1 / Avg: 405.18 / Max: 508.1
2 x Xeon Gold 6138
Min: 282.3 / Avg: 353.73 / Max: 376.9
90
180
270
360
450


7-Zip Compression 16.02
Compress Speed Test
MIPS Per Watt, More Is Better
2 x EPYC 7601
406.85
2 x Xeon Gold 6138
453.40
100
200
300
400
500
7-Zip Compression 16.02
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 207.2 / Avg: 384.19 / Max: 499.2
2 x Xeon Gold 6138
Min: 100 / Avg: 322.76 / Max: 415.2
90
180
270
360
450
Stockfish 9
Total Time
Nodes Per Second Per Watt, More Is Better
2 x EPYC 7601
202014.26
2 x Xeon Gold 6138
181793.69
40K
80K
120K
160K
200K
Stockfish 9
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 156.8 / Avg: 507.28 / Max: 543.7
2 x Xeon Gold 6138
Min: 95.8 / Avg: 378.57 / Max: 442.5
100
200
300
400
500


asmFish 2017-09-19
1024 Hash Memory, 26 Depth
Nodes/second Per Watt, More Is Better
2 x EPYC 7601
232034.75
2 x Xeon Gold 6138
219925.44
50K
100K
150K
200K
250K
asmFish 2017-09-19
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 307.4 / Avg: 519.61 / Max: 535.2
2 x Xeon Gold 6138
Min: 97.6 / Avg: 370.28 / Max: 415
90
180
270
360
450
ebizzy 0.3
Records/s Per Watt, More Is Better
2 x EPYC 7601
3896.18
2 x Xeon Gold 6138
3128.95
800
1600
2400
3200
4000
ebizzy 0.3
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 149.9 / Avg: 440.8 / Max: 493.8
2 x Xeon Gold 6138
Min: 98.1 / Avg: 318.58 / Max: 380.7
90
180
270
360
450


Timed Linux Kernel Compilation 4.18
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 151.6 / Avg: 349.35 / Max: 553.9
2 x Xeon Gold 6138
Min: 105.3 / Avg: 268.98 / Max: 401.2
100
200
300
400
500
Timed LLVM Compilation 6.0.1
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 150.1 / Avg: 394.37 / Max: 559.9
2 x Xeon Gold 6138
Min: 105.7 / Avg: 322.1 / Max: 426.6
100
200
300
400
500
POV-Ray 3.7.0.7
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 306.8 / Avg: 456.98 / Max: 549.2
2 x Xeon Gold 6138
Min: 101.7 / Avg: 315.94 / Max: 389.6
100
200
300
400
500
Primesieve 7.1
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 150.2 / Avg: 298.63 / Max: 498.1
2 x Xeon Gold 6138
Min: 98.8 / Avg: 277.44 / Max: 361.2
90
180
270
360
450


m-queens 1.1
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 146 / Avg: 360.7 / Max: 423.4
2 x Xeon Gold 6138
Min: 98.1 / Avg: 343.78 / Max: 384.4
80
160
240
320
400
Tachyon 0.98.9
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 111.9 / Avg: 132.6 / Max: 153.3
2 x Xeon Gold 6138
30
60
90
120
150
OpenSSL 1.1.1
RSA 4096-bit Performance
Signs Per Second Per Watt, More Is Better
2 x EPYC 7601
25.14
2 x Xeon Gold 6138
22.27
6
12
18
24
30
OpenSSL 1.1.1
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 148.5 / Avg: 367.33 / Max: 432
2 x Xeon Gold 6138
Min: 102.1 / Avg: 351.96 / Max: 417.1
80
160
240
320
400

Sysbench 2018-07-28

Test: CPU



Sysbench 2018-07-28


System Power Consumption Monitor


Blender 2.79a


System Power Consumption Monitor

Blender 2.79a


System Power Consumption Monitor


RAR Compression 5.6.1
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 196.5 / Avg: 233.55 / Max: 247.5
2 x Xeon Gold 6138
Min: 97.4 / Avg: 177.75 / Max: 200.5
40
80
120
160
200
Chaos Group V-RAY 1.1.0
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 204.6 / Avg: 447.05 / Max: 540.1
2 x Xeon Gold 6138
Min: 101.4 / Avg: 318.84 / Max: 431.6
100
200
300
400
500
Open Porous Media Git
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 223.5 / Avg: 306.85 / Max: 315.2
2 x Xeon Gold 6138
Min: 97.6 / Avg: 307.03 / Max: 359.1
60
120
180
240
300
Open Porous Media Git
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 151.7 / Avg: 298.72 / Max: 306
2 x Xeon Gold 6138
Min: 95 / Avg: 301.99 / Max: 346.7
60
120
180
240
300



Open Porous Media Git
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 153.5 / Avg: 368.88 / Max: 384.1
2 x Xeon Gold 6138
Min: 98.2 / Avg: 379.34 / Max: 418
70
140
210
280
350
Open Porous Media Git
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 154.6 / Avg: 402.18 / Max: 422.3
2 x Xeon Gold 6138
Min: 113.6 / Avg: 384.77 / Max: 419.3
80
160
240
320
400
Open Porous Media Git
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 182.3 / Avg: 349.46 / Max: 361.8
2 x Xeon Gold 6138
Min: 113.4 / Avg: 369.89 / Max: 407.5
70
140
210
280
350
Open Porous Media Git
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 153.6 / Avg: 370.78 / Max: 384.9
2 x Xeon Gold 6138
Min: 106.6 / Avg: 379.29 / Max: 423.4
80
160
240
320
400


m-queens 1.2
System Power Consumption Monitor
Watts, Fewer Is Better
2 x EPYC 7601
Min: 154.8 / Avg: 381.94 / Max: 441.5
2 x Xeon Gold 6138
Min: 107.7 / Avg: 319.11 / Max: 365.2
80
160
240
320
400
System Power Consumption Monitor
Phoronix Test Suite System Monitoring
Watts
2 x EPYC 7601
Min: 145.4 / Avg: 276.23 / Max: 569.4
2 x Xeon Gold 6138
Min: 94.1 / Avg: 251.75 / Max: 442.5
100
200
300
400
500
Stream 2013-01-17
System Power Consumption Monitor
Watts, Fewer Is Better
2 x Xeon Gold 6138
20
40
60
80
100


These geometric means are based upon test groupings / test suites for this result file.




Geometric mean based upon tests: pts/stockfish, pts/asmfish and pts/m-queens




Geometric mean based upon tests: pts/build-linux-kernel and pts/build-llvm




Geometric mean based upon tests: pts/stockfish, pts/build-llvm, pts/compress-7zip, pts/john-the-ripper, pts/openssl and pts/tachyon




Geometric mean based upon tests: pts/asmfish, pts/build-llvm, pts/build-linux-kernel, pts/compress-7zip, pts/ebizzy, pts/john-the-ripper, pts/openssl, pts/m-queens, pts/namd, pts/povray, pts/primesieve, pts/stockfish, pts/sysbench, pts/tachyon, pts/v-ray and pts/blender




Geometric mean based upon tests: pts/tachyon, pts/povray, pts/blender and pts/v-ray




Geometric mean based upon tests: pts/blender, pts/sysbench, pts/tachyon, pts/povray, pts/stockfish, pts/m-queens, pts/primesieve, pts/john-the-ripper, pts/namd, pts/asmfish, pts/ebizzy, pts/compress-7zip, pts/build-linux-kernel, pts/build-llvm and pts/v-ray




Geometric mean based upon tests: pts/build-linux-kernel and pts/build-llvm




Geometric mean based upon tests: pts/tachyon and pts/povray




Geometric mean based upon tests: pts/tachyon, pts/povray, pts/blender and pts/v-ray



Geometric mean based upon tests: pts/ebizzy and pts/openssl



Geometric mean based upon tests: pts/namd, pts/john-the-ripper, pts/compress-7zip, pts/stockfish, pts/asmfish, pts/build-linux-kernel, pts/build-llvm, pts/povray, pts/m-queens, pts/openssl, pts/sysbench and pts/blender



Geometric mean based upon tests: pts/blender and pts/sysbench

This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 06:12.