

www.phoronix-test-suite.com

OpenArena - i7-4702mq + HD4600

Intel Core i7-4702MQ testing with a LENOVO 20AWS05T00 (GLET98WW 2.52 BIOS) and Intel Haswell Mobile 2GB on Arch Linux via the Phoronix Test Suite.

Test Systems:

Intel Haswell Mobile

Processor: Intel Core i7-4702MQ @ 3.20GHz (4 Cores / 8 Threads), Motherboard: LENOVO 20AWS05T00 (GLET98WW 2.52 BIOS), Chipset: Intel Xeon E3-1200 v3/4th, Memory: 12288MB, Disk: 525GB Crucial_CT525MX3 + 256GB NT-256, Graphics: Intel Haswell Mobile 2GB (1150MHz), Audio: Intel Xeon E3-1200 v3/4th, Network: Intel I217-LM + Broadcom BCM43224 802.11a/b/g/n

OS: Arch Linux, Kernel: 5.2.9-arch1-1-ARCH (x86_64), Desktop: GNOME Shell 3.32.2, Display Server: X Server 1.20.4, Display Driver: intel 2.99.917, OpenGL: 4.5 Mesa 19.1.5, OpenCL: OpenCL 2.1 LINUX, Compiler: GCC 9.1.0, File-System: ext4, Screen Resolution: 1920x1080


Processor Notes: Scaling Governor: intel_pstate performance
Graphics Notes: SNA

OpenArena - i7-4702mq + HD4600

Security Notes: l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Vulnerable: Clear buffers attempted no microcode; SMT vulnerable + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: conditional RSB filling

	Intel Haswell Mobile
OpenArena - 1920 x 1080 (FPS)	23.13
Standard Deviation	1.3%

OpenArena - i7-4702mq + HD4600



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 08:21.