

www.phoronix-test-suite.com

Specs

testing

Test Systems:

test

Processor: Intel Core i3-3217U @ 1.80GHz (2 Cores / 4 Threads), Motherboard: ASUS X550CA v1.0 (X550CA.300 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 4096 MB + 8192 MB DDR3-1600MT/s, Disk: 80GB TOSHIBA MK8034GS, Graphics: Intel Ivybridge Mobile 2GB (1050MHz), Audio: Realtek ALC270, Network: Realtek RTL8111/8168/8411 + Qualcomm Atheros AR9485

OS: Parrot 4.7, Kernel: 5.2.0-2parrot1-amd64 (x86_64), Display Server: X Server 1.20.4, Display Driver: modesetting 1.20.4, OpenGL: 4.2 Mesa 19.1.4, OpenCL: OpenCL 1.2 pocl 1.3 +Asserts LLVM 6.0.1 SLEEF DISTRO POCL_DEBUG + OpenCL 1.2 LINUX, Compiler: GCC 8.3.0 + Clang 7.0.1-9+b1, File-System: xfs, Screen Resolution: 1366x768


Processor Notes: Scaling Governor: intel_pstate powersave
Security Notes: l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Mitigation of Clear buffers; SMT vulnerable + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization +

Specs

spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: conditional RSB filling

	test
Unigine Heaven - 1366 x 768 - Fullscreen - OpenGL (FPS)	6.00

Specs



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 13:06.