

www.phoronix-test-suite.com

Superfast screening example (timtaw test suite).

Example results using the timtaw/screening-superfast test suite.

Automated Executive Summary

Xps 9550 Arch rolling Superfast had the most wins, coming in first place for 60% of the tests.

Based on the geometric mean of all complete results, the fastest (Xps 9550 Arch rolling Superfast) was 7.328x the speed of the slowest (Samsung RV515 (Ubuntu 14.04) [Superfast]). Chenbro RM217 (Ubuntu 14.04) [Superfast] was 0.379x the speed of Xps 9550 Arch rolling Superfast, Chenbro RM217 (Ubuntu 14.04) RAID1 [Superfast] was 0.931x the speed of Chenbro RM217 (Ubuntu 14.04) [Superfast], Samsung X22 (Ubuntu 14.04) [Superfast] was 0.979x the speed of Chenbro RM217 (Ubuntu 14.04) RAID1 [Superfast], Samsung RV515 (Ubuntu 14.04) [Superfast] was 0.395x the speed of Samsung X22 (Ubuntu 14.04) [Superfast].

Test Systems:

Chenbro RM217 (Ubuntu 14.04) RAID1 [Superfast]

Processor: Intel Xeon L5420 @ 2.50GHz (4 Cores), Motherboard: Supermicro X7DB8, Memory: 32768MB, Disk: 2 x 500GB Western Digital WD5002ABYS-0, Graphics: radeondrmfb

OS: Ubuntu 14.04, Kernel: 3.13.0-125-generic (x86_64), Compiler: GCC 4.8.4, File-System: ext4, Screen Resolution: 1024x768

Environment Notes: _PMT_DEBUG_LEVEL=0
Disk Notes: DEADLINE / data=ordered,nosuid,relatime,rw

Chenbro RM217 (Ubuntu 14.04) [Superfast]

Processor: Intel Xeon L5420 @ 2.50GHz (4 Cores), Motherboard: Supermicro X7DB8, Memory: 32768MB, Disk: 2 x 500GB Western Digital WD5002ABYS-0, Graphics: radeondrmfb, Monitor: DELL E173FP

OS: Ubuntu 14.04, Kernel: 3.13.0-123-generic (x86_64), Compiler: GCC 4.8.4, File-System: ext4, Screen Resolution: 1280x1024

Environment Notes: _PMT_DEBUG_LEVEL=0
Disk Notes: DEADLINE / data=ordered,nosuid,relatime,rw

Samsung RV515 (Ubuntu 14.04) [Superfast]

Processor: AMD E-350 @ 1.60GHz (2 Cores), Motherboard: SAMSUNG RV415/RV415, Memory: 6144MB, Disk: 320GB Seagate ST9320423AS, Graphics: radeondrmfb (800/800MHz), Audio: Realtek ALC269VB

OS: Ubuntu 14.04, Kernel: 3.13.0-123-generic (x86_64), Compiler: GCC 4.8.4, File-System: ext4, Screen Resolution: 1366x768

Environment Notes: _PMT_DEBUG_LEVEL=0
Disk Notes: DEADLINE / data=ordered,nosuid,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

Samsung X22 (Ubuntu 14.04) [Superfast]

Processor: Intel Core 2 Duo T7500 @ 2.20GHz (2 Cores), Motherboard: SAMSUNG SX22S, Memory: 2048MB, Disk: 200GB Hitachi HTS54252, Graphics: radeondrmfb (450/500MHz), Audio: Realtek ALC262

OS: Ubuntu 14.04, Kernel: 3.13.0-125-generic (x86_64), Compiler: GCC 4.8.4, File-System: ext4, Screen Resolution: 1280x800

Environment Notes: _PMT_DEBUG_LEVEL=0
Disk Notes: DEADLINE / data=ordered,nosuid,relatime,rw
Processor Notes: Scaling Governor: acpi-cpufreq ondemand

Xps 9550 Arch rolling Superfast

Processor: Intel Core i7-6700HQ @ 3.50GHz (4 Cores / 8 Threads), Motherboard: Dell 0N7TVV (1.9.0 BIOS), Chipset: Intel Xeon E3-1200 v5/E3-1500, Memory: 16384MB, Disk: PC300 NVMe SK hynix 512GB, Graphics: Intel HD 530 2GB (1050MHz), Audio: Realtek ALC3266, Network: Qualcomm Atheros QCA6174 802.11ac

OS: Arch rolling, Kernel: 5.2.11-arch1-1-ARCH (x86_64), Desktop: LXDE, Display Server: X Server 1.20.5, Display Driver: intel 2.99.917, Compiler: GCC 9.1.0, File-System: ext4, Screen Resolution: 1920x1080


Compiler Notes: --disable-libssp --disable-libstdcxx-pch --disable-libunwind-exceptions --disable-werror --enable-__cxa_atexit --enable-cet=auto --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-default-ssp --enable-gnu-indirect-function --enable-gnu-unique-object --enable-install-libiberty

Superfast screening example (timtaw test suite).


--enable-languages=c,c++,ada,fortran,go,lto,objc,obj-c++ --enable-lto --enable-multilib --enable-plugin --enable-shared --enable-threads=posix --mandir=/usr/share/man --with-isl --with-linker-hash-style=gnu
Disk Notes: NONE / relatime,rw
Processor Notes: Scaling Governor: intel_pstate powersave
Security Notes: l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Mitigation of Clear buffers; SMT vulnerable + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: conditional RSB filling

	Chenbro RM217 (Ubuntu 14.04) RAID1 [Superfast]	Chenbro RM217 (Ubuntu 14.04) [Superfast]	Samsung RV515 (Ubuntu 14.04) [Superfast]	Samsung X22 (Ubuntu 14.04) [Superfast]	Xps 9550 Arch rolling Superfast
Flexible IO Tester - Rand Read - POSIX AIO - Yes - No - 4KB (IOPS)	172	172	120	110	
Normalized	100%	100%	69.77%	63.95%	
Standard Deviation	2.9%		1%	0.5%	
Flexible IO Tester - Rand Write - POSIX AIO - Yes - No - 4KB (MB/s)	129.93	156.23	107.41	19.92	
Normalized	83.17%	100%	68.75%	12.75%	
Standard Deviation	61%	26.3%	52.1%	34.5%	
Flexible IO Tester - Rand Write - POSIX AIO - Yes - No - 4KB (IOPS)	32479	39054	26849	4976	
Normalized	83.16%	100%	68.75%	12.74%	
Standard Deviation	61%	26.3%	52.2%	34.5%	
Stream - Copy (MB/s)	3711	3940	3173		12315
Normalized	30.13%	31.99%	25.77%		100%
Standard Deviation	0.1%	0.1%	0.5%		0.2%
SciMark - Composite (Mflops)	516	526	245	468	1464
Normalized	35.25%	35.93%	16.73%	31.97%	100%
Standard Deviation	0.3%	0.4%	1.3%	0.3%	0.4%
Himeno Benchmark - P.P.S (MFLOPS)	754	853	238	797	2139
Normalized	35.25%	39.88%	11.13%	37.26%	100%
Standard Deviation	1.6%	1.7%	1.2%	0.6%	0.2%


Superfast screening example (timtaw test suite).



Superfast screening example (timtaw test suite).




Superfast screening example (timtaw test suite).



Superfast screening example (timtaw test suite).

These geometric means are based upon test groupings / test suites for this result file.



Geometric mean based upon tests: pts/scimark2 and pts/himeno

This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 18:36.