

www.phoronix-test-suite.com

ODROID-H2 Intel Ubuntu Linux Benchmarks

ASROCK J4205-ITX Linux Benchmarks PSTATE MAX by frankk

Test Systems:

Raspberry Pi 2 Model B

Processor: ARMv7 rev 5 @ 0.90GHz (4 Cores), Motherboard: BCM2835 Raspberry Pi 2 Model B Rev 1.1, Memory: 927MB, Disk: 32GB GB2MW, Graphics: BCM2708

OS: Raspbian 9.6, Kernel: 4.14.79-v7+ (armv7l), Desktop: LXDE, Display Server: X Server 1.19.2, Compiler: GCC 6.3.0 20170516, File-System: ext4, Screen Resolution: 656x416

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc=auto --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --program-prefix=arm-linux-gnueabihf- --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv6 --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfp --with-target-system-zlib -v
Processor Notes: Scaling Governor: BCM2835 Freq ondemand
Python Notes: Python 2.7.13 + Python 3.5.3

Raspberry Pi 3 Model B

Processor: ARMv7 rev 4 @ 1.20GHz (4 Cores), Motherboard: BCM2835 Raspberry Pi 3 Model B Rev 1.2, Memory: 927MB, Disk: 32GB GB1QT, Graphics: BCM2708

OS: Raspbian 9.6, Kernel: 4.14.79-v7+ (armv7l), Desktop: LXDE, Display Server: X Server 1.19.2, Compiler: GCC 6.3.0 20170516, File-System: ext4, Screen Resolution: 656x416

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc=auto --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --program-prefix=arm-linux-gnueabihf- --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv6 --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfp --with-target-system-zlib -v
Processor Notes: Scaling Governor: BCM2835 Freq ondemand
Python Notes: Python 2.7.13 + Python 3.5.3

Raspberry Pi 3 Model B+

Processor: ARMv7 rev 4 @ 1.40GHz (4 Cores), Motherboard: BCM2835 Raspberry Pi 3 Model B Plus Rev 1.3, Memory: 927MB, Disk: 32GB GB2MW, Graphics: BCM2708

OS: Raspbian 9.6, Kernel: 4.14.79-v7+ (armv7l), Desktop: LXDE, Display Server: X Server 1.19.2, Compiler: GCC 6.3.0 20170516, File-System: ext4, Screen Resolution: 1824x984

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc=auto --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --program-prefix=arm-linux-gnueabihf- --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv6 --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfp --with-target-system-zlib -v
Processor Notes: Scaling Governor: BCM2835 Freq ondemand
Python Notes: Python 2.7.13 + Python 3.5.3

Raspberry Pi 3 Model A+

Processor: ARMv7 rev 4 @ 1.40GHz (4 Cores), Motherboard: BCM2835 Raspberry Pi 3 Model A Plus Rev 1.0, Memory: 431MB, Disk: 32GB SC32G, Graphics: BCM2708

OS: Raspbian 9.6, Kernel: 4.14.79-v7+ (armv7l), Desktop: LXDE, Display Server: X Server 1.19.2, Compiler: GCC 6.3.0 20170516, File-System: ext4, Screen Resolution: 1824x984

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc=auto --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --program-prefix=arm-linux-gnueabihf- --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv6 --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfp --with-target-system-zlib -v
Processor Notes: Scaling Governor: BCM2835 Freq ondemand
Python Notes: Python 2.7.13 + Python 3.5.3

ASUS Tinker Board

Processor: ARMv7 rev 1 @ 1.80GHz (4 Cores), Motherboard: Rockchip (Device Tree), Memory: 2048MB, Disk: 32GB GB1QT

OS: Debian 9.0, Kernel: 4.4.16-00006-g4431f98-dirty (armv7l), Desktop: LXDE, Display Server: X Server 1.18.4, Compiler: GCC 6.3.0 20170516, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc=auto --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --program-prefix=arm-linux-gnueabihf- --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb --with-target-system-zlib -v
Processor Notes: Scaling Governor: cpufreq-dt interactive

Python Notes: Python 2.7.13 + Python 3.5.3

Firefly ROC-RK3328-CC

Processor: Rockchip ARMv8 Cortex-A53 @ 1.39GHz (4 Cores), Motherboard: Firefly ROC-RK3328-CC, Memory: 2048MB, Disk: 32GB GB1QT

OS: Ubuntu 18.04, Kernel: 4.4.114 (aarch64), Display Server: X Server 1.18.4, Compiler: GCC 7.3.0, File-System: ext4, Screen Resolution: 1024x768

Compiler Notes: --build=aarch64-linux-gnu --disable-libquadmath --disable-libquadmath-support --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-fix-cortex-a53-843419 --enable-gnu-unique-object --enable-languages=c,ada,c++,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-plugin --enable-shared --enable-threads=posix --host=aarch64-linux-gnu --program-prefix=aarch64-linux-gnu- --target=aarch64-linux-gnu --with-as=/usr/bin/aarch64-linux-gnu-as --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-ld=/usr/bin/aarch64-linux-gnu-ld -v
Processor Notes: Scaling Governor: cpufreq-dt performance
Python Notes: Python 2.7.15rc1 + Python 3.6.5

ODROID-C2

Processor: Amlogic ARMv8 Cortex-A53 @ 1.54GHz (4 Cores), Motherboard: ODROID-C2, Memory: 2048MB, Disk: 32GB GB1QT, Graphics: OSD

OS: Ubuntu 18.04, Kernel: 3.16.57-20 (aarch64), Display Server: X Server 1.19.6, Compiler: GCC 7.3.0, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=aarch64-linux-gnu --disable-libquadmath --disable-libquadmath-support --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-fix-cortex-a53-843419 --enable-gnu-unique-object --enable-languages=c,ada,c++,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-plugin --enable-shared --enable-threads=posix --host=aarch64-linux-gnu --program-prefix=aarch64-linux-gnu- --target=aarch64-linux-gnu --with-as=/usr/bin/aarch64-linux-gnu-as --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-ld=/usr/bin/aarch64-linux-gnu-ld -v
Processor Notes: Scaling Governor: meson_cpufreq performance
Python Notes: Python 2.7.15rc1 + Python 3.6.5

ODROID-H2

Processor: Intel Celeron J4105 @ 2.50GHz (4 Cores), Motherboard: HARDKERNEL ODROID-H2 v1.0 (5.13 BIOS), Chipset: Intel Device 31f0, Memory: 32768MB, Disk: 500GB Western Digital WDS500G2X0C-00L350, Graphics: inteldrmfb (750MHz), Audio: Realtek ALC662 rev1, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 18.10, Kernel: 4.15.0-38-generic (x86_64), Display Server: X Server, Compiler: GCC 8.2.0, File-System: overlayfs, Screen Resolution: 1920x1080, System Layer: docker

Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: intel_pstate powersave
Python Notes: Python 2.7.15+ + Python 3.6.7
Security Notes: KPTI + __user pointer sanitization + Full generic retpoline IBPB IBRS_FW + SSB disabled via prctl and seccomp

1909120-FK-AROCKJ4105-CPUPERF

Processor: Intel Celeron J4105 @ 1.50GHz (4 Cores), Motherboard: ASRock J4105-ITX (P1.40 BIOS), Chipset: Intel Device 31f0, Memory: 1 x 16384 MB DDR4-2133MT/s CMSO16GX4M1A2133C1, Disk: 64GB KINGSTON SV100S2 + 500GB Seagate ST500LM021-1KJ15 + 16GB Storage Device, Graphics: inteldrmfb (750MHz), Audio: Realtek ALC892, Monitor: LCD VGA, Network: Realtek RTL8111/8168/8411

ODROID-H2 Intel Ubuntu Linux Benchmarks

OS: Debian 10, Kernel: 4.19.0-6-amd64 (x86_64), Desktop: GNOME Shell 3.30.2, Display Server: X Server, Compiler: GCC 8.3.0, File-System: ext4, Screen Resolution: 1280x1024

Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-bootstrap --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++ --enable-libmpx --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: intel_pstate performance
Python Notes: Python 2.7.16 + Python 3.7.3
Security Notes: l1tf: Not affected + mds: Not affected + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Enhanced IBRS IBPB: conditional RSB filling

	Raspberry Pi 2 Model B	Raspberry Pi 3 Model B	Raspberry Pi 3 Model B+	Raspberry Pi 3 Model A+	ASUS Tinker Board	Firefly ROC-RK3328-CC	ODROID-C2	ODROID-H2	1909120-FK-AROCKJ4105-CPUPERF
C-Ray - Total Time - 4.1.R.P.P (sec)	4364	2317	2111	2068	1579	2604	1559	454	721
Normalized	10.4%	19.59%	21.51%	21.95%	28.75%	17.43%	29.12%	100%	62.97%
Standard Deviation	1.6%	0.9%	0.2%	0.4%	0.3%	0.8%	1.9%	0%	0%
AOBench - 2048 x 2048 - Total Time (sec)	668	334	298	286	214	298	262	88.80	146.26
Normalized	13.29%	26.59%	29.8%	31.05%	41.5%	29.8%	33.89%	100%	60.71%
Standard Deviation	0.4%	0.1%	4.7%	0.4%	3.4%	0.4%	0.9%	0.5%	1.4%
Perl Benchmarks - Pod2html (sec)	2.39198371	1.29932392	1.21061075	1.15952401	0.74372882	1.70325877	1.08893965	0.32890668	0.53630882
Normalized	13.75%	25.31%	27.17%	28.37%	44.22%	19.31%	30.2%	100%	61.33%
Standard Deviation	1.9%	1.7%	0.8%	0.1%	1.1%	2.3%	4.7%	0.1%	1.4%
LAME MP3 Encoding - WAV To MP3 (sec)	515	352	302	304	158	315	265	73.22	107.38
Normalized	14.22%	20.8%	24.25%	24.09%	46.34%	23.24%	27.63%	100%	68.19%
Standard Deviation	0.3%	0.2%	0.3%	0.6%	0.6%	0.2%	0.1%	0%	0%
TTSIOD 3D Renderer - P.R.W.S.S.M (FPS)	11.20	15.99	16.51	17.25	22.38		22.51	77.58	46.36
Normalized	14.44%	20.61%	21.28%	22.24%	28.85%		29.02%	100%	59.76%
Standard Deviation	0.4%	3.3%	0.3%	1.6%	2.6%		2.2%	0.3%	1%
Tinymembench - Standard Memset (MB/s)	1188	1773	1826	1833	4199	5628	3737	7590	5245
Normalized	15.65%	23.36%	24.06%	24.15%	55.32%	74.15%	49.24%	100%	69.1%
Standard Deviation	0.5%	1.6%	2.4%	3.4%	0%	5.3%	0.1%	0.1%	0%
7-Zip Compression - C.S.T (MIPS)	1168	1858	1803	1993	2946	1536	2165	7244	5082
Normalized	16.12%	25.65%	24.89%	27.51%	40.67%	21.2%	29.89%	100%	70.15%
Standard Deviation	0.4%	0.3%	3%	0.7%	4%	0.5%	0.4%	0.9%	0.5%


ODROID-H2 Intel Ubuntu Linux Benchmarks

Tinymembench - Standard Memcpy (MB/s)	1000	1302	1285	1300	1532	1240	1718	5577	4215
Normalized	17.93%	23.35%	23.04%	23.31%	27.47%	22.23%	30.81%	100%	75.58%
Standard Deviation	2.5%	0.3%	1.2%	1.3%	0.3%	3.4%	0.4%	0.3%	0%
PHPBench - Performance / Cost - P.B.S (Score/Dollar)			1088	1614	944.85	1510	994.40	2317	
Normalized			46.97%	69.64%	40.78%	65.17%	42.92%	100%	
Perl Benchmarks - Performance / Cost - Pod2html (sec x Dollar)			42.37	28.99	48.34	59.61	65.34	36.51	
Normalized			68.42%	100%	59.97%	48.63%	44.37%	79.4%	
PyBench - Performance / Cost - T.F.A.T.T (Milliseconds x			742210	521850	605670	498470	757140	336441	
Normalized			45.33%	64.47%	55.55%	67.49%	44.44%	100%	
7-Zip Compression - Performance / Cost - C.S.T (MIPS/Dollar)			51.51	79.72	45.32	43.89	36.08	65.26	
Normalized			64.61%	100%	56.85%	55.06%	45.26%	81.86%	
Tinymembench - Performance / Cost - Standard Memcpy (MB/s/Dollar)			36.71	52.00	23.57	35.43	28.63		
Normalized			70.6%	100%	45.33%	68.13%	55.06%		
x264 - Performance / Cost - H.2.V.E (FPS/Dollar)			0.06		0.05	0.05	0.05	0.11	
Normalized			54.55%		45.45%	45.45%	45.45%	100%	
AOBench - Performance / Cost - 2048 x 2048 - Total Time (sec x Dollar)			10430	7150	13910	10430	15720	9857	
Normalized			68.55%	100%	51.4%	68.55%	45.48%	72.54%	
LAME MP3 Encoding - Performance / Cost - WAV To MP3 (sec x Dollar)			10570	7600	10270	11025	15900	8127	
Normalized			71.9%	100%	74%	68.93%	47.8%	93.51%	
TTSIOD 3D Renderer - Performance / Cost - P.R.W.S.S.M (FPS/Dollar)			0.47	0.69	0.34		0.38	0.70	
Normalized			67.14%	98.57%	48.57%		54.29%	100%	


ODROID-H2 Intel Ubuntu Linux Benchmarks


C-Ray - Performance / Cost - Total Time - 4.1.R.P.P (sec x Dollar)			73885	51700	**102635**	91140	93540	**50436**	
Normalized			68.26%	97.56%	49.14%	55.34%	53.92%	100%	
PyBench - T.F.A.T.T (Milliseconds)	**38087**	24328	21206	20874	9318	14242	12619	**3031**	4014
Normalized	7.96%	12.46%	14.29%	14.52%	32.53%	21.28%	24.02%	100%	75.51%
Standard Deviation	0.4%	0.4%	0.4%	0.2%	0.8%	0.4%	0.1%	0.1%	0.5%
PHPBench - P.B.S (Score)	**20920**	34426	38087	40338	61415	52852	59664	**257186**	158684
Normalized	8.13%	13.39%	14.81%	15.68%	23.88%	20.55%	23.2%	100%	61.7%
Standard Deviation	0.5%	0.2%	0.7%	0.2%	0.7%	0.5%	0.2%	0.1%	0.1%
x264 - H.2.V.E (FPS)	**1.13**	2.03	2.08		3.36	1.65	2.88	**12.03**	
Normalized	9.39%	16.87%	17.29%		27.93%	13.72%	23.94%	100%	
Standard Deviation	0.5%	0%	0.6%		0.5%	0.6%	0.2%	0.3%	
Perl Benchmarks - Performance / Cost - Interpreter (sec x Dollar)			0.28	0.24	0.28	**0.21**	0.33	**0.37**	
Normalized			75%	87.5%	75%	100%	63.64%	56.76%	
Git - Performance / Cost - T.T.C.C.G.C (sec x Dollar)			1721	1467	1672	1451	**2525**	**1442**	
Normalized			83.78%	98.31%	86.25%	99.34%	57.11%	100%	
Tinymembench - Performance / Cost - Standard Memset (MB/s/Dollar)								68.38	
Git - T.T.C.C.G.C (sec)	**96.99**	59.52	49.17	58.67	25.72	41.47	42.08	**12.99**	22.14
Normalized	13.39%	21.82%	26.42%	22.14%	50.51%	31.32%	30.87%	100%	58.67%
Standard Deviation	5.5%	10.2%	10.4%	1.7%	3.5%	2.5%	13.9%	2%	1.5%
Perl Benchmarks - Interpreter (sec)	**0.014098 89**	0.008430 41	0.008079 74	0.009716 87	0.004274 66	0.005988 28	0.005480 34	**0.003332 89**	0.003665 98
Normalized	23.64%	39.53%	41.25%	34.3%	77.97%	55.66%	60.82%	100%	90.91%
Standard Deviation	5.7%	3.3%	7%	14.5%	7.2%	0.2%	0.9%	0.6%	1.7%


ODROID-H2 Intel Ubuntu Linux Benchmarks




ODROID-H2 Intel Ubuntu Linux Benchmarks






Perl Benchmarks
Test: Pod2html
Seconds, Fewer Is Better
ODROID-H2
SE +/- 0.00017697, N = 3
0.32890668
1909120-FK-AROCKJ4105-CPUPERF
SE +/- 0.00438967, N = 3
0.53630882
ASUS Tinker Board
SE +/- 0.00463075, N = 3
0.74372882
ODROID-C2
SE +/- 0.01698561, N = 9
1.08893965
Raspberry Pi 3 Model A+
SE +/- 0.00092390, N = 3
1.15952401
Raspberry Pi 3 Model B+
SE +/- 0.00526666, N = 3
1.21061075
Raspberry Pi 3 Model B
SE +/- 0.01280566, N = 3
1.29932392
Firefly ROC-RK3328-CC
SE +/- 0.02244345, N = 3
1.70325877
Raspberry Pi 2 Model B
SE +/- 0.02647362, N = 3
2.39198371
0.5382
1.0764
1.6146
2.1528
2.691


LAME MP3 Encoding 3.100
WAV To MP3
Seconds, Fewer Is Better
ODROID-H2
SE +/- 0.01, N = 3
-lncurses
73.22
1909120-FK-AROCKJ4105-CPUPERF
SE +/- 0.01, N = 3
107.38
ASUS Tinker Board
SE +/- 0.54, N = 3
158.00
ODROID-C2
SE +/- 0.21, N = 3
265.00
Raspberry Pi 3 Model B+
SE +/- 0.45, N = 3
302.00
Raspberry Pi 3 Model A+
SE +/- 1.06, N = 3
304.00
Firefly ROC-RK3328-CC
SE +/- 0.28, N = 3
315.00
Raspberry Pi 3 Model B
SE +/- 0.32, N = 3
352.00
Raspberry Pi 2 Model B
SE +/- 0.82, N = 3
515.00
110
220
330
440
550
1. (CC) gcc options: -lm


ODROID-H2 Intel Ubuntu Linux Benchmarks




Tinymembench 2018-05-28
Standard Memset
MB/s, More Is Better
ODROID-H2
SE +/- 2.48, N = 3
7590
Firefly ROC-RK3328-CC
SE +/- 121.56, N = 6
5628
1909120-FK-AROCKJ4105-CPUPERF
SE +/- 0.90, N = 3
5245
ASUS Tinker Board
SE +/- 0.69, N = 3
4199
ODROID-C2
SE +/- 2.73, N = 3
3737
Raspberry Pi 3 Model A+
SE +/- 35.55, N = 3
1833
Raspberry Pi 3 Model B+
SE +/- 24.88, N = 3
1826
Raspberry Pi 3 Model B
SE +/- 16.88, N = 3
1773
Raspberry Pi 2 Model B
SE +/- 3.17, N = 3
1188
1600
3200
4800
6400
8000
1. (CC) gcc options: -O2 -lm



7-Zip Compression 16.02
Compress Speed Test
MIPS, More Is Better
ODROID-H2
SE +/- 37.33, N = 3
7244
1909120-FK-AROCKJ4105-CPUPERF
SE +/- 15.86, N = 3
5082
ASUS Tinker Board
SE +/- 33.93, N = 12
2946
ODROID-C2
SE +/- 5.03, N = 3
2165
Raspberry Pi 3 Model A+
SE +/- 7.97, N = 3
1993
Raspberry Pi 3 Model B
SE +/- 3.18, N = 3
1858
Raspberry Pi 3 Model B+
SE +/- 31.01, N = 3
1803
Firefly ROC-RK3328-CC
SE +/- 4.51, N = 3
1536
Raspberry Pi 2 Model B
SE +/- 2.91, N = 3
1168
1600
3200
4800
6400
8000
1. (CXX) g++ options: -pipe -lpthread

ODROID-H2 Intel Ubuntu Linux Benchmarks



PHPBench 0.8.1


Performance / Cost - PHP Benchmark Suite



1. ODROID-H2: $111.00 reported cost.
2. Raspberry Pi 3 Model A+: $25 reported cost.
3. Firefly ROC-RK3328-CC: $35 reported cost.
4. Raspberry Pi 3 Model B+: $35 reported cost.
5. ODROID-C2: $60 reported cost.
6. ASUS Tinker Board: $65 reported cost.

Perl Benchmarks


Performance / Cost - Test: Pod2html



1. Raspberry Pi 3 Model A+: $25 reported cost.
2. ODROID-H2: $111.00 reported cost.
3. Raspberry Pi 3 Model B+: $35 reported cost.
4. ASUS Tinker Board: $65 reported cost.
5. Firefly ROC-RK3328-CC: $35 reported cost.
6. ODROID-C2: $60 reported cost.

PyBench 2018-02-16


Performance / Cost - Total For Average Test Times



1. ODROID-H2: $111.00 reported cost.
2. Firefly ROC-RK3328-CC: $35 reported cost.
3. Raspberry Pi 3 Model A+: $25 reported cost.
4. ASUS Tinker Board: $65 reported cost.
5. Raspberry Pi 3 Model B+: $35 reported cost.
6. ODROID-C2: $60 reported cost.

7-Zip Compression 16.02


Performance / Cost - Compress Speed Test



1. Raspberry Pi 3 Model A+: $25 reported cost.
2. ODROID-H2: $111.00 reported cost.
3. Raspberry Pi 3 Model B+: $35 reported cost.
4. ASUS Tinker Board: $65 reported cost.
5. Firefly ROC-RK3328-CC: $35 reported cost.
6. ODROID-C2: $60 reported cost.

Tinymembench 2018-05-28


Performance / Cost - Standard Memcpy



1. Raspberry Pi 3 Model A+: $25 reported cost.
2. Raspberry Pi 3 Model B+: $35 reported cost.
3. Firefly ROC-RK3328-CC: $35 reported cost.
4. ODROID-C2: $60 reported cost.
5. ASUS Tinker Board: $65 reported cost.

x264 2018-09-25


Performance / Cost - H.264 Video Encoding



1. ODROID-H2: $111.00 reported cost.
2. Raspberry Pi 3 Model B+: $35 reported cost.
3. ODROID-C2: $60 reported cost.
4. Firefly ROC-RK3328-CC: $35 reported cost.
5. ASUS Tinker Board: $65 reported cost.

AOBench


Performance / Cost - Size: 2048 x 2048 - Total Time



1. Raspberry Pi 3 Model A+: $25 reported cost.
2. ODROID-H2: $111.00 reported cost.
3. Raspberry Pi 3 Model B+: $35 reported cost.
4. Firefly ROC-RK3328-CC: $35 reported cost.
5. ASUS Tinker Board: $65 reported cost.
6. ODROID-C2: $60 reported cost.

LAME MP3 Encoding 3.100


Performance / Cost - WAV To MP3



1. Raspberry Pi 3 Model A+: $25 reported cost.
2. ODROID-H2: $111.00 reported cost.
3. ASUS Tinker Board: $65 reported cost.
4. Raspberry Pi 3 Model B+: $35 reported cost.
5. Firefly ROC-RK3328-CC: $35 reported cost.
6. ODROID-C2: $60 reported cost.

TTSIOD 3D Renderer 2.3b


Performance / Cost - Phong Rendering With Soft-Shadow Mapping



1. ODROID-H2: $111.00 reported cost.
2. Raspberry Pi 3 Model A+: $25 reported cost.
3. Raspberry Pi 3 Model B+: $35 reported cost.
4. ODROID-C2: $60 reported cost.
5. ASUS Tinker Board: $65 reported cost.


C-Ray 1.1


Performance / Cost - Total Time - 4K, 16 Rays Per Pixel



1. ODROID-H2: $111.00 reported cost.
2. Raspberry Pi 3 Model A+: $25 reported cost.
3. Raspberry Pi 3 Model B+: $35 reported cost.
4. Firefly ROC-RK3328-CC: $35 reported cost.
5. ODROID-C2: $60 reported cost.
6. ASUS Tinker Board: $65 reported cost.


ODROID-H2 Intel Ubuntu Linux Benchmarks




PHPBench 0.8.1
PHP Benchmark Suite
Score, More Is Better
ODROID-H2
SE +/- 196.73, N = 3
257186
1909120-FK-AROCKJ4105-CPUPERF
SE +/- 115.87, N = 3
158684
ASUS Tinker Board
SE +/- 241.65, N = 3
61415
ODROID-C2
SE +/- 81.27, N = 3
59664
Firefly ROC-RK3328-CC
SE +/- 154.37, N = 3
52852
Raspberry Pi 3 Model A+
SE +/- 38.37, N = 3
40338
Raspberry Pi 3 Model B+
SE +/- 154.15, N = 3
38087
Raspberry Pi 3 Model B
SE +/- 37.95, N = 3
34426
Raspberry Pi 2 Model B
SE +/- 55.17, N = 3
20920
60K
120K
180K
240K
300K

x264 2018-09-25


H.264 Video Encoding



1. (CC) gcc options: -ldl -lm -lpthread


Perl Benchmarks

Performance / Cost - Test: Interpreter





1. Firefly ROC-RK3328-CC: $35 reported cost.
2. Raspberry Pi 3 Model A+: $25 reported cost.
3. Raspberry Pi 3 Model B+: $35 reported cost.
4. ASUS Tinker Board: $65 reported cost.
5. ODROID-C2: $60 reported cost.
6. ODROID-H2: $111.00 reported cost.

ODROID-H2 Intel Ubuntu Linux Benchmarks




ODROID-H2 Intel Ubuntu Linux Benchmarks





Perl Benchmarks
Test: Interpreter
Seconds, Fewer Is Better
ODROID-H2
SE +/- 0.00001092, N = 3
0.00333289
1909120-FK-AROCKJ4105-CPUPERF
SE +/- 0.00003546, N = 3
0.00366598
ASUS Tinker Board
SE +/- 0.00008878, N = 12
0.00427466
ODROID-C2
SE +/- 0.00002918, N = 3
0.00548034
Firefly ROC-RK3328-CC
SE +/- 0.00000741, N = 3
0.00598828
Raspberry Pi 3 Model B+
SE +/- 0.00016248, N = 12
0.00807974
Raspberry Pi 3 Model B
SE +/- 0.00015906, N = 3
0.00843041
Raspberry Pi 3 Model A+
SE +/- 0.00040707, N = 12
0.00971687
Raspberry Pi 2 Model B
SE +/- 0.00023188, N = 12
0.01409889
0.0032
0.0064
0.0096
0.0128
0.016


These geometric means are based upon test groupings / test suites for this result file.



Geometric mean based upon tests: pts/aobench, pts/c-ray, pts/compress-7zip, pts/encode-mp3 and pts/x264




Geometric mean based upon tests: pts/c-ray, pts/compress-7zip, pts/x264, pts/encode-mp3, pts/phpbench, pts/tinymembench and pts/ttsiod-renderer




Geometric mean based upon tests: pts/c-ray, pts/aobench, pts/ttsiod-renderer, pts/x264 and pts/encode-mp3


ODROID-H2 Intel Ubuntu Linux Benchmarks




Geometric mean based upon tests: pts/c-ray, pts/x264, pts/compress-7zip, pts/aobench and pts/ttsiod-renderer




Geometric mean based upon tests: pts/git and pts/pybench



Geometric mean based upon tests: pts/c-ray, pts/aobench and pts/ttsiod-renderer




Geometric mean based upon tests: pts/phpbench and pts/perl-benchmark



Geometric mean based upon tests: pts/x264, pts/compress-7zip, pts/c-ray, pts/pybench and pts/phpbench

ODROID-H2 Intel Ubuntu Linux Benchmarks



Geometric mean based upon tests: pts/encode-mp3, pts/perl-benchmark, pts/pybench, pts/phpbench and pts/git

This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 11:02.