

www.phoronix-test-suite.com

test

AMD Ryzen 5 3500U testing with a LENOVO 20NE0002US (R11ET39W 1.19 BIOS) and AMD Picasso 2GB on Pop 20.10 via the Phoronix Test Suite.

Test Systems:

PopOS20.10

Processor: AMD Ryzen 5 3500U @ 2.10GHz (4 Cores / 8 Threads), Motherboard: LENOVO 20NE0002US (R11ET39W 1.19 BIOS), Chipset: AMD Raven/Raven2, Memory: 14GB, Disk: 1000GB Samsung SSD 970 EVO Plus 1TB, Graphics: AMD Picasso 2GB (1200/1200MHz), Audio: AMD Raven/Raven2/Fenghuang, Network: Realtek RTL8111/8168/8411 + Intel Wi-Fi 6 AX200


OS: Pop 20.10, Kernel: 5.9.8-xanmod1 (x86_64), Desktop: GNOME Shell 3.38.1, Display Server: X Server 1.20.8, Display Driver: modesetting 1.20.8, OpenGL: 4.6 Mesa 21.0.0-devel (git-f89b29f 2020-11-12 groovy-oibaf-ppa) (LLVM 11.0.0), Vulkan: 1.2.145, Compiler: GCC 10.2.0, File-System: ext4, Screen Resolution: 1920x1080

Processor Notes: Scaling Governor: acpi-cpufreq performance - CPU Microcode: 0x8108102
Security Notes: itlb_multihit: Not affected + l1tf: Not affected + mds: Not affected + meltdown: Not affected + spec_store_bypass: Mitigation of SSB disabled via prctl and

seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full AMD retpoline IBPB: conditional STIBP: disabled RSB filling + srbds: Not affected + tsx_async_abort: Not affected

	PopOS20.10
Xonotic - 800 x 600 - Low (FPS)	237.5269417
Standard Deviation	0.9%

test



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 06:35.