

www.phoronix-test-suite.com

Scimark Macbook Pro Retina 2012

FreeBSD 12.2 Clang 10.0.1

Automated Executive Summary

Gentoo 5.6.4 NOPTI Clang 9.0.1 O3 ivybridge had the most wins, coming in first place for 33% of the tests.

Test Systems:

Xcode 10

Xcode 10 O2

Xcode 10 O3

Xcode 10 Ofast

Xcode 10 O2 march=ivybridge

Xcode 10 GCC 6

GCC 6 O2

GCC 6 O3

GCC 6 Ofast

GCC 6 O2 march=ivybridge

GCC 7

GCC 7 O2

GCC 7 O2 march=ivybridge

GCC 7 O3

GCC 7 Ofast

GCC 8

GCC 8 O2

GCC O3

GCC 8 Ofast

GCC 8 O2 march=ivybridge

GCC 9

GCC 9 O2

GCC 9 O3

GCC 9 Ofast

Processor: Intel Core i7 @ 2.30GHz (4 Cores / 8 Threads), Motherboard: Apple MacBook Pro, Chipset: Intel 7, Memory: 2 x 4 GB DDR3-1600MHz, Disk: 251GB APPLE SSD SM256E, Graphics: Intel HD 4000 + NVIDIA GeForce GT 650M 2GB, Monitor: Color LCD

OS: macOS 10.13.6, Kernel: 17.7.0 (x86_64), Display Server: X Server 1.18.4, OpenGL: 2.1, Compiler: Clang 8.0.0 + GCC 4.2.1 + LLVM 8.0.0 + Xcode 10.1 + CUDA 10.1, File-System: MS-DOS FAT16, Screen Resolution: 2880x1800

Environment Notes: CPPFLAGS=-march=ivybridge-mtune=ivybridge XPC_FLAGS=0x0 CFLAGS=-march=ivybridge-mtune=ivybridge
Compiler Notes: --build=x86_64-apple-darwin17.7.0 --disable-multilib --enable-checking=release --enable-languages=c,c++,objc,obj-c++,fortran --enable-nls --with-gmp=/usr/local/opt/gmp --with-mpc=/usr/local/opt/libmpc --with-mpfr=/usr/local/opt/mpfr

Clang 6

Clang 6 O2

Clang 6 O3

Clang 6 Ofast

Processor: Intel Core i7 @ 2.30GHz (4 Cores / 8 Threads), Motherboard: Apple MacBook Pro, Chipset: Intel 7, Memory: 2 x 4 GB DDR3-1600MHz, Disk: 251GB APPLE SSD SM256E, Graphics: Intel HD 4000 + NVIDIA GeForce GT 650M 2GB, Monitor: Color LCD

OS: macOS 10.13.6, Kernel: 17.7.0 (x86_64), Display Server: X Server 1.18.4, OpenGL: 2.1, Compiler: Clang 6.0.1 + GCC 4.2.1 + LLVM 6.0.1 + Xcode 10.1 + CUDA 10.1, File-System: MS-DOS FAT16, Screen Resolution: 2880x1800

Environment Notes: LDFLAGS=-L/usr/local/opt/llvm@6/lib-Wl-rpath /usr/local/opt/llvm@6/lib CPPFLAGS=-I/usr/local/opt/llvm@6/ lude XPC_FLAGS=0x0
Compiler Notes: Optimized build; Default target: x86_64-apple-darwin17.7.0; Host CPU: ivybridge

Clang 6 O2 march=ivybridge

Processor: Intel Core i7 @ 2.30GHz (4 Cores / 8 Threads), Motherboard: Apple MacBook Pro, Chipset: Intel 7, Memory: 2 x 4 GB DDR3-1600MHz, Disk: 251GB APPLE SSD SM256E, Graphics: Intel HD 4000 + NVIDIA GeForce GT 650M 2GB, Monitor: Color LCD

OS: macOS 10.13.6, Kernel: 17.7.0 (x86_64), Display Server: X Server 1.18.4, OpenGL: 2.1, Compiler: Clang 8.0.0 + GCC 4.2.1 + LLVM 8.0.0 + Xcode 10.1 + CUDA 10.1, File-System: MS-DOS FAT16, Screen Resolution: 2880x1800

Environment Notes: LDFLAGS=-L/usr/local/opt/llvm@6/lib-Wl-rpath /usr/local/opt/llvm@6/lib CPPFLAGS=-march=ivybridge-mtune=ivybridge XPC_FLAGS=0x0 CFLAGS=-march=ivybridge-mtune=ivybridge
Compiler Notes: Optimized build; Default target: x86_64-apple-darwin17.7.0; Host CPU: ivybridge

Clang 7

Clang 7 O2

Clang 7 O3

Clang 7 Ofast

Processor: Intel Core i7 @ 2.30GHz (4 Cores / 8 Threads), Motherboard: Apple MacBook Pro, Chipset: Intel 7, Memory: 2 x 4 GB DDR3-1600MHz, Disk: 251GB APPLE SSD SM256E, Graphics: Intel HD 4000 + NVIDIA GeForce GT 650M 2GB, Monitor: Color LCD

OS: macOS 10.13.6, Kernel: 17.7.0 (x86_64), Display Server: X Server 1.18.4, OpenGL: 2.1, Compiler: Clang 7.0.1 + GCC 4.2.1 + LLVM 7.0.1 + Xcode 10.1 + CUDA 10.1, File-System: MS-DOS FAT16, Screen Resolution: 2880x1800

Environment Notes: LDFLAGS=-L/usr/local/opt/llvm@7/lib-Wl-rpath /usr/local/opt/llvm@7/lib CPPFLAGS=-I/usr/local/opt/llvm@7/ lude XPC_FLAGS=0x0
Compiler Notes: Optimized build; Default target: x86_64-apple-darwin17.7.0; Host CPU: ivybridge

Clang 7 O2 march=ivybridge

Clang 8

Clang 8 O2

Clang 8 O3

Clang 8 Ofast

Clang 8 O2 march=ivybridge

Processor: Intel Core i7 @ 2.30GHz (4 Cores / 8 Threads), Motherboard: Apple MacBook Pro, Chipset: Intel 7, Memory: 2 x 4 GB DDR3-1600MHz, Disk: 251GB APPLE SSD SM256E, Graphics: Intel HD 4000 + NVIDIA GeForce GT 650M 2GB, Monitor: Color LCD

OS: macOS 10.13.6, Kernel: 17.7.0 (x86_64), Display Server: X Server 1.18.4, OpenGL: 2.1, Compiler: Clang 8.0.0 + GCC 4.2.1 + LLVM 8.0.0 + Xcode 10.1 + CUDA 10.1, File-System: MS-DOS FAT16, Screen Resolution: 2880x1800

Environment Notes: LDFLAGS=-Wl-mllvm-threads=8 CPPFLAGS=-march=ivybridge-mtune=ivybridge XPC_FLAGS=0x0 CFLAGS=-march=ivybridge-mtune=ivybridge
Compiler Notes: Optimized build; Default target: x86_64-apple-darwin17.7.0; Host CPU: ivybridge

Archlinux GCC 8.2

Archlinux GCC 8.2 V2

Archlinux GCC 8.2 O3

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (251.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8192MB, Disk: 251GB APPLE SSD SM256E, Graphics: NVIDIA GeForce GT 650M 1GB (797/2508MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Antergos Linux 19.3-ISO-Rolling, Kernel: 5.0.4-arch1-1-ARCH (x86_64), Desktop: Cinnamon 4.0.10, Display Server: X Server 1.20.4, Display Driver: NVIDIA 418.56, OpenGL: 4.6.0, Vulkan: 1.1.95, Compiler: GCC 8.2.1 20181127 + Clang 7.0.1 + LLVM 7.0.1 + CUDA 10.0, File-System: ext4, Screen Resolution: 2880x1800

Processor Notes: Scaling Governor: intel_pstate performance
Security Notes: KPTI + __user pointer sanitization + Full generic retpoline IBPB: conditional IBRS_FW STIBP: conditional RSB filling + SSB disabled via prctl and seccomp + PTE Inversion; VMX: conditional cache flushes SMT vulnerable

Archlinux Clang 7

Archlinux Clang 7 O3

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (251.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8192MB, Disk: 251GB APPLE SSD SM256E, Graphics: NVIDIA GeForce GT 650M 1GB (797/2508MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Antergos Linux 19.3-ISO-Rolling, Kernel: 5.0.4-arch1-1-ARCH (x86_64), Desktop: Cinnamon 4.0.10, Display Server: X Server 1.20.4, Display Driver: NVIDIA 418.56, OpenGL: 4.6.0, Vulkan: 1.1.95, Compiler: Clang 7.0.1 + GCC 8.2.1 20181127 + LLVM 7.0.1 + CUDA 10.0, File-System: ext4, Screen Resolution: 2880x1800

Compiler Notes: Optimized build; Default target: x86_64-pc-linux-gnu; Host CPU: ivybridge
Processor Notes: Scaling Governor: intel_pstate performance
Security Notes: KPTI + __user pointer sanitization + Full generic retpoline IBPB: conditional IBRS_FW STIBP: conditional RSB filling + SSB disabled via prctl and seccomp + PTE Inversion; VMX: conditional cache flushes SMT vulnerable

Gentoo 5.1.1 NOPTI GCC 8.3 02 ivybridge

Gentoo 5.1.1 NOPTI GCC 8.3 03 ivybridge

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (253.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8192MB, Disk: 251GB APPLE SSD SM256E, Graphics: Intel NVIDIA NVE7 1GB (1200MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Gentoo/Linux, Kernel: 5.1.1-gentoo (x86_64), Desktop: MATE 1.22.0, Display Server: X Server 1.20.4, Display Driver: nouveau 1.0.16, Compiler: GCC 8.3.0 + Clang 8.0.0 + LLVM 8.0.0, File-System: ext4, Screen Resolution: 2880x1800

Environment Notes: CFLAGS=-march=ivybridge-mtune=ivybridge-O3 CXXFLAGS=-march=ivybridge-mtune=ivybridge-O3
Processor Notes: Scaling Governor: intel_pstate performance
Security Notes: __user pointer sanitization + disabled STIBP: disabled + PTE Inversion

Clear Linux GCC 9 O2 ivybridge

Clear Linux GCC 9 O3 ivybridge

Clear Linux GCC 9 Ofast ivybridge

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (253.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8192MB, Disk: 251GB APPLE SSD SM256E, Graphics: NVIDIA NVE7 1GB (1200MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom NetXtreme BCM57762 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Clear Linux OS 29540, Kernel: 5.0.17-765.native (x86_64), Desktop: Xfce 4.12, Display Server: X Server 1.20.4, Display Driver: nouveau 1.0.16, OpenGL: 4.3 Mesa 19.2.0-devel, Vulkan: 1.1.102, Compiler: GCC 9.1.1 20190520 gcc-9-branch@271393 + Clang 8.0.0 + LLVM 8.0.0, File-System: ext4, Screen Resolution: 2880x1800

Environment Notes: CFFLAGS=-g-O3-feliminate-unused-debug-types-pipe-Wall-Wp-D_FORTIFY_SOURCE=2-fexceptions-fstack-protector--param=ssp-buffer-size=32-m64-fasynchronous-unwind-tables-Wp-D_REENTRANT-ftree-loop-distribute-patterns-Wl-z-Wl now-Wl-z-Wl relro-malign-data=abi-fno-semantic-interposition-ftree-vectorize-ftree-loop-vectorize-Wl-sort-common-Wl--enable-new-dtags FFLAGS=-g-O3-feliminate-unused-debug-types-pipe-Wall-Wp-D_FORTIFY_SOURCE=2-fexceptions-fstack-protector--param=ssp-buffer-size=32-m64-fasynchronous-unwind-tables-Wp-D_REENTRANT-ftree-loop-distribute-patterns-Wl-z-Wl relro-malign-data=abi-fno-semantic-interposition-ftree-vectorize-ftree-loop-vectorize-Wl--enable-new-dtags CXXFLAGS=-march=ivybridge-mtune=ivybridge-O2 MESA_GLSL_CACHE_DISABLE=0 CFLAGS=-march=ivybridge-mtune=ivybridge-O2 THEANO_FLAGS=floatX=float32 openmp=true gcc.cxxflags="-ftree-vectorize-mavx"
Compiler Notes: --build=x86_64-generic-linux --disable-libmpx --disable-libunwind-exceptions --disable-multiarch --disable-vtable-verify --disable-werror --enable-__cxa_atexit --enable-bootstrap --enable-cet --enable-clocale=gnu --enable-default-pie --enable-gnu-indirect-function --enable-languages=c,c++,fortran,go --enable-ld=default --enable-libstdcxx-pch --enable-lto --enable-multilib --enable-plugin --enable-shared --enable-threads=posix --exec-prefix=/usr --includedir=/usr/include --target=x86_64-generic-linux --with-arch=westmere --with-gcc-major-version-only --with-glibc-version=2.19 --with-gnu-ld --with-isl --with-ppl=yes --with-tune=haswell
Processor Notes: Scaling Governor: intel_pstate performance
Security Notes: l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT vulnerable + mds: Vulnerable: Clear buffers attempted no microcode; SMT vulnerable + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: conditional RSB filling

Gentoo 5.6.4 NOPTI GCC 9.3 O2 ivybridge

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (259.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8GB, Disk: 251GB APPLE SSD SM256E, Graphics: NVIDIA GeForce GT 650M 1GB (797/2508MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Gentoo 2.6, Kernel: 5.6.4-gentoo-x86_64 (x86_64), Desktop: LXQt 0.14.1, Display Server: X Server 1.20.7, Display Driver: NVIDIA 440.82, OpenGL: 4.6.0, OpenCL: OpenCL 1.2 CUDA 10.2.159, Compiler: GCC 9.3.0 + Clang 9.0.1 +

LLVM 9.0.1 + CUDA 10.2, File-System: ext4, Screen Resolution: 2880x1800

Environment Notes: CFLAGS="-march=ivybridge -O2 -pipe -falign-functions=32" CXXFLAGS="-march=ivybridge -O2 -pipe -falign-functions=32" LDFLAGS="-Wl,-O2 -Wl,--as-needed"
Processor Notes: Scaling Governor: intel_pstate performance - CPU Microcode: 0x21
Security Notes: itlb_multihit: KVM: Vulnerable + l1tf: Mitigation of PTE Inversion; VMX: vulnerable + mds: Vulnerable; SMT vulnerable + meltdown: Vulnerable + spec_store_bypass: Vulnerable + spectre_v1: Vulnerable: __user pointer sanitization and usercopy barriers only; no swapgs barriers + spectre_v2: Vulnerable IBPB: disabled STIBP: disabled + tsx_async_abort: Not affected

Gentoo 5.6.4 NOPTI Clang 9.0.1 O2 ivybridge

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (259.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8GB, Disk: 251GB APPLE SSD SM256E, Graphics: NVIDIA GeForce GT 650M 1GB (797/2508MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Gentoo 2.6, Kernel: 5.6.4-gentoo-x86_64 (x86_64), Desktop: LXQt 0.14.1, Display Server: X Server 1.20.7, Display Driver: NVIDIA 440.82, OpenGL: 4.6.0, OpenCL: OpenCL 1.2 CUDA 10.2.159, Compiler: Clang 9.0.1 + GCC 9.3.0 + LLVM 9.0.1 + CUDA 10.2, File-System: ext4, Screen Resolution: 2880x1800

Environment Notes: CFLAGS="-march=ivybridge -O2 -pipe -falign-functions=32" CXXFLAGS="-march=ivybridge -O2 -pipe -falign-functions=32" LDFLAGS="-Wl,-O2 -Wl,--as-needed"
Compiler Notes: Optimized build; Default target: x86_64-pc-linux-gnu; Host CPU: ivybridge
Processor Notes: Scaling Governor: intel_pstate performance - CPU Microcode: 0x21
Security Notes: itlb_multihit: KVM: Vulnerable + l1tf: Mitigation of PTE Inversion; VMX: vulnerable + mds: Vulnerable; SMT vulnerable + meltdown: Vulnerable + spec_store_bypass: Vulnerable + spectre_v1: Vulnerable: __user pointer sanitization and usercopy barriers only; no swapgs barriers + spectre_v2: Vulnerable IBPB: disabled STIBP: disabled + tsx_async_abort: Not affected

Gentoo 5.6.4 NOPTI GCC 9.3 O3 ivybridge

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (259.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8GB, Disk: 251GB APPLE SSD SM256E, Graphics: NVIDIA GeForce GT 650M 1GB (797/2508MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Gentoo 2.6, Kernel: 5.6.4-gentoo-x86_64 (x86_64), Desktop: LXQt 0.14.1, Display Server: X Server 1.20.7, Display Driver: NVIDIA 440.82, OpenGL: 4.6.0, OpenCL: OpenCL 1.2 CUDA 10.2.159, Compiler: GCC 9.3.0 + Clang 9.0.1 + LLVM 9.0.1 + CUDA 10.2, File-System: ext4, Screen Resolution: 2880x1800

Environment Notes: CFLAGS="-march=ivybridge -O3 -pipe -falign-functions=32" CXXFLAGS="-march=ivybridge -O3 -pipe -falign-functions=32" LDFLAGS="-Wl,-O2 -Wl,--as-needed"
Processor Notes: Scaling Governor: intel_pstate performance - CPU Microcode: 0x21
Security Notes: itlb_multihit: KVM: Vulnerable + l1tf: Mitigation of PTE Inversion; VMX: vulnerable + mds: Vulnerable; SMT vulnerable + meltdown: Vulnerable + spec_store_bypass: Vulnerable + spectre_v1: Vulnerable: __user pointer sanitization and usercopy barriers only; no swapgs barriers + spectre_v2: Vulnerable IBPB: disabled STIBP: disabled + tsx_async_abort: Not affected

Gentoo 5.6.4 NOPTI Clang 9.0.1 O3 ivybridge

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (259.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8GB, Disk: 251GB APPLE SSD SM256E, Graphics: NVIDIA GeForce GT 650M 1GB (797/2508MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Gentoo 2.6, Kernel: 5.6.4-gentoo-x86_64 (x86_64), Desktop: LXQt 0.14.1, Display Server: X Server 1.20.7, Display Driver: NVIDIA 440.82, OpenGL: 4.6.0, OpenCL: OpenCL 1.2 CUDA 10.2.159, Compiler: Clang 9.0.1 + GCC 9.3.0 + LLVM 9.0.1 + CUDA 10.2, File-System: ext4, Screen Resolution: 2880x1800

Environment Notes: CFLAGS="-march=ivybridge -O3 -pipe -falign-functions=32" CXXFLAGS="-march=ivybridge -O3 -pipe -falign-functions=32" LDFLAGS="-Wl,-O2

-Wl,--as-needed"
Compiler Notes: Optimized build; Default target: x86_64-pc-linux-gnu; Host CPU: ivybridge
Processor Notes: Scaling Governor: intel_pstate performance - CPU Microcode: 0x21
Security Notes: itlb_multihit: KVM: Vulnerable + l1tf: Mitigation of PTE Inversion; VMX: vulnerable + mds: Vulnerable; SMT vulnerable + meltdown: Vulnerable + spec_store_bypass: Vulnerable + spectre_v1: Vulnerable: __user pointer sanitization and usercopy barriers only; no swapgs barriers + spectre_v2: Vulnerable IBPB: disabled STIBP: disabled + tsx_async_abort: Not affected

Gentoo 5.6.4 NOPTI GCC 9.3 O3 G-overlay ivybridge

Processor: Intel Core i7-3615QM @ 3.30GHz (4 Cores / 8 Threads), Motherboard: Apple Mac-C3EC7CD22292981F (259.0.0.0.0 BIOS), Chipset: Intel 3rd Gen Core DRAM, Memory: 8GB, Disk: 251GB APPLE SSD SM256E, Graphics: NVIDIA GeForce GT 650M 1GB (797/2508MHz), Audio: Cirrus Logic CS4206, Monitor: Color LCD, Network: Broadcom NetXtreme BCM57786 PCIe + Broadcom BCM4331 802.11a/b/g/n

OS: Gentoo 2.6, Kernel: 5.6.4-gentoo-x86_64 (x86_64), Desktop: LXQt 0.14.1, Display Server: X Server 1.20.7, Display Driver: NVIDIA 440.82, OpenGL: 4.6.0, OpenCL: OpenCL 1.2 CUDA 10.2.159, Compiler: GCC 9.3.0 + Clang 9.0.1 + LLVM 9.0.1 + CUDA 10.2, File-System: ext4, Screen Resolution: 2880x1800

Environment Notes: CFLAGS="-march=ivybridge -O3 -pipe -falign-functions=32 -flto -fipa-pta -fgraphite-identity -floop-nest-optimize -fdevirtualize-at-ltrans" CXXFLAGS="-march=ivybridge -O3 -pipe -falign-functions=32 -flto -fipa-pta -fgraphite-identity -floop-nest-optimize -fdevirtualize-at-ltrans" LDFLAGS="-Wl,-O2 -Wl,--as-needed"
Processor Notes: Scaling Governor: intel_pstate performance - CPU Microcode: 0x21
Security Notes: itlb_multihit: KVM: Vulnerable + l1tf: Mitigation of PTE Inversion; VMX: vulnerable + mds: Vulnerable; SMT vulnerable + meltdown: Vulnerable + spec_store_bypass: Vulnerable + spectre_v1: Vulnerable: __user pointer sanitization and usercopy barriers only; no swapgs barriers + spectre_v2: Vulnerable IBPB: disabled STIBP: disabled + tsx_async_abort: Not affected

FreeBSD 12.1 Clang 8.0.1

Processor: Intel Core i7-3615QM @ 2.30GHz (8 Cores), Motherboard: Apple MacBookPro10 1 1.0, Chipset: Intel 3rd Gen Core DRAM, Memory: 8GB, Disk: 218GB, Graphics: Unknown 981MB, Audio: NVIDIA (0x0e1b) HDA

OS: FreeBSD, Kernel: 12.1-RELEASE (x86_64), Display Server: X Server 1.20.8, Display Driver: modesetting 1.20.8, Compiler: Clang 8.0.1 (SVN 366581), File-System: zfs, Screen Resolution: 2880x1800

Environment Notes: LIBGL_ALWAYS_SOFTWARE=1
Security Notes: KPTI

FreeBSD 12.2 Clang 10.0.1

Processor: Intel Core i7-3615QM @ 2.30GHz (8 Cores), Motherboard: Apple MacBookPro10 1 1.0, Chipset: Intel 3rd Gen Core DRAM, Memory: 8GB, Disk: 208GB, Graphics: NVIDIA GeForce GT 650M 981MB, Audio: NVIDIA (0x0e1b) HDA, Monitor: Color LCD

OS: FreeBSD, Kernel: 12.2-RELEASE-p1 (x86_64), Desktop: Xfce 4.14, Display Server: X Server 1.20.9, Display Driver: NVIDIA 1.0.0, Compiler: Clang 10.0.1, File-System: zfs, Screen Resolution: 2880x1800

Security Notes: KPTI

Xcode 12


Processor: Intel Core i7-3615QM @ 2.30GHz (4 Cores / 8 Threads), Motherboard: Apple MacBook Pro, Chipset: Intel 7, Memory: 2 x 4 GB DDR3-1600MHz, Disk: 251GB APPLE SSD SM256E, Graphics: Intel HD 4000 + NVIDIA GeForce GT 650M 2GB, Monitor: Color LCD

OS: macOS 10.15.7, Kernel: 19.6.0 (x86_64), Compiler: Clang 12.0.0 + GCC 12.0.0 + Xcode 12.3, File-System: APFS, Screen Resolution: 2880x1800

Scimark Macbook Pro Retina 2012

Environment Notes: LDFLAGS=-L/usr/local/opt/openssl@1.1/lib CPPFLAGS=-I/usr/local/opt/openssl@1.1/include XPC_FLAGS=0x0
Processor Notes: CPU Microcode: 33


Scimark Macbook Pro Retina 2012




Scimark Macbook Pro Retina 2012




Scimark Macbook Pro Retina 2012



Scimark Macbook Pro Retina 2012



Scimark Macbook Pro Retina 2012




Scimark Macbook Pro Retina 2012


| | | |

Scimark Macbook Pro Retina 2012


Scimark Macbook Pro Retina 2012




Scimark Macbook Pro Retina 2012




Scimark Macbook Pro Retina 2012




Scimark Macbook Pro Retina 2012



Scimark Macbook Pro Retina 2012



Scimark Macbook Pro Retina 2012



Scimark Macbook Pro Retina 2012

This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 12:33.