

www.phoronix-test-suite.com

ffte1800xbench

AMD Ryzen 7 1800X Eight-Core testing with a ASUS ROG STRIX X470-F GAMING (5603 BIOS) and NVIDIA GeForce RTX 2060 6GB on Ubuntu 20.04 via the Phoronix Test Suite.

Test Systems:

1800x

Processor: AMD Ryzen 7 1800X Eight-Core @ 3.60GHz (8 Cores / 16 Threads), Motherboard: ASUS ROG STRIX X470-F GAMING (5603 BIOS), Chipset: AMD 17h, Memory: 32GB, Disk: 2 x HP SSD EX950 512GB + 1000GB Western Digital WD10EFRX-68F + 1000GB Western Digital WD10JPCX-24U + 4001GB Seagate ST4000DM004-2CV1 + 16GB Cruzer Blade, Graphics: NVIDIA GeForce RTX 2060 6GB (1365/7000MHz), Audio: NVIDIA TU106 HD Audio, Monitor: FG276, Network: Intel I211


OS: Ubuntu 20.04, Kernel: 5.8.0-38-generic (x86_64), Desktop: GNOME Shell 3.36.4, Display Server: X Server 1.20.9, Display Driver: NVIDIA 455.32.00, OpenGL: 4.6.0, OpenCL: OpenCL 1.2 CUDA 11.1.102, Vulkan: 1.2.142, Compiler: GCC 9.3.0 + CUDA 11.1, File-System: ext4, Screen Resolution: 2560x1440

fft1800xbench

Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++,gm2 --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none=/build/gcc-9-HskZEa/gcc-9-9.3.0/debian/tmp-nvptx/usr,hsa --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib=auto --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq ondemand (Boost: Enabled) - CPU Microcode: 0x8001138
Security Notes: itlb_multihit: Not affected + l1tf: Not affected + mds: Not affected + meltdown: Not affected + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full AMD retpoline IBPB: conditional STIBP: disabled RSB filling + srbds: Not affected + tsx_async_abort: Not affected

	1800x
FFTE - N.2.3.C.F.R (MFLOPS)	40808
Standard Deviation	2.5%

ffte1800xbench



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 16:41.