

www.phoronix-test-suite.com

Raspberry Pi vs Orange Pi vs Banana Pi 2016-03 Showdown by LoveRPi

test

Automated Executive Summary

test3 had the most wins, coming in first place for 42% of the tests.

Test Systems:

Orange Pi One on Armbian

Processor: ARMv7 rev 5 @ 1.20GHz (4 Cores), Motherboard: sun8i, Memory: 494MB, Disk: 32GB 00000

OS: Debian 8.3, Kernel: 3.4.110-sun8i (armv7l), Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1280x1440

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: cpufreq-sunxi interactive

Orange Pi PC on Armbian

Processor: ARMv7 rev 5 @ 1.30GHz (4 Cores), Motherboard: sun8i, Memory: 1024MB, Disk: 32GB 00000

OS: Debian 8.3, Kernel: 3.4.110-sun8i (armv7l), Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1280x1440

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: cpufreq-sunxi interactive

Orange Pi Plus on Armbian

Processor: ARMv7 rev 5 @ 1.30GHz (4 Cores), Motherboard: sun8i, Memory: 1024MB, Disk: 32GB 00000 + 8GB M8G1GC

OS: Debian 8.3, Kernel: 3.4.110-sun8i (armv7l), Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1280x1440

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: cpufreq-sunxi interactive

Raspberry Pi 2 on Raspbian

Processor: ARMv7 rev 5 @ 0.90GHz (4 Cores), Motherboard: BCM2709 Raspberry Pi 2 Model B Rev 1.1, Memory: 925MB, Disk: 8GB SD

OS: Raspbian 8.0, Kernel: 4.1.13-v7+ (armv7l), Desktop: LXDE 0.7.2, Display Server: X Server 1.16.4, Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1824x984

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv6 --with-float=hard --with-fpu=vfp -v
Processor Notes: Scaling Governor: BCM2835 Freq ondemand

Raspberry Pi 3 on Raspbian

Processor: ARMv7 rev 4 @ 1.20GHz (4 Cores), Motherboard: BCM2709 Raspberry Pi 3 Model B Rev 1.2, Memory: 925MB, Disk: 63GB 00000

OS: Raspbian GNU/Linux 8, Kernel: 4.1.20-v7+ (armv7l), Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1824x984

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv6 --with-float=hard --with-fpu=vfp -v
Processor Notes: Scaling Governor: BCM2835 Freq ondemand

Banana Pi M2 by LoveRPi

Processor: ARMv7 rev 3 @ 1.01GHz (4 Cores), Motherboard: Allwinner sun6i (A31) Family Sinovoip BPI-M2, Memory: 1024MB, Disk: 129GB 00000

OS: Ubuntu 14.04, Kernel: 4.4.1-sunxi (armv7l), Compiler: GCC 4.8.4, File-System: ext4

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libmudflap --disable-libquadmath --disable-sjlj-exceptions --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: cpufreq-dt ondemand

Banana Pi M3 by LoveRPi

Processor: ARMv7 rev 5 @ 1.80GHz (8 Cores), Motherboard: sun8i, Memory: 2048MB, Disk: 8GB M8G1GC + 129GB TO

OS: Ubuntu 15.10, Kernel: 3.4.39-BPI-M3-aufs (armv7l), Compiler: GCC 5.2.1 20151010, File-System: aufs, Screen Resolution: 1920x2160

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: sunxi-iks interactive

Banana Pi M2+ SinoVoip

Processor: ARMv7 rev 5 @ 1.20GHz (1 Core), Motherboard: sun8i, Memory: 745MB, Disk: 64GB 00000 + 8GB 8WMB3R

OS: Debian 8.4, Kernel: 3.4.111-sun8i (armv7l), Desktop: Xfce, Display Driver: modesetting 0.9.0, Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1280x720

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: cpufreq-sunxi interactive

Banana Pi M2+ on Armbian

Processor: ARMv7 rev 5 @ 1.20GHz (4 Cores), Motherboard: sun8i, Memory: 745MB, Disk: 64GB 00000 + 8GB 8WMB3R

OS: Debian 8.4, Kernel: 3.4.111-sun8i (armv7l), Desktop: Xfce, Display Driver: modesetting 0.9.0, Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: cpufreq-sunxi interactive

Banana Pi M2+ Raspbian 8.0

Processor: ARMv7 rev 5 @ 1.20GHz (3 Cores), Motherboard: sun8i, Memory: 1024MB, Disk: 8GB SU08G + 8GB 8WMB3R

OS: Raspbian 8.0, Kernel: 3.4.39-02-lobo (armv7l), Desktop: LXDE, Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1280x720

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++

--enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv6 --with-float=hard --with-fpu=vfp -v
Processor Notes: Scaling Governor: cpufreq-sunxi ondemand

MiQi on Lubuntu 14.04

Processor: ARMv7 rev 1 @ 1.80GHz (4 Cores), Motherboard: Rockchip RK3288 (Flattened Device Tree), Memory: 2048MB, Disk: 31GB BIWIN

OS: Ubuntu 14.04, Kernel: 3.10.0 (armv7l), Desktop: LXDE, Compiler: GCC 4.8.4, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libmudflap --disable-libquadmath --disable-sjlj-exceptions --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: rockchip interactive

DragonBoard 410c on Debian RPB 16.03

Processor: Unknown @ 1.21GHz (4 Cores), Memory: 833MB, Disk: 8GB DS2008, Monitor: TX-NR636

OS: Debian 8.3, Kernel: 4.4.0-104-arm64 (aarch64), Desktop: LXDE, Compiler: GCC 4.9.2, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=aarch64-linux-gnu --disable-browser-plugin --disable-libquadmath --disable-libsanitizer --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-plugin --enable-shared --enable-threads=posix --host=aarch64-linux-gnu --target=aarch64-linux-gnu --with-arch-directory=arm64 -v
Processor Notes: Scaling Governor: cpufreq-dt ondemand

MeUbuntu 14.04.3

Processor: Intel Atom Z3735F @ 1.83GHz (4 Cores), Motherboard: Mini PC v2.80, Chipset: Intel ValleyView SSA-CUnit, Memory: 2048MB, Disk: 31GB NCard, Graphics: Intel ValleyView Gen7 (646MHz), Monitor: TX-NR636

OS: Ubuntu 14.04, Kernel: 3.16.0-45-generic (x86_64), Desktop: Unity 7.2.6, Display Driver: intel 2.99.914, Compiler: GCC 4.8.4, File-System: ext4, Screen Resolution: 1920x1080

Compiler Notes: --build=x86_64-linux-gnu --disable-browser-plugin --disable-libmudflap --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-arch-directory=amd64 --with-multilib-list=m32,m64,mx32 --with-tune=generic -v
Processor Notes: Scaling Governor: intel_pstate powersave

NanoPi NEO 512MB No Heatsink

Processor: ARMv7 rev 5 @ 0.82GHz (4 Cores), Motherboard: sun8i, Memory: 495MB, Disk: 8GB SL08G

OS: Ubuntu 15.10, Kernel: 3.4.39-h3 (armv7l), Compiler: GCC 5.2.1 20151010, File-System: ext4, Screen Resolution: 1280x1440

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: cpufreq-sunxi interactive

NanoPi NEO 512MB Heatsink

NanoPi NEO 512MB Heatsink 2

NanoPi NEO 512MB Heatsink2

Processor: ARMv7 rev 5 @ 1.20GHz (4 Cores), Motherboard: sun8i, Memory: 495MB, Disk: 8GB SL08G

OS: Ubuntu 15.10, Kernel: 3.4.39-h3 (armv7l), Compiler: GCC 5.2.1 20151010, File-System: ext4, Screen Resolution: 1280x1440

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --disable-werror --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-multilib --enable-nls --enable-objc-gc --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb -v
Processor Notes: Scaling Governor: cpufreq-sunxi interactive

NanoPi NEO 2 FA Ubuntu 16.04.2

Processor: AArch64 rev 4 @ 0.82GHz (4 Cores), Motherboard: sun50iw2, Memory: 468MB, Disk: 8GB SL08G

OS: Ubuntu 16.04, Kernel: 3.10.65 (aarch64), Compiler: GCC 5.4.0 20160609, File-System: ext4, Screen Resolution: 1280x1440

Compiler Notes: --build=aarch64-linux-gnu --disable-browser-plugin --disable-libquadmath --disable-werror --enable-checking=release --enable-clocale=gnu --enable-fix-cortex-a53-843419 --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-plugin --enable-shared --enable-threads=posix --host=aarch64-linux-gnu --target=aarch64-linux-gnu --with-arch-directory=aarch64 --with-default-libstdcxx-abi=new -v
Processor Notes: Scaling Governor: cpufreq-sunxi interactive

NanoPi NEO 2 Armbian Ubuntu 16.04.2

Processor: AArch64 rev 4 (4 Cores), Motherboard: Xunlong Orange Pi PC 2, Memory: 483MB, Disk: 8GB SL08G

OS: Ubuntu 16.04, Kernel: 4.10.0-sun50iw2 (aarch64), Compiler: GCC 5.4.0 20160609, File-System: ext4

Compiler Notes: --build=aarch64-linux-gnu --disable-browser-plugin --disable-libquadmath --disable-werror --enable-checking=release --enable-clocale=gnu --enable-fix-cortex-a53-843419 --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-plugin --enable-shared --enable-threads=posix --host=aarch64-linux-gnu --target=aarch64-linux-gnu --with-arch-directory=aarch64 --with-default-libstdcxx-abi=new -v

VS-RK3399 Board - Debian 9

Processor: ARMv8 rev 4 @ 1.42GHz (6 Cores), Motherboard: Rockchip RK3399 VideoStrong Board MID (Android), Memory: 4096MB, Disk: 31GB BWBD3R, Monitor: TX-NR636

OS: Debian 9.1, Kernel: 4.4.55 (aarch64), Desktop: LXDE, Compiler: GCC 6.3.0 20170516, File-System: ext4, Screen Resolution: 1024x600p86

Compiler Notes: --build=arm-linux-gnueabihf --disable-browser-plugin --disable-libitm --disable-libquadmath --disable-sjlj-exceptions --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-gtk-cairo --enable-java-awt=gtk --enable-java-home --enable-languages=c,ada,c++,java,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc=auto --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --program-prefix=arm-linux-gnueabihf- --target=arm-linux-gnueabihf --with-arch-directory=arm --with-arch=armv7-a --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfpv3-d16 --with-mode=thumb --with-target-system-zlib -v
Processor Notes: Scaling Governor: cpufreq-dt ondemand

test

test1

Processor: ARMv7 rev 3 @ 2.49GHz (4 Cores), Motherboard: BCM2711 Raspberry Pi 4 Model B Rev 1.4, Memory: 8192MB, Disk: 120GB X5, Graphics: vc4drmfb

OS: Raspbian 10, Kernel: 5.10.11-v7l+ (armv7l), Desktop: LXDE, Display Server: X Server 1.20.4, Display Driver: modesetting 1.20.4, Compiler: GCC 8.3.0, File-System: ext4, Screen Resolution: 1024x768

Kernel Notes: snd_bcm2835.enable_compat_alsa=0 snd_bcm2835.enable_hdmi=1
Compiler Notes: --build=arm-linux-gnueabihf --disable-libitm --disable-libquadmath --disable-libquadmath-support --disable-sjlj-exceptions --disable-werror --enable-bootstrap --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-languages=c,ada,c++,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc=auto --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --program-prefix=arm-linux-gnueabihf- --target=arm-linux-gnueabihf --with-arch=armv6 --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfp --with-gcc-major-version-only --with-target-system-zlib -v
Processor Notes: Scaling Governor: cpufreq-dt ondemand

test2

test3

Processor: ARMv7 rev 3 @ 2.49GHz (4 Cores), Motherboard: BCM2711 Raspberry Pi 4 Model B Rev 1.4, Memory: 8192MB, Disk: 120GB X5, Graphics: V3D 4.2 7GB

OS: Raspbian 10, Kernel: 5.10.11-v7l+ (armv7l), Desktop: LXDE 0.10.0, Display Server: X Server 1.20.4, Display Driver: modesetting 1.20.4, OpenGL: 2.1 Mesa 19.3.2, Compiler: GCC 8.3.0, File-System: ext4, Screen Resolution: 1024x768

Kernel Notes: snd_bcm2835.enable_compat_alsa=0 snd_bcm2835.enable_hdmi=1
Compiler Notes: --build=arm-linux-gnueabihf --disable-libitm --disable-libquadmath --disable-libquadmath-support --disable-sjlj-exceptions --disable-werror --enable-bootstrap --enable-checking=release --enable-clocale=gnu --enable-gnu-unique-object --enable-languages=c,ada,c++,go,d,fortran,objc,obj-c++ --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-nls --enable-objc-gc=auto --enable-plugin --enable-shared --enable-threads=posix --host=arm-linux-gnueabihf --program-prefix=arm-linux-gnueabihf- --target=arm-linux-gnueabihf --with-arch=armv6 --with-default-libstdcxx-abi=new --with-float=hard --with-fpu=vfp --with-gcc-major-version-only --with-target-system-zlib -v
Processor Notes: Scaling Governor: cpufreq-dt ondemand

Raspberry Pi vs Orange Pi vs Banana Pi 2016-03 Showdown by LoveRPi


	Orange Pi One on Armbian	Orange Pi PC on Armbian	Orange Pi Plus on Armbian	Raspberry Pi 2 on Raspbian	Raspberry Pi 3 on Raspbian	Banana Pi M2 by LoveRPi	Banana Pi M3 by LoveRPi	Banana Pi M2 + SinoVoip	Banana Pi M2 + on Armbian	Banana Pi M2 + Raspbian 8.0	MiQi on Lubuntu 14.04	Dragon Board 410c on Debian RPB 16.03	MeUbuntu 14.04.3	NanoPi NEO 512MB NoHeatsink	NanoPi NEO 512MB Heatsink	NanoPi NEO 512MB Heatsink 2	NanoPi NEO 512MB Heatsink 2	NanoPi NEO2 FAUbuntu 16.04.2	NanoPi NEO2 Armbian Ubuntu 16.04.2	VS-RK3399 Board - Debian 9	test	test1	test2	test3
C-Ray - Total Time (sec)	36.54	34.52	35.07	50.54	25.79	43.10	13.64	17.78	58.13	89.24	13.96	34.80	20.29	84.52	46.70		46.89	35.48	34.91	98.08					58.08
Normalized	15.87%	16.86%	16.59%	11.49%	23.16%	13.47%	42.66%	3.27%	9.99%	6.56%	42.41%	16.99%	29%	6.84%	12.58%		12.47%	16.57%	16.81%	59.29%					100%
Standard Deviation	0.2%	1.5%	0.5%	0.3%	0.1%	0%	0.3%	0.4%	3.6%	2.3%	4.3%	3.8%	0%	7.8%	3%		1.8%	0%	0.1%	3.1%					7.8%
FLAC Audio Encoding - WAV To FLAC	22.954	22.089	23.138	31.458	23.730	28.816		27.995	23.200	28.260	81.96	19.814	36.43	32.52	23.19		23.099	23.061	29.091	48.84					38.34
Normalized	15.87%	15.97%	15.74%	11.58%	15.33%	12.66%		13.01%	15.87%	12.84%	44.47%	18.31%	100%	11.19%	15.74%		15.74%	15.47%	12.56%	74.59%					95.02%
Standard Deviation	0.2%	1%	1.4%	0.9%	1.6%	0.1%		0.2%	0.3%	0.3%	0.9%	3.3%	7.7%	1.8%	0.3%		0.1%	0.2%	0%	0.2%					0.3%
Himeno Benchmark - P.P.S (MFLOPS)	64.38	68.23	68.01	33.29	60.28	61.26	31.80	56.83	64.35	63.04	89.84	66.91	443.65	41.32	15.34		15.31	52.67	49.18	195.30					304.70
Normalized	14.51%	15.38%	15.33%	7.52%	13.59%	13.81%	7.17%	12.86%	14.51%	14.20%	20.25%	15.07%	100%	9.31%	3.46%		3.45%	11.82%	11.08%	44.04%					68.68%
Standard Deviation	0.4%	0.8%	0.1%	2.4%	1.1%	0.2%	2.7%	1.4%	1%	1.5%	3%	1.2%	0.9%	0.2%	0.5%		1.8%	8.2%	0.7%	0.7%					18.9%


Raspberry Pi vs Orange Pi vs Banana Pi 2016-03 Showdown by LoveRPi


Himeno Benchmark - Performance / Cost - P.P.S (MFLOPS/Dollar)	**6.44**	4.55	1.74		1.72	1.36	**0.40**																		
Normalized	100%	70.6%	27.0%		26.7%	21.1%	6.21%																		
John The Ripper - Blowfish (Real C/S)	50990	55000	54007	38	59598	43688	14008	**104**	390	323	1055	535	1003	313	232		452	456	478	759					**1714**
Normalized	29.7%	32.0%	31.5%	22.5%	34.9%	25.5%	82.1%	6.07%	22.7%	18.8%	61.5%	31.2%	58.5%	18.2%	26.9%		26.3%	26.6%	27.8%	44.2%					100%
Standard Deviation	0.1%	0%	0%	0.3%	0.6%	0.1%	0.6%	3%	14.2%	0.8%	0.2%	11.2%	20.4%	9.1%	2.7%		2.7%	0.6%		3.3%					0.5%
John The Ripper - Performance / Cost - Blowfish (Real C/S/Dollar)	**50.90**	36.67	13.85		17.11	**9.73**	17.60																		
Normalized	100%	72.0%	27.2%		33.6%	19.1%	34.5%																		


Raspberry Pi vs Orange Pi vs Banana Pi 2016-03 Showdown by LoveRPi


Meta Performance Per Dollar - P.P.D (Performance/ Dollar)	**19.65**	14.12	5.34		6.48	**3.80**	6.18																
Normalized	100	71.8%	27.1%		32.9%	19.3%	31.4%																
OpenSSL - R.4.b.P (Signs/sec)	16	17.20	17.13	11.93	20.60	13.40	43.30	**3.30**	10.48	6.67	29.70	10.90	**66.53**	7.68	12.35		12.40						60.50
Normalized	24.0	25.8%	25.7%	17.9%	30.9%	20.1%	65.0%	4.96%	15.7%	10.0%	44.6%	16.3%	100%	11.5%	18.5%		18.6%						90.9%
Standard Deviation	0%	0%	0.3%	0.5%	8.9%	0%	2%	0%	14.2%	0.9%	0%	9%	1.4%	18.6%	3.4%		4.4%						0.6%
OpenSSL - Performance / Cost - R.4.b.P (Signs/sec/Dollar)	**1.60**	1.15	0.44		0.59	**0.30**	0.54																
Normalized	100	71.8%	27.5%		36.8%	18.7%	33.7%																
Smallpt - G.I.R.1.S (sec)	16	15	15	21	13	19	62	**81**	24	39	86	23	62	28	21		21	13	12	67			**33**
	65	47	49	75	90	54	1	**27**	83	06	6	41	0	29	34		01	08	85	9			**9**
Normalized	20.3	21.9	21.8	15.5	24.3	17.3	54.5	4.17	13.6	8.68	39.1	14.4	54.6	11.9	15.8		16.1	25.9	26.3	49.9			100
Standard Deviation	0%	0.4%	0.1%	0.5%	0.2%	0.1%	0.4%	0.5%	0%	0.3%	0.5%	11%	0.2%	4%	0.2%		0.1%	0%	0.1%	2.4%			
Timed MAFFT Alignment - M.S.A (sec)		62.45	63.17	75.46	61.06	70.58	**29.72**	**21.62**	81.13	12.16	42.84	73.91	33.12	13.29	77.66		75.34	63.73	64.47				
Normalized		47.5%	47.0%	39.3%	48.6%	42.1%	100%	14.1%	36.6%	24.3%	69.3%	40.2%	89.7%	22.4%	38.2		39.4%	46.6%	46.1%				
Standard Deviation		8.2%	2.1%	2.3%	10.4%	2%	0.8%	0%	8.4%	9.5%	4.6%	8.1%	1.2%	9.4%	2.5%		1.6%	8.2%	0.4%				


C-Ray 1.1
Total Time
Seconds, Fewer Is Better
Banana Pi M2 by LoveRPi
SE +/- 0.02, N = 3
431.10
Banana Pi M2+ Raspbian 8.0
SE +/- 11.64, N = 3
893.24
Banana Pi M2+ SinoVoip
SE +/- 3.91, N = 3
1777.89
Banana Pi M2+ on Armbian
SE +/- 8.44, N = 6
581.37
Banana Pi M3 by LoveRPi
SE +/- 0.24, N = 3
136.14
DragonBoard 410c on Debian RPB 16.03
SE +/- 5.37, N = 6
341.80
MeUbuntu 14.04.3
SE +/- 0.02, N = 3
200.29
MiQi on Lubuntu 14.04
SE +/- 2.39, N = 6
136.96
NanoPi NEO 2 Armbian Ubuntu 16.04.2
SE +/- 0.18, N = 3
344.91
NanoPi NEO 2 FA Ubuntu 16.04.2
SE +/- 0.09, N = 3
350.48
NanoPi NEO 512MB Heatsink
SE +/- 7.92, N = 3
461.70
NanoPi NEO 512MB Heatsink2
SE +/- 4.74, N = 3
466.89
NanoPi NEO 512MB No Heatsink
SE +/- 27.05, N = 6
848.52
Orange Pi One on Armbian
SE +/- 0.37, N = 3
365.94
Orange Pi PC on Armbian
SE +/- 2.95, N = 3
344.52
Orange Pi Plus on Armbian
SE +/- 1.06, N = 3
350.07
Raspberry Pi 2 on Raspbian
SE +/- 0.74, N = 3
505.44
Raspberry Pi 3 on Raspbian
SE +/- 0.11, N = 3
250.79
VS-RK3399 Board - Debian 9
SE +/- 1.73, N = 3
98.08
test3
SE +/- 1.18, N = 15
58.08
400
800
1200
1600
2000
1. (CC) gcc options: -lm -lpthread -O3


FLAC Audio Encoding 1.3.1
WAV To FLAC
Seconds, Fewer Is Better
Banana Pi M2 by LoveRPi
SE +/- 0.09, N = 5
288.16
Banana Pi M2+ Raspbian 8.0
SE +/- 0.41, N = 5
282.60
Banana Pi M2+ SinoVoip
SE +/- 0.28, N = 5
279.95
Banana Pi M2+ on Armbian
SE +/- 0.30, N = 5
230.20
DragonBoard 410c on Debian RPB 16.03
SE +/- 2.44, N = 7
198.14
MeUbuntu 14.04.3
SE +/- 0.88, N = 10
36.43
MiQi on Lubuntu 14.04
SE +/- 0.35, N = 5
81.96
NanoPi NEO 2 Armbian Ubuntu 16.04.2
SE +/- 0.03, N = 5
290.91
NanoPi NEO 2 FA Ubuntu 16.04.2
SE +/- 0.19, N = 5
236.51
NanoPi NEO 512MB Heatsink
SE +/- 0.31, N = 5
231.39
NanoPi NEO 512MB Heatsink2
SE +/- 0.14, N = 5
230.99
NanoPi NEO 512MB No Heatsink
SE +/- 2.55, N = 5
325.72
Orange Pi One on Armbian
SE +/- 0.16, N = 5
229.54
Orange Pi PC on Armbian
SE +/- 1.01, N = 5
228.09
Orange Pi Plus on Armbian
SE +/- 1.46, N = 5
231.38
Raspberry Pi 2 on Raspbian
SE +/- 1.30, N = 5
314.58
Raspberry Pi 3 on Raspbian
SE +/- 1.73, N = 5
237.30
VS-RK3399 Board - Debian 9
SE +/- 0.05, N = 5
48.84
test3
SE +/- 0.05, N = 5
38.34
70
140
210
280
350
1. (CXX) g++ options: -O2 -fvisibility=hidden -lm



Himeno Benchmark 3.0
Poisson Pressure Solver
MFLOPS, More Is Better
Banana Pi M2 by LoveRPi
SE +/- 0.08, N = 3
61.26
Banana Pi M2+ Raspbian 8.0
SE +/- 0.53, N = 3
63.04
Banana Pi M2+ SinoVoip
SE +/- 0.46, N = 3
56.83
Banana Pi M2+ on Armbian
SE +/- 0.37, N = 3
64.35
Banana Pi M3 by LoveRPi
SE +/- 0.49, N = 3
31.80
DragonBoard 410c on Debian RPB 16.03
SE +/- 0.47, N = 3
66.91
MeUbuntu 14.04.3
SE +/- 2.37, N = 3
443.65
MiQi on Lubuntu 14.04
SE +/- 1.56, N = 3
89.84
NanoPi NEO 2 Armbian Ubuntu 16.04.2
SE +/- 0.21, N = 3
49.18
NanoPi NEO 2 FA Ubuntu 16.04.2
SE +/- 1.76, N = 6
52.67
NanoPi NEO 512MB Heatsink
SE +/- 0.05, N = 3
15.34
NanoPi NEO 512MB Heatsink2
SE +/- 0.16, N = 3
15.31
NanoPi NEO 512MB No Heatsink
SE +/- 0.06, N = 3
41.32
Orange Pi One on Armbian
SE +/- 0.16, N = 3
64.38
Orange Pi PC on Armbian
SE +/- 0.32, N = 3
68.23
Orange Pi Plus on Armbian
SE +/- 0.04, N = 3
68.01
Raspberry Pi 2 on Raspbian
SE +/- 0.47, N = 3
33.29
Raspberry Pi 3 on Raspbian
SE +/- 0.37, N = 3
60.28
VS-RK3399 Board - Debian 9
SE +/- 0.80, N = 3
195.30
test3
SE +/- 16.59, N = 12
304.70
100
200
300
400
500
1. (CC) gcc options: -O3


Himeno Benchmark 3.0
Performance / Cost - Poisson Pressure Solver
MFLOPS Per Dollar, More Is Better
Banana Pi M2 by LoveRPi
1.36
Banana Pi M3 by LoveRPi
0.40
Orange Pi One on Armbian
6.44
Orange Pi PC on Armbian
4.55
Orange Pi Plus on Armbian
1.74
Raspberry Pi 3 on Raspbian
1.72
2
4
6
8
10
1. Banana Pi M2 by LoveRPi: $45 reported cost.
2. Banana Pi M3 by LoveRPi: $80 reported cost.
3. Orange Pi One on Armbian: $10 reported cost.
4. Orange Pi PC on Armbian: $15 reported cost.
5. Orange Pi Plus on Armbian: $39 reported cost.
6. Raspberry Pi 3 on Raspbian: $35 reported cost.


John The Ripper 1.8.0
Test: Blowfish
Real C/S, More Is Better
Banana Pi M2 by LoveRPi
SE +/- 0.33, N = 3
438
Banana Pi M2+ Raspbian 8.0
SE +/- 1.45, N = 3
323
Banana Pi M2+ SinoVoip
SE +/- 1.55, N = 4
104
Banana Pi M2+ on Armbian
SE +/- 22.63, N = 6
390
Banana Pi M3 by LoveRPi
SE +/- 5.24, N = 3
1408
DragonBoard 410c on Debian RPB 16.03
SE +/- 24.47, N = 6
535
MeUbuntu 14.04.3
SE +/- 83.72, N = 6
1003
MiQi on Lubuntu 14.04
SE +/- 1.00, N = 3
1055
NanoPi NEO 2 Armbian Ubuntu 16.04.2
478
NanoPi NEO 2 FA Ubuntu 16.04.2
SE +/- 1.53, N = 3
456
NanoPi NEO 512MB Heatsink
SE +/- 7.33, N = 3
462
NanoPi NEO 512MB Heatsink2
SE +/- 6.98, N = 3
452
NanoPi NEO 512MB No Heatsink
SE +/- 11.64, N = 6
313
Orange Pi One on Armbian
SE +/- 0.33, N = 3
509
Orange Pi PC on Armbian
SE +/- 0.00, N = 3
550
Orange Pi Plus on Armbian
SE +/- 0.00, N = 3
540
Raspberry Pi 2 on Raspbian
SE +/- 0.67, N = 3
387
Raspberry Pi 3 on Raspbian
SE +/- 2.19, N = 3
599
VS-RK3399 Board - Debian 9
SE +/- 14.50, N = 3
759
test3
SE +/- 4.70, N = 3
1714
400
800
1200
1600
2000
1. (CC) gcc options: -fopenmp

John The Ripper 1.8.0


Performance / Cost - Test: Blowfish




1. Banana Pi M2 by LoveRPi: $45 reported cost.
2. Banana Pi M3 by LoveRPi: $80 reported cost.
3. Orange Pi One on Armbian: $10 reported cost.
4. Orange Pi PC on Armbian: $15 reported cost.
5. Orange Pi Plus on Armbian: $39 reported cost.
6. Raspberry Pi 3 on Raspbian: $35 reported cost.


Meta Performance Per Dollar


Performance Per Dollar




1. Banana Pi M2 by LoveRPi: $45 reported cost. Average result: 170.89.
2. Banana Pi M3 by LoveRPi: $80 reported cost. Average result: 494.37.
3. Orange Pi One on Armbian: $10 reported cost. Average result: 196.46.
4. Orange Pi PC on Armbian: $15 reported cost. Average result: 211.81.
5. Orange Pi Plus on Armbian: $39 reported cost. Average result: 208.38.
6. Raspberry Pi 3 on Raspbian: $35 reported cost. Average result: 226.63.


OpenSSL 1.0.1g
RSA 4096-bit Performance
Signs Per Second, More Is Better
Banana Pi M2 by LoveRPi
SE +/- 0.00, N = 3
-march=armv7-a
13.40
Banana Pi M2+ Raspbian 8.0
SE +/- 0.03, N = 3
-march=armv7-a
6.67
Banana Pi M2+ SinoVoip
SE +/- 0.00, N = 3
3.30
Banana Pi M2+ on Armbian
SE +/- 0.61, N = 6
-march=armv7-a
10.48
Banana Pi M3 by LoveRPi
SE +/- 0.50, N = 3
-march=armv7-a
43.30
DragonBoard 410c on Debian RPB 16.03
SE +/- 0.40, N = 6
-fomit-frame-pointer
10.90
MeUbuntu 14.04.3
SE +/- 0.52, N = 3
-m64
66.53
MiQi on Lubuntu 14.04
SE +/- 0.00, N = 3
-march=armv7-a
29.70
NanoPi NEO 512MB Heatsink
SE +/- 0.17, N = 6
-march=armv7-a
12.35
NanoPi NEO 512MB Heatsink2
SE +/- 0.23, N = 6
-march=armv7-a
12.40
NanoPi NEO 512MB No Heatsink
SE +/- 0.58, N = 6
-march=armv7-a
7.68
Orange Pi One on Armbian
SE +/- 0.00, N = 3
-march=armv7-a
16.00
Orange Pi PC on Armbian
SE +/- 0.00, N = 3
-march=armv7-a
17.20
Orange Pi Plus on Armbian
SE +/- 0.03, N = 3
-march=armv7-a
17.13
Raspberry Pi 2 on Raspbian
SE +/- 0.03, N = 3
-march=armv7-a
11.93
Raspberry Pi 3 on Raspbian
SE +/- 0.75, N = 6
-march=armv7-a
20.60
test3
SE +/- 0.20, N = 3
-march=armv7-a
60.50
15
30
45
60
75
1. (CC) gcc options: -O3 -lssl -lcrypto -ldl


OpenSSL 1.0.1g
Performance / Cost - RSA 4096-bit Performance
Signs Per Second Per Dollar, More Is Better
Banana Pi M2 by LoveRPi
0.30
Banana Pi M3 by LoveRPi
0.54
Orange Pi One on Armbian
1.60
Orange Pi PC on Armbian
1.15
Orange Pi Plus on Armbian
0.44
Raspberry Pi 3 on Raspbian
0.59
0.36
0.72
1.08
1.44
1.8
1. Banana Pi M2 by LoveRPi: $45 reported cost.
2. Banana Pi M3 by LoveRPi: $80 reported cost.
3. Orange Pi One on Armbian: $10 reported cost.
4. Orange Pi PC on Armbian: $15 reported cost.
5. Orange Pi Plus on Armbian: $39 reported cost.
6. Raspberry Pi 3 on Raspbian: $35 reported cost.


Smallpt 1.0
Global Illumination Renderer; 100 Samples
Seconds, Fewer Is Better
Banana Pi M2 by LoveRPi
SE +/- 0.58, N = 3
1954
Banana Pi M2+ Raspbian 8.0
SE +/- 7.13, N = 3
3906
Banana Pi M2+ SinoVoip
SE +/- 22.54, N = 3
8127
Banana Pi M2+ on Armbian
SE +/- 0.58, N = 3
2483
Banana Pi M3 by LoveRPi
SE +/- 1.33, N = 3
621
DragonBoard 410c on Debian RPB 16.03
SE +/- 148.98, N = 3
2341
MeUbuntu 14.04.3
SE +/- 0.58, N = 3
620
MiQi on Lubuntu 14.04
SE +/- 2.67, N = 3
866
NanoPi NEO 2 Armbian Ubuntu 16.04.2
SE +/- 0.58, N = 3
1285
NanoPi NEO 2 FA Ubuntu 16.04.2
SE +/- 0.33, N = 3
1308
NanoPi NEO 512MB Heatsink
SE +/- 2.89, N = 3
2134
NanoPi NEO 512MB Heatsink2
SE +/- 1.15, N = 3
2101
NanoPi NEO 512MB No Heatsink
SE +/- 65.74, N = 3
2829
Orange Pi One on Armbian
SE +/- 0.00, N = 3
1665
Orange Pi PC on Armbian
SE +/- 3.51, N = 3
1547
Orange Pi Plus on Armbian
SE +/- 0.67, N = 3
1549
Raspberry Pi 2 on Raspbian
SE +/- 5.90, N = 3
2175
Raspberry Pi 3 on Raspbian
SE +/- 1.86, N = 3
1390
VS-RK3399 Board - Debian 9
SE +/- 9.35, N = 3
679
test3
339
2K
4K
6K
8K
10K
1. (CXX) g++ options: -fopenmp



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 08:35.