

www.phoronix-test-suite.com

2021-04-01-2324

Intel Core i5-4440 testing with a Gigabyte B85-HD3 (F3 BIOS) and Gigabyte Intel Haswell Desktop 2GB on Peppermint 10 via the Phoronix Test Suite.

Test Systems:

Intel Core i5-4440

Processor: Intel Core i5-4440 @ 3.30GHz (4 Cores), Motherboard: Gigabyte B85-HD3 (F3 BIOS), Chipset: Intel 4th Gen Core DRAM, Memory: 2 x 8192 MB DDR3-1333MT/s, Disk: 3 x 6001GB TOSHIBA HDWD260 + 120GB KINGSTON SHFS37A + 16GB USB Flash Drive, Graphics: Gigabyte Intel Haswell Desktop 2GB (1100MHz), Audio: Intel Xeon E3-1200 v3/4th, Network: Realtek RTL8169 PCI


OS: Peppermint 10, Kernel: 5.0.0-37-generic (x86_64), Desktop: LXDE, Display Server: X Server 1.20.4, OpenGL: 4.5 Mesa 19.0.8, Compiler: GCC 7.5.0, File-System: overlayfs, Screen Resolution: 1920x1080

Kernel Notes: Transparent Huge Pages: madvise
Processor Notes: Scaling Governor: intel_pstate performance - CPU Microcode: 0x27 - Thermald 1.7
Java Notes: OpenJDK Runtime Environment (build 11.0.10+9-Ubuntu-0ubuntu1.18.04)

2021-04-01-2324

Security Notes: itlb_multihit: KVM: Mitigation of Split huge pages + l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT disabled + mds: Mitigation of Clear buffers; SMT disabled + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: disabled RSB filling + tsx_async_abort: Not affected

	Intel Core i5-4440
DaCapo Benchmark - H2 (msec)	3923
Standard Deviation	5.1%
DaCapo Benchmark - Jython (msec)	6277



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 21:46.