

www.phoronix-test-suite.com

intel mlc xeon test

Intel Xeon Silver 4216 testing with a TYAN S7100AG2NR (V4.02 BIOS) and ASPEED on Debian 10 via the Phoronix Test Suite.

Automated Executive Summary

1 had the most wins, coming in first place for 54% of the tests.

Based on the geometric mean of all complete results, the fastest (1) was 1.002x the speed of the slowest (2). 3 was 0.999x the speed of 1 and 2 was 0.999x the speed of 3.

Test Systems:

1

2

intel mlc xeon test

3

Processor: Intel Xeon Silver 4216 @ 3.20GHz (16 Cores / 32 Threads), Motherboard: TYAN S7100AG2NR (V4.02 BIOS), Chipset: Intel Sky Lake-E DMI3 Registers, Memory: 24GB, Disk: 240GB Corsair Force MP500, Graphics: ASPEED, Audio: Realtek ALC892, Network: 2 x Intel I350

OS: Debian 10, Kernel: 4.19.0-9-amd64 (x86_64), Desktop: GNOME Shell 3.30.2, Display Server: X Server, Compiler: GCC 8.3.0, File-System: ext4, Screen Resolution: 1024x768


Kernel Notes: Transparent Huge Pages: always
Processor Notes: Scaling Governor: intel_pstate powersave - CPU Microcode: 0x500002c
Security Notes: itlb_multihit: KVM: Mitigation of Split huge pages + l1tf: Not affected + mds: Not affected + meltdown: Not affected + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Enhanced IBRS IBPB: conditional RSB filling + srbds: Not affected + tsx_async_abort: Mitigation of TSX disabled

	1	2	3
Intel Memory Latency Checker - Idle Latency (ns)	**77.9**	**78.2**	78.1
Normalized	100%	99.62%	99.74%
Standard Deviation	0.3%	0.3%	0.8%
Intel Memory Latency Checker - Max Bandwidth - All Reads (MB/s)	**102719**	**101534**	102141
Normalized	100%	98.85%	99.44%
Standard Deviation	0.6%	0%	0.8%
Intel Memory Latency Checker - Max Bandwidth - 3:1 Reads-Writes (MB/s)	**88336**	**86818**	87899
Normalized	100%	98.28%	99.5%
Standard Deviation	0.2%	0%	0.6%
Intel Memory Latency Checker - Max Bandwidth - 2:1 Reads-Writes (MB/s)	**85327**	**84161**	85002
Normalized	100%	98.63%	99.62%
Standard Deviation	0.2%	0.1%	0.5%
Intel Memory Latency Checker - Max Bandwidth - 1:1 Reads-Writes (MB/s)	**73180**	**72935**	73092
Normalized	100%	99.67%	99.88%
Standard Deviation	0%	0.1%	0.1%
Intel Memory Latency Checker - Max Bandwidth - Stream-Triad Like (MB/s)	**90322**	**88625**	89785
Normalized	100%	98.12%	99.41%
Standard Deviation	0.2%	0.1%	0.8%
Intel Memory Latency Checker - P.I.B - All Reads (MB/s)	**100646**	**102650**	101211
Normalized	98.05%	100%	98.6%
Standard Deviation	2%	1.2%	0.7%
Intel Memory Latency Checker - P.I.B - 3:1 Reads-Writes (MB/s)	**87229**	**88032**	87544
Normalized	99.09%	100%	99.45%
Standard Deviation	1%	0.4%	0.4%


intel mlc xeon test

Intel Memory Latency Checker - P.I.B - 2:1 Reads-Writes (MB/s)	**84684**	**85290**	84935
Normalized	99.29%	100%	99.58%
Standard Deviation	0.7%	0.2%	0.2%
Intel Memory Latency Checker - P.I.B - 1:1 Reads-Writes (MB/s)	**72998**	**73169**	73080
Normalized	99.77%	100%	99.88%
Standard Deviation	0.2%	0.1%	0%
Intel Memory Latency Checker - P.I.B - Stream-Triad Like (MB/s)	**80099**	**80543**	80264
Normalized	99.45%	100%	99.65%
Standard Deviation	0.6%	0.2%	0.2%


intel mlc xeon test




intel mlc xeon test



intel mlc xeon test



intel mlc xeon test



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 03:14.