

www.phoronix-test-suite.com

truenas-20210502fio

KVM testing on Ubuntu 20.04 via the Phoronix Test Suite.

Automated Executive Summary

iSCSI Sync L2ARC No ZIL Again had the most wins, coming in first place for 50% of the tests.

The results with the greatest spread from best to worst included:

Flexible IO Tester (Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory) at 12.209x
Flexible IO Tester (Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory) at 12.12x
Flexible IO Tester (Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory) at 11.758x
Flexible IO Tester (Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory) at 11.723x
Flexible IO Tester (Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory) at 8.36x
Flexible IO Tester (Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory) at 8.067x
Flexible IO Tester (Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk

Target: Default Test Directory) at 1.101x
Flexible IO Tester (Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory) at 1.098x
Flexible IO Tester (Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory) at 1.038x
Flexible IO Tester (Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory) at 1.03x.

Test Systems:

iSCSI Sync L2ARC No ZIL

iSCSI Sync L2ARC No ZIL Again

iSCSI Sync L2ARC No ZIL Retry

iSCSI Sync No L2ARC No ZIL

iSCSI Sync ZIL

iSCSI Sync ZIL Take 2

Processor: Common KVM (2 Cores), Motherboard: QEMU Standard PC (i440FX + PIIX 1996) (rel-1.14.0-0-g155821a1990b-prebuilt.qemu.org BIOS), Chipset: Intel 440FX 82441FX PMC, Memory: 2048MB, Disk: 34GB QEMU HDD + 3427GB iSCSI Disk, Graphics: bochs-drmdrmfb, Monitor: QEMU Monitor, Network: 2 x Red Hat Virtio device

OS: Ubuntu 20.04, Kernel: 5.4.0-72-generic (x86_64), Compiler: GCC 9.3.0, File-System: ext4, Screen Resolution: 1024x768, System Layer: KVM

Kernel Notes: Transparent Huge Pages: madvise
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++,gm2 --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none=/build/gcc-9-HskZEa/gcc-9-9.3.0/debian/tmp-nvptx/usr,hsa --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib=auto --with-tune=generic --without-cuda-driver -v
Disk Notes: MQ-DEADLINE / noatime,rw,stripe=256 / Block Size: 4096
Processor Notes: CPU Microcode: 0x1
Security Notes: itlb_multihit: KVM: Vulnerable + l1tf: Mitigation of PTE Inversion + mds: Vulnerable: Clear buffers attempted no microcode; SMT Host state unknown + meltdown: Mitigation of PTI + spec_store_bypass: Vulnerable + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline STIBP: disabled RSB filling + srbds: Not affected + tsx_async_abort: Not affected

truenas-20210502fio

	iSCSI Sync L2ARC No ZIL	iSCSI Sync L2ARC No ZIL Again	iSCSI Sync L2ARC No ZIL Retry	iSCSI Sync No L2ARC No ZIL	iSCSI Sync ZIL	iSCSI Sync ZIL Take 2
Flexible IO Tester - Rand Read - Sync - Yes - No - 1MB	191					
Flexible IO Tester - Rand Read - Sync - Yes - No - 1MB (IOPS)	191					
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 1MB (MB/s)		**3.096**	4.616	9.494	**115.2**	
Normalized		2.69%	4.01%	8.24%	100%	
Standard Deviation		17.2%	57.9%	22.2%	150.2%	
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 1MB (IOPS)		**1**	3	7	**112**	
Normalized		0.89%	2.68%	6.25%	100%	
Standard Deviation			94.3%	37.8%	154.6%	
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 4KB (MB/s)		**101**		**101**	98.1	**86.5**
Normalized		100%		100%	97.13%	85.64%
Standard Deviation		2.6%		1.1%	5.2%	13.1%
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 4KB (IOPS)		**25867**		25800	25133	**22233**
Normalized		100%		99.74%	97.16%	85.95%
Standard Deviation		2.6%		1.3%	5.3%	12.7%
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 16KB (MB/s)		**212**		218	**220**	
Normalized		96.36%		99.09%	100%	
Standard Deviation		1.5%		3.1%	1.3%	
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 16KB (IOPS)		**13533**		**13933**	13700	
Normalized		97.13%		100%	98.33%	
Standard Deviation		1.5%		2.7%	4.6%	
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 64KB (MB/s)		**229**			**162**	
Normalized		100%			70.74%	
Standard Deviation		2.1%			24.6%	
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 64KB (IOPS)		**3657**			**2588**	
Normalized		100%			70.77%	
Standard Deviation		2%			24.5%	

truenas-20210502fio

Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 1MB (MB/s)	**839**	**104**	279	
Normalized	100%	12.4%	33.25%	
Standard Deviation	3.2%	1%	3.3%	
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 1MB (IOPS)	**836**	**100**	275	
Normalized	100%	11.96%	32.89%	
Standard Deviation	3.3%	1.2%	3.5%	
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 4KB (MB/s)	74.4	**7.625**	**75.0**	74.6
Normalized	99.2%	10.17%	100%	99.47%
Standard Deviation	17.7%	7%	5.1%	8.7%
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 4KB (IOPS)	19000	**1902**	**19200**	19167
Normalized	98.96%	9.91%	100%	99.83%
Standard Deviation	17.8%	7%	5%	8.9%
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 16KB (MB/s)	**223**	**18.4**	200	
Normalized	100%	8.25%	89.69%	
Standard Deviation	0.9%	0.5%	1.3%	
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 16KB (IOPS)	**14333**	**1174**	12767	
Normalized	100%	8.19%	89.07%	
Standard Deviation	0.8%	0.7%	1.2%	
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 64KB (MB/s)	**459**		**263**	
Normalized	100%		57.3%	
Standard Deviation	57%		1.3%	
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 64KB (IOPS)	**7343**		**4205**	
Normalized	100%		57.27%	
Standard Deviation	57%		1.2%	
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 1MB (MB/s)	12.494	**277.104**	**9.522**	
Normalized	4.51%	100%	3.44%	
Standard Deviation	65.1%	168.4%	15%	
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 1MB (IOPS)	9	**274**	**7**	
Normalized	3.28%	100%	2.55%	
Standard Deviation	91.1%	170%	20.8%	

truenas-20210502fio


Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 4KB (MB/s)	**132**	140	**145**	143
Normalized	91.03%	96.55%	100%	98.62%
Standard Deviation		0.7%	2.4%	2.8%
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 4KB (IOPS)	**33667**	35933	**37067**	36533
Normalized	90.83%	96.94%	100%	98.56%
Standard Deviation	2.4%	0.7%	2.6%	3%
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 16KB (MB/s)	**189**	227	**243**	
Normalized	77.78%	93.42%	100%	
Standard Deviation	22.5%	3.3%	1.4%	
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 16KB (IOPS)	**12086**	14500	**15533**	
Normalized	77.81%	93.35%	100%	
Standard Deviation	22.4%	3.6%	1.3%	
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 64KB (MB/s)	**23.9**		**5.220**	
Normalized	100%		21.84%	
Standard Deviation	32.9%		47.5%	
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 64KB (IOPS)	**379**		**78**	
Normalized	100%		20.58%	
Standard Deviation	33.3%		49.4%	
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 1MB (MB/s)	**560**	**99.0**	274	
Normalized	100%	17.68%	48.93%	
Standard Deviation	69.5%	8.9%	4.1%	
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 1MB (IOPS)	**556**	**95**	271	
Normalized	100%	17.09%	48.74%	
Standard Deviation	69.9%	9.2%	4.4%	
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 4KB (MB/s)	**115**	**9.81**	80.4	82.2
Normalized	100%	8.53%	69.91%	71.48%
Standard Deviation	4.9%	0.4%	1.8%	2.7%
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 4KB (IOPS)	**29500**	**2509**	20233	21033
Normalized	100%	8.51%	68.59%	71.3%
Standard Deviation	4.8%	0.4%	1%	2.7%

Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 16KB (MB/s)	**349**	**22.9**	199
Normalized	100%	6.56%	57.02%
Standard Deviation	9.8%	1.1%	
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 16KB (IOPS)	**22367**	**1460**	12700
Normalized	100%	6.53%	56.78%
Standard Deviation	9.9%	1.3%	
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 64KB (MB/s)	**446**		**248**
Normalized	100%		55.61%
Standard Deviation	52.8%		1.2%
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 64KB (IOPS)	**7134**		**3962**
Normalized	100%		55.54%
Standard Deviation	53%		1.3%
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 32KB (MB/s)		226	
Standard Deviation		2.3%	
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 32KB (IOPS)		7234	
Standard Deviation		2.4%	
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 32KB (MB/s)		19.3	
Standard Deviation		3.6%	
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 32KB (IOPS)		614	
Standard Deviation		3.6%	
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 32KB (MB/s)		49.2	
Standard Deviation		94%	
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 32KB (IOPS)		1570	
Standard Deviation		94.1%	
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 32KB (MB/s)		26.9	
Standard Deviation		0.4%	

Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 32KB (IOPS)	858	
Standard Deviation	0.4%	
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 2MB (MB/s)		9.526
Standard Deviation		31.3%
Flexible IO Tester - Rand Read - Linux AIO - No - Yes - 2MB (IOPS)		3
Standard Deviation		43.3%
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 2MB (MB/s)		280
Standard Deviation		0.9%
Flexible IO Tester - Rand Write - Linux AIO - No - Yes - 2MB (IOPS)		137
Standard Deviation		0.8%
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 2MB (MB/s)		12.26
Standard Deviation		20.2%
Flexible IO Tester - Seq Read - Linux AIO - No - Yes - 2MB (IOPS)		4
Standard Deviation		25%
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 2MB (MB/s)		279
Standard Deviation		2%
Flexible IO Tester - Seq Write - Linux AIO - No - Yes - 2MB (IOPS)		136
Standard Deviation		1.9%

Flexible IO Tester 3.25


Type: Random Read - Engine: Sync - Buffered: Yes - Direct: No - Block Size: 1MB - Disk Target: Default Test Directory



1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native

Flexible IO Tester 3.25


Type: Random Read - Engine: Sync - Buffered: Yes - Direct: No - Block Size: 1MB - Disk Target: Default Test Directory




1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native


Flexible IO Tester 3.25


Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory





1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 100.00, N = 3
112
iSCSI Sync No L2ARC No ZIL
SE +/- 1.53, N = 3
7
iSCSI Sync L2ARC No ZIL Retry
SE +/- 2.00, N = 2
3
iSCSI Sync L2ARC No ZIL Again
1
30
60
90
120
150
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 6.54, N = 3
86.5
iSCSI Sync ZIL
SE +/- 2.96, N = 3
98.1
iSCSI Sync No L2ARC No ZIL
SE +/- 0.67, N = 3
101.0
iSCSI Sync L2ARC No ZIL Again
SE +/- 1.53, N = 3
101.0
20
40
60
80
100
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 1634.35, N = 3
22233
iSCSI Sync ZIL
SE +/- 775.31, N = 3
25133
iSCSI Sync No L2ARC No ZIL
SE +/- 200.00, N = 3
25800
iSCSI Sync L2ARC No ZIL Again
SE +/- 384.42, N = 3
25867
6K
12K
18K
24K
30K
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 1.67, N = 3
220
iSCSI Sync No L2ARC No ZIL
SE +/- 3.84, N = 3
218
iSCSI Sync L2ARC No ZIL Again
SE +/- 1.86, N = 3
212
50
100
150
200
250
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 360.56, N = 3
13700
iSCSI Sync No L2ARC No ZIL
SE +/- 218.58, N = 3
13933
iSCSI Sync L2ARC No ZIL Again
SE +/- 120.19, N = 3
13533
3K
6K
9K
12K
15K
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 64KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 23.03, N = 3
162
iSCSI Sync L2ARC No ZIL Again
SE +/- 2.73, N = 3
229
50
100
150
200
250
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 64KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 365.33, N = 3
2588
iSCSI Sync L2ARC No ZIL Again
SE +/- 42.36, N = 3
3657
800
1600
2400
3200
4000
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 5.36, N = 3
279
iSCSI Sync No L2ARC No ZIL
SE +/- 0.58, N = 3
104
iSCSI Sync L2ARC No ZIL Again
SE +/- 15.39, N = 3
839
200
400
600
800
1000
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 5.57, N = 3
275
iSCSI Sync No L2ARC No ZIL
SE +/- 0.67, N = 3
100
iSCSI Sync L2ARC No ZIL Again
SE +/- 15.72, N = 3
836
200
400
600
800
1000
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 3.755, N = 3
74.600
iSCSI Sync ZIL
SE +/- 2.198, N = 3
75.000
iSCSI Sync No L2ARC No ZIL
SE +/- 0.307, N = 3
7.625
iSCSI Sync L2ARC No ZIL Again
SE +/- 7.593, N = 3
74.400
20
40
60
80
100
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 983.76, N = 3
19167
iSCSI Sync ZIL
SE +/- 550.76, N = 3
19200
iSCSI Sync No L2ARC No ZIL
SE +/- 76.59, N = 3
1902
iSCSI Sync L2ARC No ZIL Again
SE +/- 1951.92, N = 3
19000
4K
8K
12K
16K
20K
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 1.45, N = 3
200.0
iSCSI Sync No L2ARC No ZIL
SE +/- 0.06, N = 3
18.4
iSCSI Sync L2ARC No ZIL Again
SE +/- 1.20, N = 3
223.0
50
100
150
200
250
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 88.19, N = 3
12767
iSCSI Sync No L2ARC No ZIL
SE +/- 4.67, N = 3
1174
iSCSI Sync L2ARC No ZIL Again
SE +/- 66.67, N = 3
14333
3K
6K
9K
12K
15K
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 64KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 2.00, N = 3
263
iSCSI Sync L2ARC No ZIL Again
SE +/- 150.96, N = 3
459
100
200
300
400
500
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 64KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 29.24, N = 3
4205
iSCSI Sync L2ARC No ZIL Again
SE +/- 2416.02, N = 3
7343
1600
3200
4800
6400
8000
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 0.823, N = 3
9.522
iSCSI Sync No L2ARC No ZIL
SE +/- 269.452, N = 3
277.104
iSCSI Sync L2ARC No ZIL Again
SE +/- 4.699, N = 3
12.494
60
120
180
240
300
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 0.88, N = 3
7
iSCSI Sync No L2ARC No ZIL
SE +/- 269.34, N = 3
274
iSCSI Sync L2ARC No ZIL Again
SE +/- 4.91, N = 3
9
60
120
180
240
300
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 2.33, N = 3
143
iSCSI Sync ZIL
SE +/- 2.00, N = 3
145
iSCSI Sync No L2ARC No ZIL
SE +/- 0.58, N = 3
140
iSCSI Sync L2ARC No ZIL Again
132
30
60
90
120
150
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native


Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 638.57, N = 3
36533
iSCSI Sync ZIL
SE +/- 566.67, N = 3
37067
iSCSI Sync No L2ARC No ZIL
SE +/- 145.30, N = 3
35933
iSCSI Sync L2ARC No ZIL Again
SE +/- 466.67, N = 3
33667
8K
16K
24K
32K
40K
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 2.03, N = 3
243
iSCSI Sync No L2ARC No ZIL
SE +/- 4.33, N = 3
227
iSCSI Sync L2ARC No ZIL Again
SE +/- 24.50, N = 3
189
50
100
150
200
250
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 120.19, N = 3
15533
iSCSI Sync No L2ARC No ZIL
SE +/- 300.00, N = 3
14500
iSCSI Sync L2ARC No ZIL Again
SE +/- 1564.60, N = 3
12086
3K
6K
9K
12K
15K
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native


Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 64KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 1.432, N = 3
5.220
iSCSI Sync L2ARC No ZIL Again
SE +/- 4.535, N = 3
23.900
6
12
18
24
30
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 64KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 22.36, N = 3
78
iSCSI Sync L2ARC No ZIL Again
SE +/- 72.85, N = 3
379
80
160
240
320
400
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 6.51, N = 3
274.0
iSCSI Sync No L2ARC No ZIL
SE +/- 5.07, N = 3
99.0
iSCSI Sync L2ARC No ZIL Again
SE +/- 224.87, N = 3
560.0
120
240
360
480
600
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



Flexible IO Tester 3.25
Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 1MB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 6.84, N = 3
271
iSCSI Sync No L2ARC No ZIL
SE +/- 5.03, N = 3
95
iSCSI Sync L2ARC No ZIL Again
SE +/- 224.55, N = 3
556
120
240
360
480
600
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 1.29, N = 3
82.20
iSCSI Sync ZIL
SE +/- 0.83, N = 3
80.40
iSCSI Sync No L2ARC No ZIL
SE +/- 0.02, N = 3
9.81
iSCSI Sync L2ARC No ZIL Again
SE +/- 3.28, N = 3
115.00
30
60
90
120
150
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native


Flexible IO Tester 3.25
Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 4KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 328.30, N = 3
21033
iSCSI Sync ZIL
SE +/- 120.19, N = 3
20233
iSCSI Sync No L2ARC No ZIL
SE +/- 5.46, N = 3
2509
iSCSI Sync L2ARC No ZIL Again
SE +/- 818.54, N = 3
29500
6K
12K
18K
24K
30K
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
199.0
iSCSI Sync No L2ARC No ZIL
SE +/- 0.15, N = 3
22.9
iSCSI Sync L2ARC No ZIL Again
SE +/- 19.78, N = 3
349.0
80
160
240
320
400
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 16KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
12700
iSCSI Sync No L2ARC No ZIL
SE +/- 10.58, N = 3
1460
iSCSI Sync L2ARC No ZIL Again
SE +/- 1273.23, N = 3
22367
5K
10K
15K
20K
25K
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native


Flexible IO Tester 3.25
Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 64KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL
SE +/- 1.73, N = 3
248
iSCSI Sync L2ARC No ZIL Again
SE +/- 136.06, N = 3
446
100
200
300
400
500
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 64KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL
SE +/- 29.75, N = 3
3962
iSCSI Sync L2ARC No ZIL Again
SE +/- 2183.99, N = 3
7134
1500
3000
4500
6000
7500
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 32KB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync No L2ARC No ZIL
SE +/- 3.06, N = 3
226
50
100
150
200
250
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 32KB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync No L2ARC No ZIL
SE +/- 101.33, N = 3
7234
1600
3200
4800
6400
8000
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native

Flexible IO Tester 3.25


Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 32KB - Disk Target: Default Test Directory



1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native

Flexible IO Tester 3.25


Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 32KB - Disk Target: Default Test Directory



1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native

Flexible IO Tester 3.25


Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 32KB - Disk Target: Default Test Directory



1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native

Flexible IO Tester 3.25


Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 32KB - Disk Target: Default Test Directory



1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native

Flexible IO Tester 3.25


Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 32KB - Disk Target: Default Test Directory



1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native

Flexible IO Tester 3.25


Type: Sequential Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 32KB - Disk Target: Default Test Directory



1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native

Flexible IO Tester 3.25


Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 2MB - Disk Target: Default Test Directory




1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native


Flexible IO Tester 3.25

Type: Random Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 2MB - Disk Target: Default Test Directory



1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native


Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 2MB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 1.53, N = 3
280
60
120
180
240
300
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Random Write - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 2MB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 0.67, N = 3
137
30
60
90
120
150
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 2MB - Disk Target: Default Test Directory
MB/s, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 1.43, N = 3
12.26
3
6
9
12
15
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native
Flexible IO Tester 3.25
Type: Sequential Read - Engine: Linux AIO - Buffered: No - Direct: Yes - Block Size: 2MB - Disk Target: Default Test Directory
IOPS, More Is Better
iSCSI Sync ZIL Take 2
SE +/- 0.58, N = 3
4
0.9
1.8
2.7
3.6
4.5
1. (CC) gcc options: -rdynamic -lrt -lpthread -lm -ldl -laio -std=gnu99 -ffast-math -include -O3 -fcommon -U_FORTIFY_SOURCE -march=native



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 05:54.