

www.phoronix-test-suite.com

test logs

AMD Ryzen 9 5950X 16-Core testing with a ASUS ROG CROSSHAIR VIII HERO (WI-FI) (3302 BIOS) and AMD Radeon RX 5600 OEM/5600 XT / 5700/5700 8GB on Ubuntu 20.10 via the Phoronix Test Suite.

Test Systems:

1


Processor: AMD Ryzen 9 5950X 16-Core @ 3.40GHz (16 Cores / 32 Threads), Motherboard: ASUS ROG CROSSHAIR VIII HERO (WI-FI) (3302 BIOS), Chipset: AMD Starship/Matisse, Memory: 32GB, Disk: 2000GB Corsair Force MP600, Graphics: AMD Radeon RX 5600 OEM/5600 XT / 5700/5700 8GB (2100/875MHz), Audio: AMD Navi 10 HDMI Audio, Monitor: ASUS MG28U, Network: Realtek RTL8125 2.5GbE + Intel I211 + Intel Wi-Fi 6 AX200

OS: Ubuntu 20.10, Kernel: 5.12.0-051200daily20210503-generic (x86_64), Desktop: GNOME Shell 3.38.2, Display Server: X Server 1.20.9, OpenGL: 4.6 Mesa 21.2.0-devel (git-55fb941 2021-04-16 groovy-oibaf-ppa) (LLVM 12.0.0), Vulkan: 1.2.168, Compiler: GCC 10.2.0, File-System: ext4, Screen Resolution: 3840x2160

Kernel Notes: Transparent Huge Pages: madvise
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-checking=release --enable-clocale=gnu --enable-default-pie

--enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++,m2 --enable-libphobos-checking=release --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none=/build/gcc-10-JvwpWM/gcc-10-10.2.0/debian/tmp-nvptx/usr,amdgcn-amdhsa=/build/gcc-10-JvwpWM/gcc-10-10.2.0/debian/tmp-gcn/usr,hsa --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib=auto --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: acpi-cpufreq schedutil (Boost: Enabled) - CPU Microcode: 0xa201009
Security Notes: itlb_multihit: Not affected + l1tf: Not affected + mds: Not affected + meltdown: Not affected + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full AMD retpoline IBPB: conditional IBRS_FW STIBP: always-on RSB filling + srbds: Not affected + tsx_async_abort: Not affected

1
Opus Codec Encoding - WAV To Opus Encode (sec) 6.116
Standard Deviation 1%



This file was automatically generated via the Phoronix Test Suite benchmarking software on Friday, 29 March 2024 01:34.