

www.phoronix-test-suite.com

ram_memtryit_3200

Intel Core i5-8500 testing with a MSI Z370-A PRO (MS-7B48) v1.0 (2.D2 BIOS) and MSI NVIDIA GeForce GTX 1060 6GB on ManjaroLinux 21.1.5 via the Phoronix Test Suite.

Test Systems:

ram_memtryit_3200

Processor: Intel Core i5-8500 @ 4.10GHz (6 Cores), Motherboard: MSI Z370-A PRO (MS-7B48) v1.0 (2.D2 BIOS), Chipset: Intel 8th Gen Core, Memory: 16GB, Disk: 512GB ADATA SX8200PNP + 120GB KINGSTON SA400S3 + 2000GB Seagate ST2000DM006-2DM1, Graphics: MSI NVIDIA GeForce GTX 1060 6GB, Audio: Realtek ALC892, Monitor: ACER V243H, Network: Realtek RTL8111/8168/8411

OS: ManjaroLinux 21.1.5, Kernel: 5.14.10-1-MANJARO (x86_64), Desktop: Xfce 4.16, Display Server: X Server 1.20.13, Display Driver: NVIDIA 470.63.01, OpenGL: 4.6.0 NVIDIA 470.63.01, Compiler: GCC 11.1.0, File-System: btrfs, Screen Resolution: 1920x1080


Kernel Notes: Transparent Huge Pages: madvise
Processor Notes: Scaling Governor: intel_pstate powersave - CPU Microcode: 0xea

ram_memtryit_3200


Security Notes: itlb_multihit: KVM: Mitigation of VMX disabled + l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT disabled + mds: Mitigation of Clear buffers; SMT disabled + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: disabled RSB filling + srbds: Mitigation of Microcode + tsx_async_abort: Mitigation of TSX disabled

	ram_memtryit_3200
Intel Memory Latency Checker - P.I.B - Stream-Triad Like (MB/s)	35812
Standard Deviation	0.1%
Intel Memory Latency Checker - P.I.B - 1:1 Reads-Writes (MB/s)	30224
Standard Deviation	0.1%
Intel Memory Latency Checker - P.I.B - 2:1 Reads-Writes (MB/s)	33937
Standard Deviation	0.1%
Intel Memory Latency Checker - P.I.B - 3:1 Reads-Writes (MB/s)	35655
Standard Deviation	0.1%
Intel Memory Latency Checker - P.I.B - All Reads (MB/s)	44667
Standard Deviation	0%
Intel Memory Latency Checker - Max Bandwidth - Stream-Triad Like (MB/s)	36729
Standard Deviation	0.2%
Intel Memory Latency Checker - Max Bandwidth - 1:1 Reads-Writes (MB/s)	30253
Standard Deviation	0%
Intel Memory Latency Checker - Max Bandwidth - 2:1 Reads-Writes (MB/s)	34627
Standard Deviation	0%
Intel Memory Latency Checker - Max Bandwidth - 3:1 Reads-Writes (MB/s)	36751
Standard Deviation	0%
Intel Memory Latency Checker - Max Bandwidth - All Reads (MB/s)	44663
Standard Deviation	0.1%
Intel Memory Latency Checker - Idle Latency (ns)	25.3
Standard Deviation	0.8%

ram_memtryit_3200



ram_memtryit_3200



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 06:27.