

www.phoronix-test-suite.com

jungleboy211110

Intel Core i5-8400 testing with a ASRock H310M-HDV (P1.40 BIOS) and Intel CometLake-S GT2 [UHD 630] 6GB on Ubuntu 21.10 via the Phoronix Test Suite.

Test Systems:

jungleboy211110_MD5

Processor: Intel Core i5-8400 @ 4.00GHz (6 Cores), Motherboard: ASRock H310M-HDV (P1.40 BIOS), Chipset: Intel Cannon Lake PCH, Memory: 16GB, Disk: 256GB ADATA SU800 + 2000GB Western Digital WD20PURZ-85G, Graphics: Intel CometLake-S GT2 [UHD 630] 6GB, Audio: Realtek ALC887-VD, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 21.10, Kernel: 5.13.0-21-generic (x86_64), Desktop: GNOME Shell 40.5, Display Server: X Server 1.20.11, Display Driver: NVIDIA, OpenCL: OpenCL 3.0 CUDA 11.4.153, Vulkan: 1.2.182, Compiler: GCC 11.2.0 + CUDA 11.4, File-System: ext4, Screen Resolution: 3840x1080

Kernel Notes: Transparent Huge Pages: madvise
Processor Notes: Scaling Governor: intel_pstate powersave - CPU Microcode: 0xea - Thermald 2.4.6
Graphics Notes: BAR1 / Visible vRAM Size: 256 MiB

Security Notes: itlb_multihit: KVM: Mitigation of VMX disabled + l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT disabled + mds: Mitigation of Clear buffers; SMT disabled + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: disabled RSB filling + srbds: Mitigation of Microcode + tsx_async_abort: Not affected

jungleboy211110_SHA1


Processor: Intel Core i5-8400 @ 4.00GHz (6 Cores), Motherboard: ASRock H310M-HDV (P1.40 BIOS), Chipset: Intel Cannon Lake PCH, Memory: 16GB, Disk: 256GB ADATA SU800 + 2000GB Western Digital WD20PURZ-85G, Graphics: Intel CometLake-S GT2 [UHD 630] 6GB, Audio: Realtek ALC887-VD, Network: Realtek RTL8111/8168/8411

OS: Ubuntu 21.10, Kernel: 5.13.0-21-generic (x86_64), Desktop: GNOME Shell 40.5, Display Server: X Server 1.20.11, Display Driver: NVIDIA, OpenGL: 4.6 Mesa 21.2.2, OpenCL: OpenCL 3.0 CUDA 11.4.153, Vulkan: 1.2.182, Compiler: GCC 11.2.0 + CUDA 11.4, File-System: ext4, Screen Resolution: 3840x1080

Kernel Notes: Transparent Huge Pages: madvise
Processor Notes: Scaling Governor: intel_pstate powersave - CPU Microcode: 0xea - Thermald 2.4.6
Graphics Notes: BAR1 / Visible vRAM Size: 256 MiB
Security Notes: itlb_multihit: KVM: Mitigation of VMX disabled + l1tf: Mitigation of PTE Inversion; VMX: conditional cache flushes SMT disabled + mds: Mitigation of Clear buffers; SMT disabled + meltdown: Mitigation of PTI + spec_store_bypass: Mitigation of SSB disabled via prctl and seccomp + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Full generic retpoline IBPB: conditional IBRS_FW STIBP: disabled RSB filling + srbds: Mitigation of Microcode + tsx_async_abort: Not affected

	jungleboy211110_MD5	jungleboy211110_SHA1
Hashcat - MD5 (H/s)	4706933333	
Standard Deviation	0%	
Hashcat - SHA1 (H/s)		1650033333
Standard Deviation		0%

jungleboy211110



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 09:12.