

www.phoronix-test-suite.com

icelake openems

Intel Core i7-1065G7 testing with a Dell 06CDVY (1.0.9 BIOS) and Intel Iris Plus ICL GT2 16GB on Ubuntu 22.04 via the Phoronix Test Suite.

Test Systems:

a

b

c

Processor: Intel Core i7-1065G7 @ 3.90GHz (4 Cores / 8 Threads), Motherboard: Dell 06CDVY (1.0.9 BIOS), Chipset: Intel Ice Lake-LP DRAM, Memory: 16GB, Disk: Toshiba KBG40ZPZ512G NVMe 512GB, Graphics: Intel Iris Plus ICL GT2 16GB (1100MHz), Audio: Realtek ALC289, Network: Intel Ice Lake-LP PCH CNVi WiFi


OS: Ubuntu 22.04, Kernel: 5.18.8-051808-generic (x86_64), Desktop: GNOME Shell 42.2, Display Server: X Server + Wayland, OpenGL: 4.6 Mesa 22.0.1, OpenCL: OpenCL 3.0, Vulkan: 1.3.204, Compiler: GCC 11.3.0, File-System: ext4,

icelake openems

Screen Resolution: 1920x1200

Kernel Notes: Transparent Huge Pages: madvise
Compiler Notes: --build=x86_64-linux-gnu --disable-vtable-verify --disable-werror --enable-bootstrap --enable-cet --enable-checking=release --enable-clocale=gnu --enable-default-pie --enable-gnu-unique-object --enable-languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++,m2 --enable-libphobos-checking=release --enable-libstdcxx-debug --enable-libstdcxx-time=yes --enable-link-serialization=2 --enable-multiarch --enable-multilib --enable-nls --enable-objc-gc=auto --enable-offload-targets=nvptx-none=/build/gcc-11-xKiWfi/gcc-11-11.3.0/debian/tmp-nvptx/usr,amdgcn-amdhsa=/build/gcc-11-xKiWfi/gcc-11-11.3.0/debian/tmp-gcn/usr --enable-plugin --enable-shared --enable-threads=posix --host=x86_64-linux-gnu --program-prefix=x86_64-linux-gnu- --target=x86_64-linux-gnu --with-abi=m64 --with-arch-32=i686 --with-build-config=bootstrap-lto-lean --with-default-libstdcxx-abi=new --with-gcc-major-version-only --with-multilib-list=m32,m64,mx32 --with-target-system-zlib=auto --with-tune=generic --without-cuda-driver -v
Processor Notes: Scaling Governor: intel_pstate powersave (EPP: balance_performance) - CPU Microcode: 0xb2 - Thermald 2.4.9
Python Notes: Python 3.10.6
Security Notes: itlb_multihit: KVM: Mitigation of VMX disabled + l1tf: Not affected + mds: Not affected + meltdown: Not affected + mmio_stale_data: Mitigation of Clear buffers; SMT vulnerable + spec_store_bypass: Mitigation of SSB disabled via prctl + spectre_v1: Mitigation of usercopy/swapgs barriers and __user pointer sanitization + spectre_v2: Mitigation of Enhanced IBRS IBPB: conditional RSB filling + srbds: Mitigation of Microcode + tsx_async_abort: Not affected

	a	b	c
OpenEMS - pyEMS Coupler (MCells/s)	**12.81**	12.49	**11.97**
Normalized	100%	97.5%	93.44%
OpenEMS - o.M (MCells/s)	**37.02**	**36.13**	36.38
Normalized	100%	97.6%	98.27%



This file was automatically generated via the Phoronix Test Suite benchmarking software on Thursday, 28 March 2024 14:12.